MIL-G-51374(EA)
AMENDMENT 1
3 April 1987

MILITARY SPECIFICATION

GRENADE, HAND, RED SMOKE, RS, M48

This amendment forms a part of MIL-G-51374(EA), dated 15 November 1974, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1:

Under "SPECIFICATIONS" "FEDERAL":

Delete "Flat" from "QQ-S-781 - Strapping, Steel, Flat and Seals."

Delete "TT-W-572 - Wood Preservative, Water Repellent."

Under "SPECIFICATIONS" "MILITARY":

Delete "MIL-B-2427 - Boxes, Ammunition Packing; Wood, Nailed."

Add "MIL-B-46506 - Boxes, Ammunition Packing Wood, Wirebound."

PAGE 6

4.4.3.4(b):

Change "Preparation for delivery (Section 5)." to "Packaging (section 5)."

Add to the list of defects "108 Strapping missing or incorrect"

4.4.4.2, line 5: Delete "function, . . . onto a" and substitute "function, the tape over the grenade emission port shall be removed, the grenade armed and thrown at least 50 feet onto a".

AMSC N/A FSC 1330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:58Z
Check the source to verify that this is the current version before use.

PAGE 7

5: Delete "PREPARATION FOR DELIVERY" and substitute "PACKAGING".

5.1, line 1: Delete "Packaging, level A." and substitute "Preservation, level A."

5.2:

Line 2: After "box" add ", Grade A,".

Lines 5-9: Delete "Prior to loading, . . . in MIL-B-2427."

Lines 11-13: Delete the last two sentences in their entirety and substitute "The PPP-B-601 and PPP-B-621 boxes shall be closed and strapped in accordance with the appendix of the applicable box specification. The MIL-B-46506 boxes shall be strapped using 5/8 by 0.020 inch strapping, class 1, type I, finish A or finish B, grade 2; and seals type D, style I or IV, class R, finish B, grade 2 conforming to QQ-S-781. Straps shall be applied straight, at right-angles to the edges of the box, and under sufficient tension to firmly grip the edges of the face board material. Strapping shall be applied before the wires at the closing edges of the box are twisted or looped. Straps shall be placed as near as practicable, but not more than 3 inches from each end edge of the box."

PAGE 8

Add new paragraph 6.7 as follows:

"6.7 International interest. Certain provisions of this specification are the subject of international standardization agreement ABCA - Army Quadripartite Standardization Agreement - 319. When amendment, revision, or cancellation of this specification is proposed which will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accommodations."

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 1330-A305

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:58Z
Check the source to verify that this is the current version before use.