[INCH-POUND]
A-A-2923
September 7, 1995

COMMERCIAL ITEM DESCRIPTION

LIGHT, DESK, INCANDESCENT, FLEXIBLE COLUMN

The General Services Administration has authorized the use of this commercial item description for all Federal agencies.

1. SCOPE

1.1 Scope. This commercial item description (cid) covers flexible arm incandescent, electric desk lights with parabolic-shaped reflectors and either a weighted or screw-clamp base.

2. CLASSIFICATION

2.1 Classification. The desk lights shall be of the following types (see 7.2):

Type I - Light, Desk, weighted base
Type II - Light, Desk, screw-clamp base

3. SALIENT CHARACTERISTICS

3.1 Fire and casualty hazards. Each contractor shall submit proof that the desk lights they propose to supply under this cid conform to the requirements of Underwriters' Laboratories, Inc., Standard No. UL 153. Evidence of conformance with UL 153 shall be the Underwriters' Listing Mark affixed to the light. In lieu of the Underwriters' Listing Mark, the contractor may submit a test report from an independent laboratory, acceptable to the Government, indicating that the desk light conforms to applicable requirements of the published standards, including test methods of UL 153. Compliance with the above preliminary requirements in regard to fire, safety and casualty hazards does not absolve the contractor from complete compliance with the other requirements of this cid in order to secure acceptance of the material or equipment.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor St., Fort Worth, TX 76102

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

3.2 Design.

3.2.1 General. The type I light shall consist of a weighted base and an attached column (see 3.7) supporting at the upper end a lampholder and reflector. The type II light shall conform to the requirements of type I except it shall have a clamp type base.

3.2.2 Electrical rating. The desk light shall be designed for operation on 110-125 volt, 60-cycle alternating current. Maximum lamp wattage rating shall be permanently indicated on the lamp base or reflector.

3.2.3 Size. With the column positioned vertically the light shall be not less than 24 inches nor more than 28 inches high when measured from the bottom of the base along the axis of the column to the farthest point on the rim of the reflector. Flexible tubing of the column shall be of sufficient length to permit at least 8 inches of movement along an arc. The arc shall begin with the lamp rim parallel to the table surface with the light directed on the table surface and end with the lamp rim parallel to the table surface and the light directed on the table surface.

3.2.4 Devices. The light shall be furnished complete with reflector, lampholder, lamp, wiring, switch, and all other devices necessary for operation.

3.3 Construction. The light shall be constructed of metal. Bases, columns, and supports shall be fabricated from one or more of the following: iron, steel, brass, bronze, aluminum, aluminum alloy, zinc alloy, or magnesium alloy. White metal castings (lead base) shall not be used in bases, columns, or supports. Each light shall consist of a metal base with one metal column or other support, on the upper end of which shall be mounted a reflector and reflector housing. The reflector may be integral with the housing or may be separate and enclosed by a housing. The light shall be sufficiently sturdy to withstand without damage, the application of any force or stress to which it will be normally subjected in service and shipment.

3.3.1 Exposed edges. Exposed edges of sheet metal or other metal parts shall be so finished that personal injury due to sharp edges will not occur under any circumstances of usage and handling.

3.3.2 Wiring and splices. The only exposed wiring shall be from the base to the plug connector and shall enter the light through or at the base. All other wiring shall be entirely concealed. All splice connections shall be made with insulated splice connectors in accordance with UL 486.

3.4 Electrical Cord. Each light shall be provided with an electrical cord having an exposed length of not less than 9 feet (2.7 m) with a molded on parallel blade, three wire grounding - type attachment-plug cap. The cord shall be three (3) conductor including equipment grounding conductor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

The cord and its attachment-plug cap shall be in accordance with the applicable requirements of UL 153. The color of the electrical cord shall match the color of the finish (see 3.10).

3.5 Base.

3.5.1 Type I. The base shall have a covering of spun or shaped steel or of zinc ally pressure-cast die casting. The base area and weight shall be sufficient to cause the light to be free standing on a horizontal surface and to prevent the light from overturning when the base is inclined at an angle of 8 degrees from the horizontal in any direction as required by UL 153. A felt pad not less than 0.035 inch (0.9 mm) thick of a color to harmonize with the light finish, shall be cemented to the bottom of the base. Provision shall be made for the cord where it exits the column below the base so that the light base shall not sit directly on the cord and create a stability problem or chafe the cord.

3.5.2 Type II. The base shall be of formed steel or cast iron and shall be equipped with steel mounting screws which will permit opening up to at least 2 inches (3.1 cm). Felt as specified in 3.5.1 shall be permanently affixed to the opposing binding surfaces of the clamp.

3.6 Column. The column shall be metal and shall consist of an upright attached to the base and a flexible arm attached to the upper end of the upright, or it shall consist of a flexible arm attached to the base. The reflector housing shall be attached at the upper end of the column.

3.6.1 Movement of column. Starting with the light on a horizontal surface so that the front and back edges of the reflector housing are in a plane parallel to the surface on which the light rests, the column shall be sufficiently flexible to permit the reflector housing, lampholder, and lamp to be moved vertically upward through an angle of at least 90 degrees. Starting as above, the column shall also permit the reflector housing, lampholder, and lamp to be moved through a horizontal angle of at least 135 degrees. The column shall remain in the position selected along the 8 inches (20.3 cm) of flexibility required by 3.2.3.

3.7 Reflector housing assembly. The reflector housing and reflector shall be metal and shall be securely fastened to the flexible tubing or the lampholder at its upper end. The reflector housing and reflector may be integral or consist of a separate housing and reflector. The size and construction shall permit the insertion and removal of a standard 60 watt medium screw base incandescent bulb. When inserted into the socket, no portion of the lamp shall project beyond the plane of the reflector rim. The reflector shall be parabolic shaped and the plane bounded by the rim shall be essentially circular.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

3.8 Lampholder. The lampholder shall permit easy insertion and removal of the lamp. The lampholder shall be of the "Electrolier" size, shall have a push switch, and shall conform to UL 496.

3.9 Performance. The desk light shall meet all applicable test requirements of UL 153.

3.10 Finish. All surfaces except aluminum reflecting surfaces, shall be covered completely with one or more coats of enamel or by electroplating. Reflecting surfaces other than aluminum shall be white and all other enameled surfaces shall be either smooth or crackle finish of brown, bronze, or gray, as specified (see 7.2). All enameled surfaces shall be free from tears, star marks, crazing, blisters, hairlines, chipping, pinholes, and other irregularities or defects.

3.11 Nameplate. Unless otherwise specified, a nameplate meeting the requirements of UL 153 shall be securely attached to the light in an inconspicuous location.

3.12 Workmanship. The desk lights shall be free from defects which detract from the appearance or which might impair the serviceability. Electrical connections shall be secure, metal joints and seams shall be tight, and all edges shall be rounded or beveled.

3.13 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

3.14 Standard commercial product. The desk light shall, as a minimum, be in accordance with the requirements of this CID and shall be the manufacturer's standard commercial product. A standard commercial product is a product which has been sold or is currently offered for sale on the commercial market through advertisements, manufacturer's catalogs, or brochures, and represents the latest production model.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.

5. QUALITY ASSURANCE PROVISIONS

5.1 Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

6. PACKAGING

6.1 Preservation, packing, and marking. Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES

7.1 Sources of non-Government association documents.

Underwriters Laboratories, Inc. standards are available from Underwriters Laboratories, Inc., 333 Pfingsten Road Northbrook, IL 60062.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number, and date of this commercial item description.
b. Type required (see 2.1).
c. Finish required (see 3.10).
d. Preservation, packing, and marking required.

7.3 National Stock Numbers (NSN's). The following NSN's correspond to this commercial item description.

NSN	Type	Nomenclature
6230-00-643-2076	I	Light, Desk
6230-00-926-1348	II	Light, Desk

MILITARY INTERESTS:

PREPARING ACTIVITY:
GSA - 7FXEE

Review Activity

DGSC - GS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:27Z
Check the source to verify that this is the current version before use.