INCH-POUND

A-A-50189A
December 15, 1993
SUPERSEDING
A-A-50189
December 28, 1988

COMMERCIAL ITEM DESCRIPTION

DISPENSER, ICE, SELF-LEVELING, MOBILE

The General Services Administration has authorized the use of this Commercial Item Description in preference to type I of MIL-D-43593.

1. ABSTRACT

1.1 Abstract. This Commercial Item Description covers mobile, self-leveling ice dispensers.

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The ice dispenser shall be designed to store not less than 175 pounds of ice in cube, cubelet, cracked, or flaked form. The ice dispenser shall be self-leveling and be a manual load and manual dispensing type. The ice dispenser shall keep ice in a frozen state for a period of not less than four hours in an ambient temperature of 90°F, at 55% relative humidity. The dispenser shall be constructed of stainless steel conforming to types 302 or 304 of ASTM A 167; lid construction of plastic shall conform to type I, class H, grade 1 of Federal Specification L-P-390. The push handle shall be constructed of 300 series stainless steel conforming to ASTM A 554. The dispenser shall be provided with wrap-around bumper guards, drain, removable drain pan, and a removable lid. The dispenser shall be mounted on four casters, two of which shall have a brake mechanism. The dispensing storage cabinet, push handle, and self-leveling mechanism shall be constructed of stainless steel. The space between the double-walled bottom and sides of the cabinet shall be filled with insulation or shall be of the

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-WEE, Natick, MA 01760-5018.

AMSC N/A FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

air insulation type. The lid shall be constructed of either stainless steel or plastic and the space within the double wall shall be filled with insulation or shall be of the air insulation type. The insulation shall be fiberglass or expanded polystyrene. Loose fill type insulation shall not be used. The cabinet shall be water tight and shall have an open drain in accordance with the manufacturer's practice. The removable drain pan shall have a drain with petcock or valve. The bumper guard shall be vinyl and be installed around the outer perimeter of the dispensing cabinet. The maximum dimensions of the ice dispenser including casters and handle shall be 31 inches long by 21 inches wide by 35 inches high.

2.1.1 Ozone depleting substances. Class I ozone depleting substances, in accordance with section 602(a) of the Clean Air Act Amendments 1990, 42 USC 7671a(a) as implemented by 40 CRF 82, Protection of Stratospheric Ozone, shall not be used for refrigerant gases, or for any other purpose, or employed in any process associated with the manufacture of any component parts for this item. See 5.6 for additional information.

2.2 Standard compliance. The dispenser shall comply with the NSF International Standard No. 12, ASTM A 167, and ASTM A 554, as applicable.

2.3 Data nameplate ("Government unique" requirement). The ice dispenser shall be furnished with a data nameplate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying, (b) Identification tags, (c) Information not required, and (d) Optional marking information shall not apply. The data nameplate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the ice dispenser by rivets, screws, or welding in such a manner as to meet the applicable NSF International sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

Contract Number
National Stock Number
Procurement Instrument Identification Number
CID Based Part Identification Number (PIN)
Manufacturer's Name, Address, and Telephone Number
Supplier's Name, Address, and Telephone Number (List Only if Different from Manufacturer)
Manufacturer's Model and Serial Number
Government Approved Manual Number (see 5.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the ice dispenser.

2.4 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified using conversion tables

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

contained in the latest revision of Federal Standard No. 376, and all other requirements of this commercial item description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

2.5 Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this commercial item description unless otherwise specified.

2.6 Workmanship. The finished dispensers shall be complete, clean, and free of fabrication marks, scratches, dents, sharp edges, sharp corners, burrs, slivers, or visible evidence of rust. Rivets, when used, shall be tight and the rivet heads and peened ends shall be round and concentric and in full contact with the joined metal surfaces. There shall be no empty rivet holes. Welds shall be clean, continuous, sound, and free of flux, pits, buildups, undercuts, and shall be ground so as to blend with the adjacent surfaces. Spot welds shall be free from pits, burn throughs, and flashes.

3. QUALITY ASSURANCE

3.1 Contractor certification. The contractor shall certify that the product offered meets the salient characteristics and requirements of this commercial item description and except for those Government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace or that had successfully been delivered to the Government on a previous contract or purchase order. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Compliance. Prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the dispenser conforms to the requirements of NSF International Standard No. 12, ASTM A 167 and ASTM A 554, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

3.2.1 NSF International. Acceptable evidence of meeting the requirements of NSF International Standard No. 12 shall be a listing in the current edition of the NSF International "Listing of Food Service Equipment" and display of the NSF International mark on the finished product, or a certified test report from a recognized independent laboratory acceptable to the Government indicating compliance with the applicable NSF International requirement(s).

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export, as specified (see 5.2).

4.2 Commercial.

4.2.1 Commercial packaging. Each ice dispenser shall be cleaned, preserved, and packaged in accordance with ASTM D 3951.

4.2.2 Commercial packing. The ice dispenser shall be packed in accordance with ASTM D 3951.

4.3 Export.

4.3.1 Export packaging. The ice dispenser lids shall be secured in a closed position with filament reinforced pressure-sensitive tape. The ice dispenser shall be cleaned, preserved, and cushioned to afford protection against corrosion, deterioration, and physical damage during shipping and storage.

4.3.2 Export packing. Each ice dispenser shall be packed in a snug-fitting wood-cleated-plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601, or nailed wood box conforming to class 1, style 2 or 4, grade B, type 2 load of PPP-B-621. The contents of each box shall be blocked and braced to prevent movement while the box is in transit. The ice dispenser shall be blocked in a manner to provide approximately 1 inch clearance between the casters and the bottom of the box. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

4.4 Marking (commercial and export). Marking of unit pack and shipping container shall be in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The ice dispenser covered by this commercial item description is intended for storing and manual dispensing of ice in dining facilities.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

5.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this commercial item description.
b. Government approved manual number to be included on data nameplate (see 2.3).
c. Selection of applicable packaging and packing required (see 4.1).

5.3 Sources for documents.

5.3.1 Sources for non-Government association documents.

ASTM A 167 - Stainless and Heat Resisting Chromium-Nickel Steel Plate, Sheet, and Strip
ASTM A 554 - Welded Stainless Steel Mechanical Tubing
ASTM D 3951 - Standard Practice for Commercial Packaging

ASTM documents are available from:

American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187

NSF International Standard No. 12 - Automatic Ice Making Equipment

NSF International documents are available from:

NSF International
3475 Plymouth Road
P.O. Box 130140
Ann Arbor, MI 48113-0140

5.3.2 Source for Government documents. Copies of military and federal documents are available from:

Standardization Documents Order Desk
Building 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.4 "Government unique" requirements. Whenever a "Government unique" requirement is included in the title of a paragraph under "Salient Characteristics", it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

5.5 Ozone depleting substances. For current information about the status of the Environmental Protection Agency's (EPA) Significant New Alternatives Policy (SNAP) program and specific refrigerant alternatives, call the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

Stratospheric Ozone Protection Hotline at (800) 296-1996 or the SNAP Coordinator at (202) 233-9195. For published information see the EPA Stratospheric Ozone Protection, Fact Sheet (EPA-430-F-93-004 dated February 1993) Short List of Alternative Refrigerants and Action Guide (EPA-430-F-93-003), dated February 1993) Cooling & Refrigerating without CFCs.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - SA
Air Force - 99

Review Activities

Army - MD, QM
Air Force - 50, 84
DLA - GS

User Activities

Navy - MC, MS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project 7320-0867

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.