A-A-54287
23 November 1990

COMMERCIAL ITEM DESCRIPTION

SIMULATION, CASUALTY KIT

The General Services Administration has authorized the use of this commercial item description.

This Commercial Item Description covers a casualty simulation kit with sufficiently varied simulation wound moulages, make-up tools and materials, and other accessories to be used for the purpose of class training and mass disaster drills, capable of withstanding repeated use.

Salient Characteristics:

The casualty simulation kit shall contain assorted simulation wound moulages, make-up tools and materials, and accessories required for its use in class training and mass disaster drills in staging "victims" to appear to be bleeding, dirty, in shock, in pain, traumatized, lacerated, and/or burned.

All materials provided in this kit shall be made from commercially accepted materials adequate for the use intended and shall be capable of withstanding repeated use.

Each moulage shall be coated with a durable finish and shall be a life-size model which shall accurately simulate the color of the skin, flesh, bone and tissue of the particular area of the human anatomy it is meant to represent.

The kit shall include strap-on moulage bleeding wounds and stick-on moulage wounds representing compound extremity fractures, various burns, puncture wounds, eviscerations, fractures, flesh wounds, fragment wounds and foreign body protrusions.

The bleeding moulages shall have the capabilty to give the appearance of bleeding by means of simulated blood pumped through simulated blood vessels, located in the moulages. At least 2 straps shall be provided on each bleeding moulage for attachment to a "victim". The necessary reservoirs, pumps,

AMSC N/A FSC 6910

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:32Z
Check the source to verify that this is the current version before use.

adaptors, connecting tubing, and valves to produce a complete, stand-alone, bleeding moulage shall be provided.

All components shall be provided with a durable compartmented carrying case which shall be capable of repeated carefree use. The carrying case shall pass a 50 centimeter drop test onto concrete at any angle without damaging the case or any of the contents. Scuff marks are allowed. The case shall not exceed 24" x 14" x 16" in size. The weight, including all the components in the kit, shall not exceed 30 pounds.

All items in this kit shall be (re)useable even after one year storage in the carrying case.

The plastic moulages shall be capable of withstanding storage conditions of 130°F at 95 percent relative humidity and -20°F. They shall withstand washing in mild soap and warm water with soft wash cloths or sponges, and patting dry with soft dry clothes without becoming damaged or degraded.

The simulated blood shall have the capability of being removed from most clothing by prompt good laundering (except woolen clothes which may become permanently stained).

Literature shall be included which provides brief instructions and a list of kit components with replacement prices.

The moulages shall be identified with name or part number which shall correspond with the literature supplied with the kit. Marking shall withstand many uses and washings.

The kit shall include all the items shown in the following lists in the quantities noted except as follows:

a. The list with heading "STICK ON MOULAGES- FOAM RUBBER OR EQUIVALENT", only 12 different moulage types of the 15 types listed are required.

b. The list with heading "STICK ON MOULAGES- PLASTIC", there shall be at least 48 moulages assorted, no more than 12 or less than 3 selected from the 8 types listed.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:32Z
Check the source to verify that this is the current version before use.

STICK ON MOULAGES- FOAM RUBBER OR EQUIVALENT

Evisceration
Large 3rd Degree Burn
Medium 3rd Degree Burn
Medium 2nd Degree Burn
Multiple Fragment Wound
Large Wide Gash
Gash
Puncture Wound
Large Laceration
Medium Laceration
Foreign Body Protrusion
Compound Fracture Large Bone
Compound Fracture Lower Part of Extremity
Compound Fracture Jaw
Compound Fracture Upper Arm

STICK ON MOULAGES- PLASTIC

Small Flesh Wound
Small Fracture
1st Degree Burn
2nd Degree Burn
3rd Degree Burn
Perforated Wound
Jaw Wound
Large Fracture

QTY BLEEDING STRAP-ON SIMULATED WOUNDS WITH PUMP ASSEMBLY

QTY	
2	Compound Fracture Humerus (Upper Arm)
2	Compound Fracture Tibia (Lower Leg)

MAKE-UP TOOLS

1	Pallete, small plastic, reuseable
1	Spatula, laboratory type
1	Scissors, general surgical, at least 5" long, corrosion resisting
1	Mirror, round, approx. 5 1/2", round, with stand
2	Atomizer, plastic, approx. 8 oz.
1	Measuring cup, plastic or aluminum, graduated, 16 oz.
9	Depressores, tongue, wood, straight

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:32Z
Check the source to verify that this is the current version before use.

9	Cotton balls, absorbent, approx. 1" or larger in diameter
9	Tissues, facial
9	Cotton tipped applicators

MAKE-UP ACCESSORIES

2	Plastex, Mortician's Wax, 6 oz.
2	Adhesive for Stick-On Wounds, 2 oz.
3	Blood, Powder, Simulated - to make three gallons of Simulated Blood (total)
2	Coagulant Make-Up, Simulated Blood, 4 oz.
1	Methyl Cellulose for Thickening Simulated Blood
2	Plexiglass for Simulated "Glass in Wound"
3	Latex Compound, 1 oz.
2	Fake dirt, 2 oz., make-up grade
4	Tape, Pressure Sensitive, Transparent, 1" x 20 yards total, Johnson & Johnson Dermiclear or equivalent
2	Duco Cement
1	Glycerine, 1 oz., Anhydrous
1	Cold Cream, 1 Lb.
2	Petrolatum, White, jelly, 1 oz.,
1	Petrolatum, Liquid, Heavy (Mineral Oil), 6 oz.,
1	Charcoal/Wood Ash, 2 oz.,
1	Modeling Paste, non-hardening, (Plastalene, Dark)
1	Modeling Paste, non-hardening (Plastalene, White)
6	Sponges, make-up type

COSMETICS

2	Lining Color- White, 1/2 oz.
2	Lining Color- Brown, 1/2 oz.
2	Lining Color- Black, 1/2 oz.
2	Lining Color- Flesh, 1/2 oz.
2	Lining Color- Red, 1/2 oz.
2	Lining Color- Yellow, 1/2 oz.
2	Lining Color- Special Blue, 1/2 oz.

Workmanship. The casualty simulation kit shall be free from defects which detract from its appearance or impair its serviceability.

Unit. Each (EA). One casualty simulation kit, as specified, constitutes one unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:32Z
Check the source to verify that this is the current version before use.

Quality Assurance Provisions.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

Inspection. Inspection, as used herein, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

Sampling for examination. Sampling for examination shall be conducted in accordance with MIL-STD-105, with an AQL of 1.0 (percent defective) and an inspection level of II. The unit of product for examination purposes shall be one casualty simulation kit, as specified in this description.

Sampling for tests. Sampling for tests, including dimensional test, shall be conducted in accordance with MIL-STD-105, with an AQL of 1.0 (percent defective) and an inspection level of II. The unit of product for test purposes shall be one casualty simulation kit .

Tests. Tests shall be conducted to determine compliance with specification requirements. Where feasible, the same sample shall be used for the determination of two or more test characteristics. As a minimum, the following tests shall be performed:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:32Z
Check the source to verify that this is the current version before use.

a. Bleeding Moulage Reservoir. Fill the reservoir with water, dry outside surfaces well and let hang for 5 minutes. Check for leaks at the reservoir stopper and hose outlets. There shall be no leakage at reservoir stopper and no more than 9 drops per 5 minutes at the hose outlet.

b. Bleeding Moulage System. With reservoir full of water, work pump to check for proper operation of pump, valves and connecting tubing to give appearance of simuated bleeding. Also check system for leaks at connections. There shall be no visible leakage at connections over a 3 minute period.

c. Carrying Case Drop Test. With all kit items loaded inside the case, drop 4 times onto a concrete floor from a height of 50 centimeters, once each onto each bottom corner. There shall be no damage to the case or contents. Minor scuffing of case is acceptable.

d. Detergent/Hot Water Test. Soak 12 plastic moulages in a mild detergent/warm water solution (120°F ±5°F) for 1 hour, rinse in warm water, pat dry. There shall be no deterioration of color or surface finish.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified using conversion tables contained in the latest revision of Federal Standard 376, and all other requirements of this document are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Contractor certification. The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producers' own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:32Z
Check the source to verify that this is the current version before use.

Regulatory requirements.

Federal Food, Drug and Cosmetic Act. If the product covered by this document has been determined by the U.S. Food and Drug Administration to be under its jurisdiction, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of the Federal Food, Drug and Cosmetic Act, as amended, and regulations promulgated thereunder. In addition, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of all other applicable Federal, State, and local statutes, ordinances and regulations.

Recovered materials. The offeror/contractor is encouraged to use recovered material in accordance with Federal Acquisition Regulation Subpart 23.4 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified, preservation, packaging, and packing shall be to a degree of protection to preclude damage to containers and/or contents thereof under normal shipping conditions, handling, etc., involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity, and shall conform to applicable carrier's rules and regulations. Intermediate and exterior package quantities and labeling and marking shall be as specified in the contract and/or order.

Ordering data. Intermediate/exterior package quantities, labeling, and marking must be specified in the contract and/or order.

NOTE: The following National Stock Number is covered by this document.

6910-01-300-6541

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:32Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:

Army - MD
Navy - MS
Air Force - 03

PREPARING ACTIVITY:

DoD-MB

Agent:

DLA-DM

CIVIL AGENCY COORDINATING ACTIVITIES:

VA-OSS
USPHS
FDA-MPQAS

Project Number: 6910-0037

Location: SIMULCID.1DB

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:32Z
Check the source to verify that this is the current version before use.