INCH POUND

MIL-T-52864/3C
23 March 1990
SUPERSEDING
MIL-T-52864/3B
22 April 1987

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK: DIESEL-ENGINE-DRIVEN, PNEUMATIC-TIRED, 15,000-POUND CAPACITY AT 24-INCH LOAD CENTER, 210-INCH LIFT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirement for acquiring the truck described herein shall consist of this specification and the latest issue of MIL-T-52864.

REQUIREMENTS

1. Capacity: 15,000 pounds at 24-inch load center.
2. Collapsed mast height: 154 inches maximum.
3. Maximum fork height: 210 inches minimum.
4. Free lift height: As applicable.
5. Fork size: 2-9/16 inches maximum thickness X 8-1/16 inches maximum width X 48 inches long, +0 inch -1/2 inch.
6. Fork spacing: 18 inches to minimum 60 inches.
7. Overhead guard height: 116 inches maximum.
8. Right-angle turn dimension "A": 240 inches maximum.
9. Underclearance beneath mast assembly: 6 inches minimum.
10. Transmission: Not less than two speeds forward and two speeds reverse.

Custodians:
Army - ME
Navy - SA
Air Force - 99

Review activity:
Army - SM
Navy - OS
Air Force - 84
User activities:
Army - MT
Navy - SH

Preparing activity
Army - ME

Project 3930-0648

AMSC N/A

FSC 3930

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:36Z
Check the source to verify that this is the current version before use.