INCH-POUND

MIL-DTL-32546/3A(AS)
11 July 2018
SUPERSEDING
MIL-DTL-32546/3(AS)
14 March 2016

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, RECEPTACLE, THREADED, JAM NUT MOUNTING, HIGH-SPEED DATA

This specification is approved for use by the Naval Air Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-32546.




FIGURE 1. Receptacle, jam nut, size 11.

TABLE I. Insert arrangement for size 11 shell.


Insert Arrangement (see figure 2)	Service Rating (DWV*)
11-08	1300V rms**

*dielectric withstanding voltage
**root mean square


AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:01Z
Check the source to verify that this is the current version before use.



Front Face – Socket Contacts



Front Face – Pin Contacts

FIGURE 2. 11-08 insert detail.

TABLE II. Contact location identification/cable wire color

Pin/ Socket 1/	Cable wire colors 2/	EIA/TIA 586A/586B Pairs 3/
1	White/Blue	1
2	Blue	
3	White/Orange	2
4	Orange	
5	White/Green	3
6	Green	
7	White/Brown	4
8	Brown	

1/ Contact location identification is for reference only (see 3.40).
2/ Recommended cable wire color locations.
3/ Recommended EIA/TIA 586 pair allocation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:01Z
Check the source to verify that this is the current version before use.

TABLE III. Contact information.

PIN					
Type	SAE AS39029 Part Number	SAE AS22520		SAE AS81969	
		Crimp Tool 1/	Positioner 1/	Installing tool 1/	Removal tool 1/
22D Pin	M39029/58-360	M22520/2-01 M22520/7-01	M22520/2-09 M22520/7-07	M81969/8-01 M81969/14-01	M81969/8-02 M81969/14-01
	M39029/107-620				
	M39029/122-671				
	M39029/71-390, -391, 392	N/A		M81969/1-04 M81969/8-01	M81969/1-04 M81969/8-02
Socket					
22D Socket	M39029/56-348	M22520/2-01 M22520/7-01	M22520/2-07 M22520/7-05	M81969/8-01 M81969/14-01	M81969/8-02 M81969/14-01
	M39029/106-614				
	M39029/121-664				
	M39029/72-524, -525, -526	N/A		M81969/1-04 M81969/8-01	M81969/1-04 M81969/8-02

1/ See SAE AS39029/56, /58, /71, /72, /106, /107, /121 and /122 for additional crimp tool and installation removal tool information.




FIGURE 3. Receptacle, jam nut, size 25 (Socket insert arrangement example.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:01Z
Check the source to verify that this is the current version before use.

TABLE IV. Insert layouts for size 25 shell.

Shell size	Arrangement no.	Number of contacts	Size contacts	Service rating	Contact location	Service rating (DWV)
25	4 X 11-08	32	22	M	All	1300V rms




FIGURE 4. Insert orientation for size 25 shell. 1/, 2/

1/ Note that the master key of insert shall be oriented at a135 degree angle toward the center of the connector. Insert arrangement 11-08 shown in cavity A as reference.
2/ See Table II for recommended contact location identification/cable wire colors for cavities A, B, C, and D.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:01Z
Check the source to verify that this is the current version before use.




FIGURE 5. Receptacle polarization.

TABLE V. Main key and keyway polarization.

Shell size	Key and keyway polarization identification letter	AR° or AP° BSC	BR° or BP° BSC	CR° or CP° BSC	DR° or DP° BSC
11	N	95	141	208	236
	A	113	156	182	292
	B	90	145	195	252
	C	53	156	220	255
	D	119	146	176	298
	E	51	141	184	242
25	N	80	142	196	293
	A	135	170	200	310
	B	49	169	200	244
	C	66	140	200	257
	D	62	145	180	280
	E	79	153	197	272

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:01Z
Check the source to verify that this is the current version before use.

TABLE VI. Receptacle with socket contact locations.

(Insert arrangement 4 X 11-08)		
Contact position identification (ID)	Contact location	
	X-axis (mm)	Y-axis (mm)
A1	-.1878 (4.77)	+.1213 (3.08)
A2	-.1213 (3.08)	+.1878 (4.77)
A3	-.1213 (3.08)	+.3122 (7.93)
A4	-.1878 (4.77)	+.3787 (9.62)
A5	-.3122 (7.93)	+.3787 (9.62)
A6	-.3787 (9.62)	+.3122 (7.93)
A7	-.3787 (9.62)	+.1878 (4.77)
A8	-.3122 (7.93)	+.1213 (3.08)
B1	+.1213 (3.08)	+.1878 (4.77)
B2	+.1878 (4.77)	+.1213 (3.08)
B3	+.3122 (7.93)	+.1213 (3.08)
B4	+.3787 (9.62)	+.1878 (4.77)
B5	+.3787 (9.62)	+.3122 (7.93)
B6	+.3122 (7.93)	+.3787 (9.62)
B7	+.1878 (4.77)	+.3787 (9.62)
B8	+.1213 (3.08)	+.3122 (7.93)
C1	+.1878 (4.77)	-.1213 (3.08)
C2	+.1213 (3.08)	-.1878 (4.77)
C3	+.1213 (3.08)	-.3122 (7.93)
C4	+.1878 (4.77)	-.3787 (9.62)
C5	+.3122 (7.93)	-.3787 (9.62)
C6	+.3787 (9.62)	-.3122 (7.93)
C7	+.3787 (9.62)	-.1878 (4.77)
C8	+.3122 (7.93)	-.1213 (3.08)
D1	-.1213 (3.08)	-.1878 (4.77)
D2	-.1878 (4.77)	-.1213 (3.08)
D3	-.3122 (7.93)	-.1213 (3.08)
D4	-.3787 (9.62)	-.1878 (4.77)
D5	-.3787 (9.62)	-.3122 (7.93)
D6	-.3122 (7.93)	-.3787 (9.62)
D7	-.1878 (4.77)	-.3787 (9.62)
D8	-.1213 (3.08)	-.3122 (7.93)




FIGURE 6. Receptacle with socket contacts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:01Z
Check the source to verify that this is the current version before use.

TABLE VII. Receptacle with pin contact locations.

(Insert arrangement 4X 11-08)		
Contact position identification (ID)	Contact location	
	X-axis (mm)	Y-axis (mm)
A1	-.1213 (3.08)	+.1878 (4.77)
A2	-.1878 (4.77)	+.1213 (3.08)
A3	-.3122 (7.93)	+.1213 (3.08)
A4	-.3787 (9.62)	+.1878 (4.77)
A5	-.3787 (9.62)	+.3122 (7.93)
A6	-.3122 (7.93)	+.3787 (9.62)
A7	-.1878 (4.77)	+.3787 (9.62)
A8	-.1213 (3.08)	+.3122 (7.93)
B1	+.1878 (4.77)	+.1213 (3.08)
B2	+.1213 (3.08)	+.1878 (4.77)
B3	+.1213 (3.08)	+.3122 (7.93)
B4	+.1878 (4.77)	+.3787 (9.62)
B5	+.3122 (7.93)	+.3787 (9.62)
B6	+.3787 (9.62)	+.3122 (7.93)
B7	+.3787 (9.62)	+.1878 (4.77)
B8	+.3122 (7.93)	+.1213 (3.08)
C1	+.1213 (3.08)	-.1878 (4.77)
C2	+.1878 (4.77)	-.1213 (3.08)
C3	+.3122 (7.93)	-.1213 (3.08)
C4	+.3787 (9.62)	-.1878 (4.77)
C5	+.3787 (9.62)	-.3122 (7.93)
C6	+.3122 (7.93)	-.3787 (9.62)
C7	+.1878 (4.77)	-.3787 (9.62)
C8	+.1213 (3.08)	-.3122 (7.93)
D1	-.1878 (4.77)	-.1213 (3.08)
D2	-.1213 (3.08)	-.1878 (4.77)
D3	-.1213 (3.08)	-.3122 (7.93)
D4	-.1878 (4.77)	-.3787 (9.62)
D5	-.3122 (7.93)	-.3787 (9.62)
D6	-.3787 (9.62)	-.3122 (7.93)
D7	-.3787 (9.62)	-.1878 (4.77)
D8	-.3122 (7.93)	-.1213 (3.08)




FIGURE 7. Receptacle with pin contacts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:01Z
Check the source to verify that this is the current version before use.




FIGURE 8. Panel mounting cutouts for jam nut receptacle.

TABLE VIII. Panel mounting dimensions.

Shell size	øA +.000/-.010	øB +.010/-.000
11	0.771	0.825
25	1.710	1.760

NOTES:

1. Dimensions are in inches.
2. Environmental backshell included with connector kit.
3. Mating face of pin insert shown on insert layouts.

REQUIREMENTS:

1. Materials:

   Resilient inserts/backshell grommet – silicone elastomer per ASTM D6411/D6411M.

   Plastic inserts – thermoplastic per ASTM D5205.

2. Dimensions and configuration: See Figure 1. Interface dimensions shall be in accordance with connector intermateability dimensions (series III) of MIL-DTL-38999.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:01Z
Check the source to verify that this is the current version before use.

3. This connector mates with MIL-DTL-32546/2.

4. Part or Identifying Number (PIN) example:




TABLE IX. Shell size code.

Shell size	Shell size code
11	B
25	F

5. See Table III for contact information for Figure 1 and 3 plug contacts.

6. The frequency range is 1-500 MHz.

7. Impedance is determined by the electrical performance and characteristics stated in MIL-DTL-32546.

8. Connector physical requirements shall meet the requirements of MIL-DTL-38999, Series III, unless otherwise noted.

9. Backshell in accordance with SAE AS85049 not applicable (see 3.5.3). The backshell shall be in accordance with Figures 1 and 3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:01Z
Check the source to verify that this is the current version before use.

10. Size 25 connector shall have removable modules (see Figure 3). Cavity fills per paragraph 3.5.10 around individual modules does not apply to the individual modules of the size 25 connector.

EXAMINATION AND TESTS:

1. Additional testing.

2. Vibration for shell sizes 11 and 25 shall be conducted with the backshell and grommet shown in figures 1 and 3, respectively. Accelerometer location (see MIL-DTL-32546, figure 2) shall be as defined in Table XI. Cable weight between rear of grommet and tie down clamp point to be considered a portion of the backshell assembly weight.

3. Group 3 and group 7 testing, Class M and J composite connectors may be tested with aluminum backshells. With aluminum backshells the class M connector will be rated at the 48 hour salt spray requirement instead of the 500 hour salt spray requirement.

4. High impact shock shall be tested with the backshell shown on figures 1 and 3.

5. Group 4 testing shall be conducted using shell size 25.

6. Group 11 testing shall be conducted using shell sizes 11 and 25.

7. The backshell shown on figures 1 and 3 shall terminate to the braid of category 6A overall shielded cable. This backshell is not intended to be used with a braidsock. Lightning strike tests are not applicable in group 11 testing.

TABLE X. Cable braid retention test.

Inspection	Requirement	Test Paragraph
Cable braid retention	12.5 pounds force with slippage not to exceed 0.125 in.	SAE AS85049 para. 4.6.9 (Method A ECIA EIA-364-38) except that the pull force is to be applied to the cable braid (less jacket).1/

1/ In the event of multiple cables, test applies to individual cables.

TABLE XI. Accelerometer location.

Shell Size	Weight (kg) +10%/-0%	LL (mm) ± 1
11	.035	10.8
25	.13	19.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:01Z
Check the source to verify that this is the current version before use.

NOTES:

1. Intended use. The connectors qualified to this specification are intended for use as high speed data connectors using copper conductor for transmission of signals up to 10 gigabits per second (Gbps), such as IEEE 802.3 10GBASE-T, over four-pair cabling.

Referenced documents. In addition to MIL-DTL-32546 and its applicable specification sheets, this specification sheet references:

ECIA EIA-364-38	MIL-DTL-38999	SAE AS39029/107
EIA/TIA 586	MIL-DTL-38999/28	SAE AS39029/121
IEEE 802.3	SAE AS39029/56	SAE AS39029/122
ASTM D5205	SAE AS39029/58	SAE AS81969
ASTM D6411/6411M	SAE AS39029/71	SAE AS85049
MIL-DTL-32546/2	SAE AS39029/72	
SAE AS22520	SAE AS39029/106	

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodian:
Navy - AS

Preparing activity:
Navy – AS
Project 5935-2018-034

NOTE: The activity listed above was interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:01Z
Check the source to verify that this is the current version before use.