
INCH-POUND
MIL-PRF-32535/4
w/AMENDMENT 4
14 February 2020
SUPERSEDING
MIL-PRF-32535/4
w/AMENDMENT 3
4 June 2018

PERFORMANCE SPECIFICATION SHEET

CAPACITOR, CHIP, FIXED, CERAMIC DIELECTRIC (TEMPERATURE STABLE AND GENERAL PURPOSE), EXTENDED RANGE, HIGH RELIABILITY AND STANDARD RELIABILITY, SIZE 0805

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-32535.



Dimensions			
L + .012, - .010	W + .012, - .010	T Max.	Y ± .010
.079	.050	.062	.020

inches	mm
.010	0.25
.012	0.30
.020	0.51
.050	1.27
.062	1.57
.079	2.01

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Dimensions and tolerances are for terminated chips.
4. For solder termination finishes, add .020 inch (0.51 mm) to the positive length tolerance and .015 inch (0.38 mm) to the positive width and thickness tolerances. The increase in dimension applies to the solder coating thickness only.

FIGURE 1. Size 0805 capacitors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:54Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Capacitance value: See table I.

Capacitance tolerance: See table I and MIL-PRF-32535.

Voltage-temperature limit or temperature characteristic (VTL/TC): BP, C0G, and X7R as specified in MIL-PRF-32535.

Rated voltage (V_{dc}): V = 4; W = 6.3; X = 10; Y = 16; Z = 25; A = 50; B = 100; C = 200. See table I for maximum rated voltage available for each capacitance value.

Operating temperature range: -55°C to +125°C.

Termination finish: D, G, H, M, R, V, and Z as specified in MIL-PRF-32535.

Electrode: P and B as specified in MIL-PRF-32535.

Product level designator: Standard reliability – M and high reliability - T as specified in MIL-PRF-32535.

Marking: In accordance with MIL-PRF-32535.

TABLE I. Size 0805 capacitor characteristics.

Part or Identifying Number (PIN) 1/	Capacitance (pF)	Capacitance tolerance	VTL/TC	Rated voltage 2/ (V_{dc})	Electrode material
M3253504 - - - 1R0 - - - -	1.0	B, C, D	BP, C0G	200	P, B
M3253504 - - - 1R5 - - - -	1.5	B, C, D	BP, C0G	200	P, B
M3253504 - - - 2R2 - - - -	2.2	B, C, D	BP, C0G	200	P, B
M3253504 - - - 2R7 - - - -	2.7	B, C, D	BP, C0G	200	P, B
M3253504 - - - 3R3 - - - -	3.3	B, C, D	BP, C0G	200	P, B
M3253504 - - - 3R9 - - - -	3.9	B, C, D	BP, C0G	200	P, B
M3253504 - - - 4R7 - - - -	4.7	B, C, D	BP, C0G	200	P, B
M3253504 - - - 5R6 - - - -	5.6	B, C, D	BP, C0G	200	P, B
M3253504 - - - 6R8 - - - -	6.8	B, C, D	BP, C0G	200	P, B
M3253504 - - - 8R2 - - - -	8.2	B, C, D	BP, C0G	200	P, B
M3253504 - - - 100 - - - -	10	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 120 - - - -	12	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 150 - - - -	15	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 180 - - - -	18	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 200 - - - -	20	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 220 - - - -	22	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 270 - - - -	27	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 330 - - - -	33	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 390 - - - -	39	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 470 - - - -	47	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 560 - - - -	56	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 680 - - - -	68	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 820 - - - -	82	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 101 - - - -	100	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 121 - - - -	120	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 151 - - - -	150	F, G, J, K	BP, C0G	200	P, B

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:54Z
Check the source to verify that this is the current version before use.

TABLE I. Size 0805 capacitor characteristics - Continued.

Part or Identifying Number (PIN) 1/	Capacitance (pF)	Capacitance tolerance	VTL/TC	Rated voltage 2/ (V_{dc})	Electrode material
M3253504 - - - 181 - - - -	180	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 221 - - - -	220	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 271 - - - -	270	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 331 - - - -	330	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 391 - - - -	390	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 471 - - - -	470	F, G, J, K	BP, C0G	200	P, B
M3253504 - - - 561 - - - -	560	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 681 - - - -	680	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 821 - - - -	820	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 102 - - - -	1,000	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 122 - - - -	1,200	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 152 - - - -	1,500	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 182 - - - -	1,800	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 202 - - - -	2,000	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 222 - - - -	2,200	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 272 - - - -	2,700	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 332 - - - -	3,300	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 392 - - - -	3,900	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 472 - - - -	4,700	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 562 - - - -	5,600	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 682 - - - -	6,800	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 822 - - - -	8,200	F, G, J, K	BP, C0G	100	P, B
M3253504 - - - 103 - - - -	10,000	F, G, J, K	BP, C0G	25	P, B
M3253504E2 - 103 - - - -	10,000	J, K, M	X7R	100	P, B
M3253504E2 - 123 - - - -	12,000	J, K, M	X7R	100	P, B
M3253504E2 - 153 - - - -	15,000	J, K, M	X7R	100	P, B
M3253504E2 - 183 - - - -	18,000	J, K, M	X7R	100	P, B
M3253504E2 - 223 - - - -	22,000	J, K, M	X7R	100	P, B
M3253504E2 - 273 - - - -	27,000	J, K, M	X7R	100	P, B
M3253504E2 - 333 - - - -	33,000	J, K, M	X7R	100	P, B
M3253504E2 - 393 - - - -	39,000	J, K, M	X7R	100	P, B
M3253504E2 - 473 - - - -	47,000	J, K, M	X7R	100	P, B
M3253504E2 - 563 - - - -	56,000	J, K, M	X7R	100	P, B
M3253504E2 - 683 - - - -	68,000	J, K, M	X7R	100	P, B
M3253504E2 - 823 - - - -	82,000	J, K, M	X7R	100	P, B
M3253504E2 - 104 - - - -	100,000	J, K, M	X7R	100	P, B
M3253504E2 - 124 - - - -	120,000	J, K, M	X7R	50	P, B
M3253504E2 - 154 - - - -	150,000	J, K, M	X7R	50	P, B
M3253504E2 - 184 - - - -	180,000	J, K, M	X7R	50	P, B
M3253504E2 - 224 - - - -	220,000	J, K, M	X7R	50	P, B
M3253504E2 - 274 - - - -	270,000	J, K, M	X7R	50	P, B
M3253504E2 - 334 - - - -	330,000	J, K, M	X7R	50	P, B
M3253504E2 - 394 - - - -	390,000	J, K, M	X7R	50	P, B
M3253504E2 - 474 - - - -	470,000	J, K, M	X7R	50	P, B
M3253504E2 - 564 - - - -	560,000	J, K, M	X7R	25	P, B
M3253504E2 - 684 - - - -	680,000	J, K, M	X7R	25	P, B
M3253504E2 - 824 - - - -	820,000	J, K, M	X7R	25	P, B
M3253504E2 - 105 - - - -	1,000,000	J, K, M	X7R	25	P, B

1/ The complete PIN shall include additional symbols to indicate VTL/TC (where applicable), voltage, capacitance tolerance, termination finish, product level, and electrode material.
2/ This is the maximum rated voltage available. All lower voltage ratings are also available.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:54Z
Check the source to verify that this is the current version before use.

Amendment notations: The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army – CR
Navy - EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5910-2019-033)

Review activities:
Army - MI
Navy - AS, MC, OS, SH
Air Force - 19
Other – MDA, NA

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:54Z
Check the source to verify that this is the current version before use.