NOT MEASUREMENT SENSITIVE


MIL-B-3628/30J
30 July 1993
SUPERSEDING
MIL-B-3628/30H
13 September 1991

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, PARACHUTIST, ARMY, NAVY, MARINE CORPS AND AIR FORCE; SENIOR AND MASTER PARACHUTIST, ARMY AND AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



DASH NO:

-1: Master Parachutist, Regular Size (A, AF)
-2: Senior Parachutist, Regular Size (A, AF)
-3: Parachutist, Regular Size (A, AF, N, MC)
-4: Master Parachutist, Dress Miniature Size (A)
-5: Senior Parachutist, Dress Miniature Size (A)
-6: Parachutist, Dress Miniature Size (A)
-7: Master Parachutist, Regular Size, Subdued (A)
-8: Senior Parachutist, Regular Size, Subdued (A)
-9: Parachutist, Regular Size, Subdued (A)

MATERIAL: Red Brass, Nickel Silver or Zinc Aluminum

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:57Z
Check the source to verify that this is the current version before use.

FINISH:

-1 thru -6:

AIR FORCE:

RED BRASS OR NICKEL SILVER: Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

ZINC ALUMINUM: Copper Plated, Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

ARMY, NAVY, MARINE CORPS:

RED BRASS OR NICKEL SILVER: Nickel Plated (Red Brass Only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

ZINC ALUMINUM: Copper Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

-7 thru -9: Dull, Flat Black Enamel

DIMENSIONS:

HEIGHT (Overall):

-1, -7: 1-13/64 inches (3.06 cm) (REF)
-2, -8: 1-3/32 inches (2.78 cm) (REF)
-3, -9: 13/16 inch (2.06 cm) (REF)
-4: 13/16 inch (2.06 cm) (REF)
-5: 5/8 inch (1.59 cm) (REF)
-6: 15/32 inch (1.19 cm) (REF)

WIDTH (Overall):

-1, -2, -3, -7, -8, -9: 1-1/2 inches (3.81 cm) (REF)
-4, -5, -6: 7/8 inch (2.22 cm) (REF)
-3: 7/8 inch (3.73 cm) (REF)

THICKNESS (At thickest point of wings):

-1, -2, -3, -7, -8, -9: 0.095 inch $\pm$ 0.005 inch (0.241 cm $\pm$ 0.012 cm)
-4, -5, -6: 0.070 inch $\pm$ 0.005 inch (0.177 cm $\pm$ 0.012 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The dull, flat black enamel for Dash Nos. -7 through -9 shall match FED-STD-595, Chip Number 37038.

3. The attaching device shall be prong and clutch type. Prongs shall be located at each intersection of the horizontal center line of the badge and the center of the wings.

4. A forcer may be used on the form of the parachute, the star and the star and wreath.

5. Piercing shall be as indicated. Piercing around the star applies to regular size badges only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:57Z
Check the source to verify that this is the current version before use.

6. As an alternate method of manufacturing for commercial sale only, Army Dash No. -1 through -6 may be nickel or rhodium plated with a mirror-like polished finish and shall match TIOH Metal Finish Chip Number 16.

Custodian:
Army - IH
Air Force - 11
Navy - NU

Preparing activities:
Army - IH

Review activities:
Air Force - 82, 99
Navy - MC
DLA - CT

(Project No. 8455-0693)

User activities:
Air Force - 45

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:57Z
Check the source to verify that this is the current version before use.