NOT MEASUREMENT SENSITIVE


MIL-B-3628/33G
30 July 1993
SUPERSEDING
MIL-B-3628/33F
26 April 1991

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, EXPERT FIELD MEDICAL, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



(-1, -2 Only)

DASH NO:
-1: Regular Size
-2: Regular Size, Subdued
-3: Dress Miniature

MATERIAL: Red Brass or Nickel Silver

FINISH:
-1, -3: Nickel Plated (Red Brass Only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.
-2: Dull, Flat, Black Enamel Finish.

DIMENSIONS:
HEIGHT (Overall):
-1, -2: 15/16 inch (2.38 cm) (REF)
-3: 9/16 inch (1.43 cm) (REF)
WIDTH (Overall):
-1, -2: 1-7/16 inches (3.65 cm) (REF)
-3: 3/4 inch (1.91 cm) (REF)
THICKNESS (At Center of Cross):
-1, -2: 0.100 inch ± .005 inch (0.254 cm ± 0.012 cm)
-3: 0.060 inch ± .005 inch (0.152 cm ± 0.012 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:59Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated for Dash No. -1 and -2 only.

3. The dull, flat, black enamel for Dash No. -2 shall match FED-STD-595, Chip No. 37038.

4. The attaching device shall be prong and clutch type. Prongs shall be located on the horizontal center line equidistant from each end and 7/8 inch ± 1/32 inch (2.22 cm ± 0.08 cm) apart for Dash No. -1 and -2 and 7/16 inch ± 1/32 inch (1.11 cm ± 0.08 cm) apart for Dash No. -3.

5. Dash -1 and -3 may be nickel or rhodium plated with a mirror-like polished finish which shall match TIOH Metal Finish Chip Number 16 for commercial sale only. For nickel or rhodium plated items, the silver plating requirement shall not apply.

Custodian:
Army - IH

Review activities:
DLA - CT

Preparing activities:
Army - IH

(Project No. 8455-0693)

Source: https://assist.dla.mil -- Downloaded: 202610-16T18:59Z
Check the source to verify that this is the current version before use.