
MIL-B-3628 / 34H
10 February 1988
SUPERSEDING
MIL-B-3628 / 34G
6 September 1973


MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, NUCLEAR REACTOR OPERATORS, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-3628.




-1, -5, -9



-2, -6, -10

(-2, -6 ONLY)

PIERCED
(-3, -4, -7, -8 ONLY)



-3, -4, -7, -8, -11, -12

DASH NOS.

-1:	NUCLEAR REACTOR OPERATOR, BASIC
-2:	NUCLEAR REACTOR OPERATOR, 2ND CLASS
-3:	NUCLEAR REACTOR OPERATOR, 1ST CLASS
-4:	NUCLEAR REACTOR OPERATOR, SHIFT SUPERVISOR
-5:	NUCLEAR REACTOR OPERATOR, BASIC, SUBDUED
-6:	NUCLEAR REACTOR OPERATOR, 2ND CLASS, SUBDUED
-7:	NUCLEAR REACTOR OPERATOR, 1ST CLASS, SUBDUED
-8:	NUCLEAR REACTOR OPERATOR, SHIFT SUPERVISOR, SUBDUED
-9:	NUCLEAR REACTOR OPERATOR, BASIC, DRESS MINIATURE
-10:	NUCLEAR REACTOR OPERATOR, 2ND CLASS, DRESS MINIATURE
-11:	NUCLEAR REACTOR OPERATOR, 1ST CLASS, DRESS MINIATURE
-12:	NUCLEAR REACTOR OPERATOR, SHIFT SUPERVISOR, DRESS MINIATURE

MATERIAL:

-1,-2,-3,-9,-10,-11:	RED BRASS OR NICKEL SILVER
-4,-5,-6,-7,-8,-12:	RED BRASS

DIMENSIONS (INCHES):

HEIGHT (OVERALL):

-1,-5:	29/32 (REF)
-2,-3,-4,-6,-7,-8:	1 (REF)
-9:	19/32 (REF)
-10,-11,-12:	11/16 (REF)

WIDTH (OVERALL):

-1 THRU -8:	1-1/8 (REF)
-9 THRU -12:	3/4 (REF)

THICKNESS (AT CENTER OF EMBLEM):

-1,-5:	.090 ± .005
-2,-3,-6,-7:	.100 ± .005
-4,-8:	.100 ± .005
-9:	.075 ± .005
-10,-11,-12:	.085 ± .005

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded:.2026-10-16T18:59Z
Check the source to verify that this is the current version before use.

FINISH:

-1,-2,-3,-9,-10,-11:	NICKEL PLATED (RED BRASS ONLY), SILVER PLATED, OXIDIZED, RELIEVED, SATIN FINISH, REVERSE AND EDGES CLEAN.
-4,-12:	GOLD PLATED, SATIN FINISH WITH POLISHED HIGHLIGHTS
-5,-6,-7:	DULL, FLAT BLACK ENAMEL FINISH
-8:	DULL, FLAT BROWN ENAMEL FINISH

NOTES:

1. DASH NOS. 1, 2, 3, 9, 10 AND 11 MAY BE MADE FROM STERLING SILVER FOR COMMERCIAL SALE AND IF SO THE THICKNESS DIMENSIONS GIVEN SHALL BE USED FOR REFERENCE ONLY. THE WEIGHTS SPECIFIED BELOW SHALL GOVERN. THE FINISH FOR STERLING SILVER BADGES SHALL BE AS SPECIFIED EXCEPT THE REQUIREMENT FOR SILVER PLATING SHALL NOT APPLY.

WEIGHT (MINIMUM			
-1:	180 GRAINS	-9:	65 GRAINS
-2:	185 GRAINS	-10:	72 GRAINS
-3:	175 GRAINS	-11:	60 GRAINS

2. ATTACHING DEVICE SHALL BE PRONG AND CLUTCH TYPE. THE PRONGS SHALL BE LOCATED ON THE HORIZONTAL CENTERLINE EQUIDISTANT FROM EACH END AND 3/4 ± 1/32 INCH ON CENTERS FOR DASH NOS. 1 THRU 8, 5/8 ± 1/32 INCH ON CENTERS FOR DASH NOS. 10, 11 AND 12, AND 1/2 ± 1/32 INCH ON CENTERS FOR DASH NO. 9.

Custodian:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0268)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:59Z
Check the source to verify that this is the current version before use.