NOT MEASUREMENT SENSITIVE

MIL-B-3628/34J
30 July 1993
SUPERSEDING
MIL-B-3628/34H
10 February 1988


MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, NUCLEAR REACTOR OPERATORS, ARMY


This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.


PIERCED (-3,-4,-7,-8 ONLY)



-3, -4, -7, -8, -11, -12



-1, -5, -9



-2, -6, -10

(-2,-6 ONLY)

DASH NO.

-1:	Nuclear Reactor Operator, Basic
-2:	Nuclear Reactor Operator, 2nd Class
-3:	Nuclear Reactor Operator, 1st Class
-4:	Nuclear Reactor Operator, Shift Supervisor
-5:	Nuclear Reactor Operator, Basic, Subdued
-6:	Nuclear Reactor Operator, 2nd Class, Subdued
-7:	Nuclear Reactor Operator, 1st Class, Subdued
-8:	Nuclear Reactor Operator, Shift Supervisor, Subdued
-9:	Nuclear Reactor Operator, Basic, Dress Miniature
-10:	Nuclear Reactor Operator, 2nd Class, Dress Miniature
-11:	Nuclear Reactor Operator, 1st Class, Dress Miniature
-12:	Nuclear Reactor Operator, Shift Supervisor, Dress Miniature

MATERIAL:

-1, -2, -3, -9, -10, -11:	Red Brass or Nickel Silver
-4, -5, -6, -7, -8, -12:	Red Brass

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:59Z
Check the source to verify that this is the current version before use.

FINISH:

-1, -2, -3, -9, -10, -11:	Nickel Plated (Red Brass only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14. Reverse and Edges Clean.
-4, -12:	Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.
-5, -6, -7:	Dull, Flat Black Enamel Finish.
-8:	Dull, Flat Brown Enamel Finish.

DIMENSIONS:

HEIGHT (Overall):

-1, -5:	29/32 inch (2.30 cm) (REF)
-2, -3, -4, -6, -7, -8:	1 inch (2.54 cm) (REF)
-9:	19/32 inch (1.51 cm) (REF)
-10, -11, -12:	11/16 inch (1.75 cm) (REF)

WIDTH (Overall):

-1 Thru -8:	1-1/8 inches (2.86 cm) (REF)
-9 Thru -12:	3/4 inch (1.91 cm) (REF)

THICKNESS (At Center of Emblem):

-1, -5:	0.090 inch ± 0.005 inch (0.287 cm ± 0.012 cm)
-2, -3, -4, -6, -7, -8:	0.100 inch ± 0.005 inch (0.254 cm ± 0.012 cm)
-9:	0.075 inch ± 0.005 inch (0.190 cm ± 0.012 cm)
-10, -11, -12:	0.085 inch ± 0.005 inch (0.216 cm ± 0.012 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated for full size badges only.

3. The dull, flat black enamel for Dash No. -5, -6, -7 shall match FED-STD-595, Chip No. 37038. The dull, flat brown enamel for Dash No. -8 shall match FED-STD-595, Chip No. 20095.

4. The attaching device shall be prong and clutch type. The prongs shall be located on the horizontal center line equidistant from each end and 3/4 inch ± 1/32 inch (1.91 cm ± 0.08 cm) apart for Dash No. -1 through -8, 5/8 inch ± 1/32 inch (1.59 cm ± 0.08 cm) apart for Dash No. -10, -11, and -12 and 1/2 inch ± 1/32 inch (1.27 cm ± 0.08 cm) apart on centers for Dash No. -9.

Custodian:
Army - IH

Preparing activities:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0693)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:59Z
Check the source to verify that this is the current version before use.