NOT MEASUREMENT SENSITIVE


MIL-B-3628/35D
30 July 1993
SUPERSEDING
MIL-B-3628/35C
10 February 1988

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, DISTINGUISHED MARKSMAN, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



MATERIAL:
PENDANT: Gilding Metal
SUSPENSION BAR: Red Brass or Gilding Metal

FINISH:
PENDANT:
OBVERSE: Hard Enameled, Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.
REVERSE: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

SUSPENSION BAR:
OBVERSE: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.
REVERSE: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-16T19:00Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

HEIGHT (Overall):
PENDANT: 1-33/64 inches (3.85 cm) (REF)
SUSPENSION BAR: 5/16 inch (0.79 cm) (REF)

WIDTH (Overall):
PENDANT: 1-9/32 inches (3.25 cm) (REF)
SUSPENSION BAR: 1-7/8 inches (4.76 cm) (REF)

THICKNESS (At Rim):
PENDANT: 0.080 inch ± .005 inch (0.203 cm ± 0.012 cm)
SUSPENSION BAR: 0.055 inch ± .005 inch (0.140 cm ± 0.012 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Black	26
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. Epoxy resin shall be smooth and flush with the dikes.

4. Lugs are intergral.

5. Links shall be 13/64 ± 1/64 inch (0.52 cm ± 0.04 cm) in width and 1/4 inch ± 1/64 inch (0.64 cm ± 0.04 cm) in length and shall be fabricated from 0.044 inch ± 0.005 inch (0.114 cm ± 0.012 cm) diameter wire.

6. The attaching device shall be prong and flat ball type clutch. The prongs and clutch shall be located on the horizontal center line of the back of the suspension bar equidistant from each end and 1-1/4 inch ± 1/32 inch (3.18 cm ± 0.08 cm) apart.

Custodian:
Army - IH
Navy - NU

Preparing activities:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-0693)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:00Z
Check the source to verify that this is the current version before use.