NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/37K
17 February 2026
SUPERSEDING
MIL-DTL-3628/37J
17 May 2024

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, LAUCHHEIMER TROPHY, MARINE CORPS

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



DASH NO.
-1: Gold
-2: Silver
-3: Bronze

MATERIAL:
-1, -2: Red Brass 85/15 (UNS Alloy No. C-230)
-3: Gilding Metal 95/5 (UNS Alloy No. C-210)

FINISH (Pendant and Suspension Bar):
OBVERSE:
-1: Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.
-2: Silver Plated, Lightly Oxidized, Relieved, Polished Highlights and shall match TIOH Metal Finish Chip Number 15.
-3: Lightly Oxidized, Relieved, Polished Highlights.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:00Z
Check the source to verify that this is the current version before use.

REVERSE:
-1: 22K Gold Plated, Mirror-like Polished, TIOH Metal Finish Chip Number 9
-2: Silver Plated, Mirror-like Polished, TIOH Metal Finish Chip Number 15
-3: Mirror-like Polished, Gilding Metal No Metal Finish Chip

DIMENSIONS:
HEIGHT (Overall):
ASSEMBLED: 1-7/8 inches (REF)
PENDANT: 1-1/2 inches (REF)
SUSPENSION BAR: 11/32 inch (REF)
WIDTH (Overall):
PENDANT: 1-1/32 inches (REF)
SUSPENSION BAR: 1-15/32 inches (REF)
THICKNESS (At rim):
PENDANT: 0.055 inch ± .005 inch
SUSPENSION BAR: 0.075 inch ± .005 inch

ATTACHING DEVICE AND LINKS:
1: The attaching device shall be prong and wing clutch type.

2: Nickel plated flat ball clutches shall be used for -2 and red brass flat ball clutches shall be used for -1 and -3. The prongs shall be located on the horizontal center line of the back of the suspension bar equidistant from each end and 1-3/32 inch ± 1/32 inch apart.

3: The connecting links shall be formed from 0.040 inch ± 0.002 inch diameter wire, shall be oblong in shape and 5/16 inch ± 1/64 inch in width.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The lugs are integral.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - IH
Navy - MC

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. (8455-2026-064)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:00Z
Check the source to verify that this is the current version before use.