
MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, ENCLOSED, SUBMERSIBLE (15 FEET), SNAP ACTION, 500 VOLTS ALTERNATING CURRENT/250 VOLTS, DIRECT CURRENT, 30 AMPERE, SYMBOL 852 (4PDT)

This specification sheet is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the switch described herein shall consist of this specification and the latest issue of MIL-S-15743(SH).




SH 131227

FIGURE 1. Switch, enclosed. (01)

NOTES:
1. All dimensions in inches.
2. Unless otherwise specified herein, tolerances shall be as follows:
   Two place decimals - plus or minus 0.02.
   Three place decimals - plus or minus 0.005.
   Angular dimensions - plus or minus 30 minutes.


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.



SH 131228

FIGURE 2. Box assembly.


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.



SH 131229

FIGURE 3. Cover assembly, (modified).


Source: https://assist.dla.mil -- Downloaded: 20261O-18T07:58Z
Check the source to verify that this is the current version before use.



SH 131230


FIGURE 4. Handle. (04)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.




SH 131231

FIGURE 5. Shaft assembly. (05)



SH 131232


FIGURE 6. Shaft. (06)



SH 131233


FIGURE 7. Coupler. (07)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.



SH 131234


FIGURE 8. Coupler plate. (08)



SH 131235


FIGURE 9. Mounting dimensions, ref.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.



SH 131236

FIGURE 10. Wiring diagram. (U9)



SH 131237

FIGURE 11. Identification plate. (11)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

SYMBOL NUMBER: See table I.

DESIGN:

Electrical rating: 500 Va.c., 60 Hz., 250 Vd.c., 0-30 ampere.
Dimensions and configuration: See figures 1 through 8.
Wiring diagram: See figure 10.
Mounting dimensions: See figure 9.
Degree of enclosure: Submersible (15 feet).
Weight: 6 pounds maximum.
Designation and marking: See figures 10 and 11.
Identification data shall be as shown on figure 11. Unless otherwise specified in the ordering data, switch action marking areas shall be blank.
Parts: The parts shown in table II and as specified in MIL-S-15743 shall be used in the construction of the switch specified herein.

GENERAL INFORMATION:

Military part numbers and general information are as shown in table I.

TABLE I. Military part number and general information.

Military part no.	Symbol no.	No. of poles and switching characteristics	Supersedes 1/				
			Type	Unit	Sheet	Revision	Date
M15743/10-001	852	4PDT	3SR4B4-2	7	8	D	6/30/77

1/ NAVSEA Drawing 9000-S6202-74276, in part.

ORDERING DATA:

Acquisition documents should specify the following:
Switch action marking, if required, (see requirements).

TABLE II. Parts list.

Item no. 1/	Description	Quantity M15743/10-001	Material/specification	Remarks
01	Switch enclosed (sym 852)	-		See figure 1
02	Enclosure	1	Brass, MIL-E-24142/5	M24142/5-003 2/
03	O-ring	1	MS28775-010	----
04	Handle	1	Copper alloy 854 of QQ-C-390	See figure 4
05	Shaft assembly	1	------	See figure 5
06	Shaft	1	Ni-Cu alloy of QQ-N-281	See figure 6
07	Coupler	1	Brass, alloy 260 of QQ-B-613	See figure 7

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.

TABLE II. Parts list. - Continued

Item no. 1/	Description	Quantity M15743/10-001	Material/specification	Remarks
08	Coupler plate	1	CRES, class 304 or 316 of QQ-S-766	See figure 8
09	Wiring diagram	1	MIL-E-2036	See figure 10
10	Switch (type 3SR4B4)	1	MIL-S-15291/7	M15291/7-010
11	Identification plate	1	Brass, QQ-B-613	See figure 11

1/ Numbers in circles shown on the figures are the same as the item numbers shown in this table.
2/ Modified enclosure cover, (see figure 3).

Preparing activity:
Navy - SH
(Project 5930-N584-10)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.