INCH-POUND
MIL-DTL-15743/13B
26 November 2002
SUPERSEDING
MIL-S-15743/13A
22 November 1993

DETAIL SPECIFICATION SHEET

SWITCH, ROTARY, ENCLOSED, DRIPPROOF ACTION, TRANSFER, WITH INDICATION, 125 VOLTS ALTERNATING CURRENT, 30 AMPERE, SYMBOL 849 (TPDT)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-15743.




FIGURE 1. Switch, enclosed. (01)

NOTES:
1. All dimensions in inches.
2. Unless otherwise specified herein, tolerances shall be as follows:
   Two place decimals - plus or minus 0.02.
   Three place decimals - plus or minus 0.005.
   Angular dimensions - plus or minus 30 minutes.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:59Z
Check the source to verify that this is the current version before use.




FIGURE 2. Box assembly (modified).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:59Z
Check the source to verify that this is the current version before use.




FIGURE 3. Cover assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:59Z
Check the source to verify that this is the current version before use.




FIGURE 4. Handle. 04

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:59Z
Check the source to verify that this is the current version before use.




FIGURE 5. Shaft assembly. 05




FIGURE 6. Shaft. 06




FIGURE 7. Coupler. 07

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:59Z
Check the source to verify that this is the current version before use.




FIGURE 8. Coupler plate. 08




FIGURE 9. Mounting dimensions, ref.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:59Z
Check the source to verify that this is the current version before use.




FIGURE 10. Wiring diagram. 09

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:59Z
Check the source to verify that this is the current version before use.







FIGURE 11. Caution plate. (16)



A. "ALT" information plate. (17)



B. "NOR" information plate. (18)



C. Identification plate. (19)

FIGURE 12. Identification and information plates.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:59Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

SYMBOL NUMBER: See table I.

DESIGN:

Electrical rating: 125 V ac, 0-30 ampere, 60 Hz.
Dimensions and configuration: See figures 1 through 8.
Wiring diagram: See figure 10.
Mounting dimensions: See figure 9.
Degree of enclosure: Dripproof.
Weight: 16 pounds maximum.
Designation and marking: See figures 11 and 12.
Identification data shall be as shown on figures 11 and 12. Unless otherwise specified in the ordering data, bottom portion of identification plate shall be blank as shown on figure 12.
Parts: The parts shown in table II and as specified in MIL-DTL-15743 shall be used in the construction of the switch specified herein.

GENERAL INFORMATION:

Military part number and general information are as shown in table I.

TABLE I. Military part number and general information.

Military part no.	Symbol no.	No. of poles and switching characteristics	Supersedes 1/		
			Type	Unit	Sheet
M15743/13-001	849	TPDT	3SR3B4-		1

1/ NAVSEA Drawing 815-1197224.

ORDERING DATA:
Acquisition documents should specify the following:
Switch action marking, if required (see requirements).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:59Z
Check the source to verify that this is the current version before use.

TABLE II. Parts list.

Item no. 1/	Description	Quantity M15743/ 13-001	Material/ specification	Remarks
01	Switch, enclosed (sym 849)	-		See figure 1
02	Enclosure	1	Brass, MIL-E-24142/3 (modified)	See figure 2 & 3 M24142/3-001
03	O-ring	1	SAE-AS28775-012	----
04	Handle (Type CFI-10)	1	Plastic, black, type CFI-10 of ASTM-D5948	See figure 4
05	Shaft assembly	1	----	See figure 5
06	Shaft	1	Ni-Cu alloy of QQ-N-281	See figure 6
07	Coupler	1	Brass, ASTM B 36 ASTM B 121	See figure 7
08	Coupler plate	1	CRES, or equivalent	See figure 8
09	Wiring diagram	1	MIL-E-2036	See figure 10
10	Switch (type 3SR3B4)	1	MIL-S-15291/7	M15291/7-009
11	Cable clamp	2	Nylon, coml	----
12	Lamp, incandescent	4	MIL-DTL-6363	Industry no.TS-159
13	Light, indicator	2	MIL-L-3661/65	Style LH 98/3
14	Target cap assy “ALT” and “NOR”	1 ea	Style LC38RNIM MIL-L-3661/52	----
15	Wiring diagram holder	1	MIL-E-24142	See figure 2
16	Caution plate	1	ASTM B 36, ASTM B 121	See figure 11
17	Information plate “ALT”	1	ASTM B 36, ASTM B 121	See figure 12a
18	Information plate “NOR”	1	ASTM B 36, ASTM B 121	See figure 12b
19	Identification plate	1	ASTM B 36, ASTM B 121	See figure 12c

1/ Numbers in circles shown on the figures are the same as the item numbers shown in this table.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodian:
Navy - SH
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-1742-13)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:59Z
Check the source to verify that this is the current version before use.