
MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, ENCLOSED, SUBMERSIBLE (15 FEET), SNAP ACTION, SIX-POLE, TWO-POSITION, POSITIVE DETENT, 125 VOLTS ALTERNATING CURRENT, 10 AMPERE, SYMBOL 2639.1

This specification sheet is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the switch described herein shall consist of this specification and the latest issue of MIL-S-15743(SH).




SH 131316

FIGURE 1. Switch, enclosed. (01)

NOTES:
1. All dimensions in inches.
2. Unless otherwise specified herein, tolerances shall be as follows:
   Two place decimals - plus or minus 0.02.
   Three place decimals - plus or minus 0.005.
   Angular dimensions - plus or minus 30 minutes.

FSC 5930


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:01Z
Check the source to verify that this is the current version before use.



SH 131317

FIGURE 2. Box assembly, (modified).


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:01Z
Check the source to verify that this is the current version before use.



SH 131318


FIGURE 3. Cover assembly, (modified).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:01Z
Check the source to verify that this is the current version before use.



SH 131319


FIGURE 4. Handle. (04)



SH 131320

FIGURE 5. Mounting dimensions, ref.

Source: https://assist.dla.mil -- Downloaded: 202610-18T08:01Z
Check the source to verify that this is the current version before use.




SH 131321

FIGURE 6. Wiring diagram. (05)

(as viewed from back of switch)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:01Z
Check the source to verify that this is the current version before use.



SH 131322

FIGURE 7. Identification plate. (06)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:01Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

SYMBOL NUMBER: See table I.

DESIGN:

Electrical rating: 125 Va.c., 0-10 ampere, 60 Hz.
Dimensions and configuration: See figures 1 through 4.
Wiring diagram: See figure 6.
Mounting dimensions: See figure 5.
Degree of enclosure: Submersible (15 feet).
Weight: 4 pounds maximum.
Designation and marking: See figure 7.
Identification data shall be as shown on figure 7. Unless otherwise specified in the ordering data, switch action and function marking shall be blank.
Parts: The parts shown in table II and as specified in MIL-S-15743 shall be used in the construction of the switch specified herein.

GENERAL INFORMATION:

Military part number and general information are as shown in table I.

TABLE I. Military part number and general information.

Military part no.	Symbol no.	No. of poles and switching characteristics	Supersedes 1/				
			Type	Unit	Sheet	Revision	Date
M15743/18-001	2639.1	Six-pole, 2 position	S2JR3-2	-	-	H	7/10/80

1/ NAVSEA Drawing 803-74055.

ORDERING DATA:

Acquisition documents should specify the following:
Switch action and function marking, if required, (see requirements).

TABLE II. Parts list.

Item no.	Description	Quantity M15743/18-001	Material/specification	Remarks
01	Switch, enclosed (sym 2639.1)	-	-----	See figure 1
02	Enclosure	1	Brass, MIL-E-24142/5	M24142/5-002 Mod 2/
03	Seal	1	-----	----
04	Handle	1	Brass, QQ-B-613	See figure 4
05	Switch (type JR 304)	1	MIL-S-21604/7	----
06	Identification plate	1	Brass, QQ-B-613	See figure 7

See footnotes at top of next page.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:01Z
Check the source to verify that this is the current version before use.

1/ Numbers in circles shown on the figures are the same as the item numbers shown in this table.
2/ Modified enclosure positioning pin and positioning pin hole location (see figures 2 and 3).

Preparing activity:
Navy - SH
(Project 5930-N584-18)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:01Z
Check the source to verify that this is the current version before use.