MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, ENCLOSED, SPLASHPROOF, SNAP ACTION, 125 VOLTS ALTERNATING CURRENT, 10 AMPERE, SYMBOL 814 (DPST)

This specification sheet is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the switch described herein shall consist of this specification and the latest issue of MIL-S-15743(SH).






FIGURE 1. Switch, enclosed. (01)

NOTES:
1. All dimensions in inches.
2. Unless otherwise specified herein, tolerances shall be as follows:
   Two place decimals - plus or minus 0.02.
   Three place decimals - plus or minus 0.005.
   Angular dimensions - plus or minus 30 minutes.

FSC 5930

Source: https://assist.dla.mil -- Downloaded: 202640-18T07:57Z
Check the source to verify that this is the currentversion before use.






SECTION A-A

SH 131192

FIGURE 2. Box assembly.


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:57Z
Check the source to verify that this is the current version before use.



SH 131193


FIGURE 3. Cover assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:57Z
Check the source to verify that this is the current version before use.



SH 131194


FIGURE 4. Cushion gasket. (04)



SH 131195


FIGURE 5. Handle. (05)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:57Z
Check the source to verify that this is the current version before use.




SH 131196

FIGURE 6. Shaft assembly. (06)



SH 131197


FIGURE 7. Shaft. (07)



SH 131198


FIGURE 8. Coupler. (08)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:57Z
Check the source to verify that this is the current version before use.



SH 131199


FIGURE 9. Coupler plate. (09)



SH 131200


FIGURE 10. Mounting dimensions, ref.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:57Z
Check the source to verify that this is the current version before use.



SH 131201

FIGURE 11. Wiring diagram. (09)



SH 131202

FIGURE 12. Identification plate. (12)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:57Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

SYMBOL NUMBER: See table I.

DESIGN:

Electrical rating: 125 Va.c., 0-10 ampere, 60 Hz.
Dimensions and configuration: See figures 1 through 9.
Wiring diagram: See figure 11.
Mounting dimensions: See figure 10.
Degree of enclosure: Splashproof.
Weight: 3 pounds maximum.
Designation and marking: See figures 11 and 12.
Identification data shall be as shown on figure 12. Unless otherwise specified in the ordering data, ON-OFF switch action marking shall be as shown on figure 11.
Parts: The parts shown in table II and as specified in MIL-S-15743 shall be used in the construction of the switches specified herein.

GENERAL INFORMATION:

Military part number and general information are as shown in table I.

TABLE I. Military part number and general information.

Military part no.	Symbol no.	No. of poles and switching characteristics	Supersedes 1/				
			Type	Unit	Sheet	Revision	Date
M15743/7-001	814	DPST	1SR2A4-4	9	10	D	10/28/57

1/ NAVSEA Drawing 9000-S6202-74207, in part.

ORDERING DATA:

Acquisition documents should specify the following:
Switch action marking, if different from that shown, (see requirements).

TABLE II. Parts list.

Item no. 1/	Description	Quantity M15743/7-001	Material/specification	Remarks
01	Switch, enclosed (sym 814)	-		See figure 1
02	Enclosure	1	Brass, MIL-E-24142/2	M24142/2-001 Mod 2/
03	O-ring	1	MS28775-010	----
04	Cushion gasket	1	MIL-R-900	See figure 4
05	Handle	2	Copper alloy 854 of QQ-C-390	See figure 5
06	Shaft assembly	2	-----	See figure 6
07	Shaft	2	Ni-Cu alloy of QQ-N-281	See figure 7
08	Coupler	2	Brass, alloy 260 of QQ-B-613	See figure 8

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:57Z
Check the source to verify that this is the current version before use.

TABLE II. Parts list. - Continued

Item no. 1/	Description	Quantity M15743/7-001	Material/specification	Remarks
09	Coupler plate	2	CRES, class 304 or 316 of QQ-S-766	See figure 9
10	Wiring diagram	1	MIL-E-2036	See figure 11
11	Switch (type 1SR1A4)	2	MIL-S-15291/3	M15291/3-002
12	Identification plate	1	Brass, QQ-B-613	See figure 12a

1/ Numbers in circles shown on the figures are the same as the item numbers shown in this table.
2/ Modified box to delete mounting tabs.

Preparing activity:
Navy - SH
(Project 5930-N584-7)

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:57Z
Check the source to verify that this is the current version before use.