INCH-POUND
MIL-S-15743/9A(SH)
22 November 1993
SUPERSEDING
MIL-S-15743/9(SH)
27 August 1984

MILITARY SPECIFICATION SHEET

SWITCHES, ROTARY, ENCLOSED, SUBMERSIBLE (15 FEET), SNAP ACTION, 500 VOLTS ALTERNATING CURRENT/250 VOLTS DIRECT CURRENT, 30 AMPERE, SYMBOLS 839.1 (4PDT), 848.1 (TPDT), AND 2752.1 (SPECIAL)

This specification sheet is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-S-15743.




FIGURE 1. Switch, enclosed. (01) (02) (03)
(-001 shown)

NOTES:
1. All dimensions in inches.
2. Unless otherwise specified herein, tolerances shall be as follows:
   Two place decimals - plus or minus 0.02.
   Three place decimals - plus or minus 0.005.
   Angular dimensions - plus or minus 30 minutes.

AMSC N/A FSC 5930
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:58Z
Check the source to verify that this is the current version before use.




FIGURE 2. Box assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.






FIGURE 3. Cover assembly (modified).


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.



A. Symbol 839.1 (06)



B. Symbol 848.1 (07)



C. Symbol 2752.1 (08)

FIGURE 4. Handles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.




FIGURE 5. Handle knob. (09)




FIGURE 6. Knob pin. (10)




FIGURE 7. Shaft assembly. (11)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.




FIGURE 8. Shaft. (12)




FIGURE 9. Coupler. (13)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.




FIGURE 10. Coupler plate. (14)




FIGURE 11. Mounting dimensions, ref.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.




FIGURE 12. Wiring diagrams.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.




FIGURE 13. Identification plate. (21)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

SYMBOL NUMBER: See table I.

DESIGN:

Electrical rating: 500 Va.c., 60 Hz, 250 Vd.c., 0-30 ampere.
Dimensions and configuration: See figures 1 through 10.
Wiring diagrams: See figure 12 a, b, and c.
Mounting dimensions: See figure 11.
Degree of enclosure: Submersible (15 feet).
Weight:
(a) Symbol 839.1 6 pounds maximum.
(b) Symbol 848.1 6 pounds maximum.
(c) Symbol 2752.1 2 pounds maximum.
Designation and marking: See figure 12.
Identification data shall be as shown on figure 13. Unless otherwise specified in the ordering data, switch action marking shall be blank.
Parts: The parts shown in table II and as specified in MIL-S-15743 shall be used in the construction of the switches specified herein.

GENERAL INFORMATION:

Military part numbers and general information are as shown in table I.

TABLE I. Military part number and general information.

Military part no.	Symbol no.	No. of poles and switching characteristics	Supersedes 1/		
			Type	Unit	Sheet
M15743/9-001	839.1	4PDT	3SR4C4-2	4	5
M15743/9-002	848.1	TPDT	3SR3B4-2	3	4
M15743/9-003	2752.1	SPECIAL	3SR7S4-2	5	6

1/ NAVSEA Drawing 9000-S6202-74276, in part.

ORDERING DATA:

Acquisition documents should specify the following:
Switch action marking, if different from that shown (see requirements).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:58Z
Check the source to verify that this is the current version before use.

TABLE II. Parts list.

Item no. 1/	Description	Quantity M15743/9-			Material/specification	Remarks
		001	002	003		
01	Switch, enclosed (sym 839.1)	-				See figure 1
02	Switch, enclosed (sym 848.1)		-			See figure 1
03	Switch, enclosed (sym 2752.1)			-		See figure 1
04	Enclosure	1	1	1	Brass, MIL-E-24142/5 (modified)	See figure 2 & 3 M24142/5-003 2/
05	O-ring	1	1	1	MS28775-010	----
06	Handle	1			Copper alloy ASTM B 584	See figure 4a
07	Handle		1		Brass, alloy ASTM B 584	See figure 4b
08	Handle			1	CRES, QQ-S-766	See figure 4c
09	Handle knob			1	Plastic, type FBG of MIL-P-79	See figure 5
10	Knob pin			1	CRES, QQ-S-763	See figure 6
11	Shaft assembly	1	1	1	----	See figure 7
12	Shaft	1	1	1	Ni-Cu alloy of QQ-N-281	See figure 8
13	Coupler	1	1	1	Brass, ASTM B 36, ASTM B 121	See figure 9
14	Coupler plate	1	1	1	CRES, class 304 or 316 of QQ-S-766	See figure 10
15	Wiring diagram	1			MIL-E-2036	See figure 12a
16	Wiring diagram		-		MIL-E-2036	See figure 12b
17	Wiring diagram			-	MIL-E-2036	See figure 12c
18	Switch (type 3SR4C4)	1			MIL-S-15291/7	M15291/7-015
19	Switch (type 3SR3B4)		1		MIL-S-15291/7	M15291/7-009
20	Switch (type 3SR7S4)			1	MIL-S-15291/7	M15291/7-018
21	Identification plate	1	1	1	ASTM B 36, ASTM B 121	See figure 13

1/ Numbers in circles shown on the figures are the same as the item numbers shown in this table.
2/ Modified enclosure cover (see figure 3).

Revision letters are not used to denote changes due to the extensiveness of the changes.

Preparing activity:
Navy - SH
(Project 5930-N746-9)

Source: https://assist.dla.mil -- Downloaded: 202610-18T07:58Z
Check the source to verify that this is the current version before use.