A-A-51058B
26 June 1987
SUPERCEDING
A-A-0051058A(DM)
6 October 1986

COMMERCIAL ITEM DESCRIPTION

WASTE RECEPTACLE, STEP-ON TYPE

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers a corrosion-resisting steel waste receptacle comprised of an outer container without a bail, an inner container with a bail, and a hinged cover operated by a foot-activated mechanism.

Salient characteristics:

The unit shall be a waste receptacle having an outer container without a bail, fitted with an automatically-closing cover hinged at the rear, activated by a cover-lifting mechanism operated by a foot pedal at the bottom, and an inner container provided with a bail for lifting the inner container from the outer container. The bail on the inner container shall also serve as a carry handle for the complete waste receptacle. The stationary position of the waste receptacle shall be unaffected by pressure on the foot pedal. The cover-lifting mechanism shall be equipped with a silencer which shall be a sponge rubber strip, a minimum of 3/4 inch wide and 1/4 inch thick, not less than 9 inches in length, securely attached to the front inside seating flange surface of the cover. The center of the bail shall be covered with suitable rubber or plastic tubing, at least four inches long.

The top rim of the inner container, the upper rim and the bottom edge of the outer container shall be beaded. The beads on the top rim and upper rim shall be rolled tightly against the outside surfaces. The bead for the bottom edge shall be similar, but against the inside surface.

AMSC N/A FSC 7240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:50Z
Check the source to verify that this is the current version before use.

The outer container shall be 10 inches in inside diameter and 13-1/4 inches in height and shall be so constructed as to adequately support the inner container. The inner container shall be 9 inches in diameter, and 11 inches in height and shall have a capacity of 3 gallons. A dimensional tolerance of plus or minus 1/8 inch shall apply. The unit shall be so constructed as to be supported within the outer container without binding. The metal parts of the waste receptacle shall be fabricated from austenitic corrosion-resisting steel. As an alternate, spring wire, commercial type coated to resist corrosion, may be used for the bail.

The foot pedal shall be formed from not less than 3/64 inch thick CRES. Overall dimensions shall be not less than 1-1/4 inches wide by 1-3/4 inches long, elliptically shaped or flat with the edges turned down. Overall finished thickness shall be not less than 3/8 inch. Attachment to the cover-lifting mechanism shall be by welding or other permanent method. The foot pedal shall not extend more than 2-1/8 inches from the front of the outer container. The bottom of the cutout in the outer container for the foot pedal shall not be more than 13/32 inch from the bottom of the outer container. After opening the waste receptacle, the horizontal member of the lift mechanism shall rest on the bottom of the cutout so that excess foot pressure is directed to a low center of gravity.

The outer container, inner container, and the cover shall be corrosion-resisting steel conforming to AISI 302 or 304 and at least 22 gauge. The inner container shall be seamlessly drawn from one piece of metal. The exterior of the outer container, including the cover, shall be polished to at least a No. 4 commercial finish. The exterior container shall be marked permanently and legibly with the manufacturer's name or registered trademark.

Workmanship. The waste receptacle shall be free from defects which detract from its appearance or impair its serviceability, and shall be free of roughness, sharpness, and burrs.

Unit. Each (EA). Each waste receptacle, as specified, constitutes one unit.

Tests. With the waste receptacle on a level floor surface, the cover shall be opened and closed 50 times in not more than two minutes with the heel of the foot resting on the floor. The waste receptacle shall not tip or tilt and there shall be no distortion or malfunction of any components during or after this test. The inner container shall not leak when filled with water to within one inch of the top and allowed to stand for 24 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:50Z
Check the source to verify that this is the current version before use.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified using conversion tables contained in the latest revision of Federal Standard 376, and all other requirements of this document are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Contractor certification. The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producers' own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements.

Federal Food, Drug and Cosmetic Act. If the product covered by this document has been determined by the U.S. Food and Drug Administration to be under its jurisdiction, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of the Federal Food, Drug and Cosmetic Act, as amended, and regulations promulgated thereunder. In addition, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of all other applicable Federal, State, and local statutes, ordinances, and regulations.

Recovered materials. The offeror/contractor is encouraged to use recovered material in accordance with Public Law 94-580 to the maximum extent practical.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified, preservation, packaging, and packing shall be to a degree of protection to preclude damage to containers and/or contents thereof under normal shipping conditions, handling, etc., involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity, and shall conform to applicable carrier's rules and regulations. Intermediate and exterior package quantities and labeling and marking shall be as specified in the contract and/or order.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:50Z
Check the source to verify that this is the current version before use.

NOTE: The following National Stock Number is covered by this document:

7240-00-788-3953

Ordering data. Intermediate/exterior package quantities, labeling, and marking must be specified in the contract and/or order.

MILITARY INTERESTS:

Custodians:

Army - MD
Navy - MS
Air Force - 03

PREPARING ACTIVITY:

DoD - MB

Agent:

DLA-DM

CIVIL AGENCY COORDINATING ACTIVITIES:

VA-OSS
PHS
FDA-MPQAS
GSA

57345

Project No. 7240-0243

Location: CID/WASTE/H11-3

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:50Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEFENSE LOGISTICS AGENCY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 4966 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Personnel Support Center
ATTN: DPSC-LS
2800 South 20th Street
Philadelphia, PA 19101

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:50Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE
A-A-51055B	

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b ADDRESS *(Street City State ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a Paragraph Number and Wording

b Recommended Wording

c Reason/Rationale for Recommendation

6 REMARKS

7a NAME OF SUBMITTER *(Last First MI)* – Optional	b WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:50Z
Check the source to verify that this is the current version before use.