NOT MEASUREMENT SENSITIVE


MIL-D-3943/15C
6 March 1992
SUPERSEDING
MIL-D-3043/15B
31 March 1987

MILITARY SPECIFICATION SHEET


DECORATION, DISTINGUISHED FLYING CROSS

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.



OBVERSE



REVERSE

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish.

DASH NO:
-1: Regular Size
-2: Miniature

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:48Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

PENDANT:

HEIGHT (Overall):

-1: 1-7/8 inch (4.76 cm) (REF)

-2: 31/32 inch (2.46 cm) (REF)

WIDTH:

-1: 1-11/16 inch (4.29 cm) (REF)

-2: 3/4 inch (1.91 cm) (REF)

THICKNESS (At thickest point):

-1: 0.215 inch ± 0.005 inch (0.546 cm ± 0.012 cm)

-2: 0.105 inch ± 0.005 inch (0.266 cm ± 0.012 cm)

SUSPENSION BAR:

HEIGHT (Overall):

-1: 5/16 inch (0.79 cm) (REF)

-2: 5/32 inch (0.40 cm) (REF)

WIDTH (Overall):

-1: 1-1/2 inch (3.81 cm) (REF)

-2: 3/4 inch (1.91 cm) (REF)

THICKNESS (At thickest point):

-1: 0.085 inch ± 0.005 inch (0.216 cm ± 0.012 cm)

NOTES:

1. A ring formed from red brass shall be soldered to the suspension bar. The ring for Dash No. 1 shall be formed from 0.057 ± .0.002 inch (0.145 cm ± 0.005 cm) diameter wire and shall have an outside diameter of 3/16 inch ± 1/64 inch (0.48 cm ± 0.16 cm). The ring for Dash No. 2 shall be formed from .036 inch ± .002 inch (0.091 cm ± 0.005 cm) diameter wire and shall have an outside diameter of 1/8 inch ± 1/64 inch (0.32 cm ± 0.04 cm).
2. The lug for the Dash No. 1 shall be cut into the working die. The lug shall be 7/32 inch (0.56 cm) in diameter, 1/16 inch ± 1/64 inch (0.16 cm ± 0.04 cm) thick with a 3/32 inch ± 1/64 inch (0.24 cm ± 0.04 cm) hole. The lug shall be flush with the reverse side.
3. Type I Decoration set shall consist of a regular size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Style 6, Type VIII with a Class 1 or 1A pad.
4. The ribbon for the pendant drape and service ribbon shall conform to MIL-R-11589/47.
5. The lapel button shall conform to MIL-L-11484/11.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activities:
Air Force - 82,99
DLA - CT

(Project No. 8455-0649)

User activity:
Air Force - 45

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:48Z
Check the source to verify that this is the current version before use.