NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/16D
1 May 1997
SUPERSEDING
MIL-D-3943/16C
24 June 1994

DETAIL SPECIFICATION SHEET

DECORATION, SOLDIER'S MEDAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:
HEIGHT (Including Lug):
-1: 1-9/16 inches (3.97 cm) (REF)
-2: 27/32 inch (2.14 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:48Z
Check the source to verify that this is the current version before use.

WIDTH:
-1: 1-3/8 inch (3.49 cm) (REF)
-2: 11/16 inch (1.75 cm) (REF)

THICKNESS (At Thickest Point):
-1: 0.230 inch ± 0.010 inch (0.584 cm ± 0.025 cm)
-2: 0.120 inch ± 0.010 inch (0.305 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The pendant ribbon ring shall be rectangular. For Dash No. -1, the ring shall be 17/32 inch (1.35 cm) wide by 3/8 inch (0.95 cm) high (outside measurement) and shall be formed from 0.057 inch ± 0.002 inch (0.030 cm ± 0.002 cm) diameter wire.

3. The pendant ribbon ring for Dash No. -2 shall be an integral part of the lug.

4. The lug for Dash No. -1 shall not be completely drilled through but shall be drilled a maximum of 1/16 inch (0.16 cm) from each side. The hole shall be 1/16 inch (0.16 cm) in diameter.

5. Decoration set shall consist of a regular size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type VIII, Style 6 with a Class 1, 1A or 3 pad.

6. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/137.

7. The lapel button shall conform to MIL-DTL-11484/12.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0887)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:48Z
Check the source to verify that this is the current version before use.