NOT MEASUREMENT SENSITIVE


MIL-D-3943/17D
24 June 1994
SUPERSEDING
MIL-D-3943/17C
31 March 1987

MILITARY SPECIFICATION SHEET

DECORATION, NAVY AND MARINE CORPS MEDAL

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.



OBVERSE REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:
HEIGHT (Including Lug):
-1: 1-5/8 inch (4.13 cm) (REF)
-2: 3/4 inch (1.91 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:49Z
Check the source to verify that this is the current version before use.

DIAMETER:
-1: 1-1/4 inch (3.18 cm) (REF)
-2: 5/8 inch (1.59 cm) (REF)

THICKNESS (At Thickest Point):
-1: 0.150 inch ± 0.010 inch (0.381 cm ± 0.025 cm)
-2: 0.085 inch ± 0.010 inch (0.216 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The lug for Dash No. -1 shall be fabricated from 0.050 inch ± 0.002 inch (0.127 cm ± 0.005 cm) nominal diameter wire with the same material and finish as the pendant. The lug shall have an outside diameter of 0.200 inch ± 0.010 inch (0.508 cm ± 0.025 cm). The lug shall be hard soldered to the top center of the pendant as shown.

3. The lug for Dash No. -2 shall be fabricated from 0.031 inch ± 0.002 inch (0.072 cm ± 0.005 cm) nominal diameter wire with the same material and finish as the pendant. The lug shall have an outside diameter of 0.125 inch ± 0.005 inch (0.317 cm ± 0.012 cm). The lug shall be hard soldered to the top center of the pendant as shown.

4. Reverse shall be flat and suitable for engraving.

5. Decoration set shall consist of a regular size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type VIII, Style 6 with a Class 1 or 1A pad.

6. The ribbon for the pendant drape and service ribbon shall conform to MIL-R-11589/106.

7. The lapel button shall conform to MIL-L-11484/13.

8. The use of any type of plastic packaging material is prohibited.

Custodians:
Army - IH
Navy - NU

Review activities:
Navy - MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0763)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:49Z
Check the source to verify that this is the current version before use.