
MIL-D-3943 / 20B
31 March 1987
SUPERSEDING
MIL-D-3943 / 20A
30 June 1971

MILITARY SPECIFICATION SHEET

DECORATION, GOLD LIFE-SAVING MEDAL AND BAR, COAST GUARD

This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-D-3943.







DASH NO.
-1: GOLD LIFE-SAVING MEDAL, REGULAR
-2: GOLD LIFE-SAVING BAR, REGULAR
-3: GOLD LIFE-SAVING MEDAL, MINIATURE
-4: GOLD LIFE-SAVING BAR, MINIATURE

MATERIAL:

-1,-3:
PENDANT AND SUSPENSION BAR: 24 KARAT GOLD
PENDANT RIBBON ATTACHING BAR: 21 KARAT GOLD
PIN, HINGE AND CATCH, SWIVEL, SWIVEL EYE AND RING: 14 KARAT GOLD

-2,-4:
BAR: 24 KARAT GOLD
PIN, HINGE AND CATCH: 14 KARAT GOLD

DIMENSIONS (INCHES):

-1,-3:
PENDANT:
DIAMETER:
-1: 1-15/32 (REF)
-3: 3/4 (REF)
THICKNESS (AT RIM):
-1: .120 (REF)
-3: .100 (REF)

-2,-4:
BAR:
HEIGHT (OVERALL):
-2: 9/16 (REF)
-4: 9/32 (REF)
WIDTH (OVERALL):
-2: 1-21/32 (REF)
-4: 53/64 (REF)
THICKNESS (AT THICKEST POINT):
-2,-4: .095 (REF)

SUSPENSION BAR:
HEIGHT (OVERALL):
-1: 15/16 (REF)
-3: 25/32 (REF)
WIDTH (OVERALL):
-1: 1-9/16 (REF)
-3: 25/32 (REF)
THICKNESS:
-1,-3: .095 (REF)

FSC 8455

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:51Z
Check the source to verify that this is the current version before use.

WEIGHT (MINIMUM):
-1 (PENDANT AND SUSPENSION BAR): 950 GRAINS
-2 (INCLUDING ATTACHING DEVICE): 253 GRAINS
-3 (PENDANT AND SUSPENSION BAR ONLY ASSEMBLED): 460 GRAINS
-4 (INCLUDING ATTACHING DEVICE): 130 GRAINS

FINISH: LIGHT MATTE FINISH

NOTES:

1. THICKNESS GIVEN FOR INFORMATION ONLY. WEIGHT GOVERNS.
2. THE SUSPENSION BAR SHALL BE FORMED FROM .050 ± .002 INCH DIAMETER WIRE FOR DASH NO. 1 AND .030 ± .002 INCH DIAMETER WIRE FOR DASH NO. 3. THE RINGS SHALL BE GOLD SOLDERED TO THE VERTICAL CENTERLINE OF THE SUSPENSION BAR 5/32 ± 1/64 INCH ABOVE THE TIP OF THE EAGLE'S BEAK FOR DASH NO. 1 AND 5/64 ± 1/64 FOR DASH NO. 3.
3. THE SWIVEL EYE RING SHALL BE FORMED FROM .044 ± .002 INCH DIAMETER WIRE FOR DASH NO. 1 AND .030 ± .002 INCH DIAMETER WIRE FOR DASH NO. 3. THE RINGS SHALL BE SWAGED IN THE SWIVEL DEVICE.
4. THE SWIVEL DEVICE SHALL BE GOLD SOLDERED TO THE TOP OF THE PENDANT.
5. THE RIBBON ATTACHMENT BAR SHALL CONFORM TO TYPE III RIBBON BAR.
6. THE ATTACHING DEVICE FOR DASH NOS. 2 AND 4 SHALL BE LOCATED ON AND GOLD SOLDERED TO THE HORIZONTAL CENTERLINE EQUIDISTANT FROM EACH SIDE. THE ATTACHING DEVICE SHALL BE 1-5/8 ± 1/64 INCH ON CENTERS FOR DASH NO. 2 AND 13/16 ± 1/64 INCH ON CENTERS FOR DASH NO. 4.
7. TYPE I DECORATION SET SHALL CONSIST OF A REGULAR SIZE MEDAL AND BAR. A SERVICE RIBBON AND A LAPEL BUTTON ALL PACKAGED IN A PRESENTATION CASE CONFORMING TO MIL-C-14633, STYLE 6, TYPE VIII WITH, CLASS 1 OR 1A PAD.
8. THE RIBBON FOR THE PENDANT DRAPE AND SERVICE RIBBON SHALL CONFORM TO MIL-R-11589/66.
9. THE LAPEL BUTTON SHALL CONFORM TO MIL-L-11484/7.

Custodians:
Army - IH
Navy - NU

Review activity:
Other - CT

User activity:
Navy - CG

Preparing activity:
Army - IH

(project No. 8455 - 0251)

FSC 8455

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution isunlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:51Z
Check the source to verify that this is the current version before use.