MIL-B-3759E
23 September 1985
SUPERSEDING
MIL-B-3759D
27 May 1976

MILITARY SPECIFICATION

BAG, PERSONAL EFFECTS

This document is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers a cotton sheeting cloth bag 7 inches in diameter and 8 inches in depth with a drawstring closure at the top.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-285 - Thread, Polyester

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

CCC-C-432 - Cloth, Sheeting, Cotton, (Unbleached, Bleached, and Dyed)
CCC-D-950 - Dyeing and Aftertreating Processes for Cotton Cloths
DDD-L-20 - Label: For Clothing, Equipage, and Tentage, (General Use)
DDD-T-86 - Tape, Textile; Cotton, General Purpose (Unbleached, Bleached, or Dyed)
PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-W-530 - Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-G-16491 - Grommet, Metallic

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

2-3-36 - Bag, Personal Effects; Assembly and Details

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

* 3.2 Materials and components (see 6.4)..

3.2.1 Cloth, sheeting, cotton. The cloth shall conform to type IV, class 1 of CCC-C-432.

* 3.2.1.1 Color and treatment. The cloth shall be dyed and treated to conform to type I, class B, inhibitor d of CCC-D-950, shade Olive Drab 7.

3.2.2 Tape, textile, cotton. The cotton tape shall conform to type III, class 1, 1/4 inch width of DDD-T-86.

3.2.2.1 Color and treatment. The tape shall be dyed and treated to conform to class 4 of MIL-W-530, shade Olive Drab 7.

3.2.3 Thread, polyester. The thread for all stitching shall conform to type I or type II, class 1, size B of V-T-285. Thread sizes shall be dyed Olive Drab S-1 (C.A. 66022) and shall show fastness to chlorine bleaching equal to or better than the standard shade sample. If no standard shade sample is available, the thread shall show good fastness to chlorine bleaching.

3.2.4 Grommet, metallic. The grommets and washers shall conform to type II, class 3, size No. 0 of MIL-G-16491.

3.3 Construction. The construction shall conform to the drawing listed in section 2 and shall be as specified herein.

* 3.3.1 Stitches, seams and stitching. All stitching, except bartacking, shall conform to FED-STD-751 as follows:

For all stitching, except the stitching indicated by "Z" on drawing.	-	Type 301, 6 to 8 stitches per inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

For stitching indicated by "Z" on drawing	-	Type 401, 6 to 8 stitches per inch. Chain portion of the stitching shall not appear on the outside of the bag.

Seam allowances shall be maintained with seams sewn so that no raw edges, run-offs, pleats, puckers, or open seams occur. Care shall be taken in sewing to see that no needle chews occur.

* 3.3.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched not less than 1 inch except where ends are turned under or caught in other seams or stitching. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewn.

3.3.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

* a. When thread breaks, or bobbin run-outs occur during stitching, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of stitching. 1/

* b. Except for thread breaks, or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area, continue over the defective area and continue a minimum of 1 inch beyond the defective area onto existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.3.1.2 Type 401 stitching. Thread tension shall be maintained so that there will be no loose stitching. All repairs shall be in accordance with 3.3.1.1a and 3.3.1.1b except substitute 1-1/2 inches for 1 inch wherever 1 inch appears. Repairs to stitch type 401 may be accomplished by use of stitch type 301.

* 3.3.1.3 Bartacking. Bartacking shall be 3/4 ± 1/16 inch in length with 1/8 ± 1/32 inch wide and shall contain 42 stitches. Bartacking shall be free of thread breaks, tight or loose stitching.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

* 3.3.2 Setting of grommets. Holes shall be prepunched to receive the grommets. Holes pre-punched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommets shall be securely clinched without cutting the materials and shall be free of sharp edges or corroded areas and shall not be broken or malformed.

3.4 Marking.

* 3.4.1 Statistics label. The statistics label, 5 inches long by 4 inches wide, shall conform to type VI, class 9 of DDD-L-20, and shall be stitched to the bag in the location shown on the drawing. Fastness of class 9 marking shall be as specified for class 5 marking. Marking on the label shall be printed in 10-point size characters and shall be as follows:

Deceased Military Personnel, Personal Effects

Serial No._____

Grade_____ Name_____

Organization_____ Rank_____

Address_____

Nearest relative_____

Address_____

Killed in action_____ Died of disease_____

Date_____ Hospital_____

Battle area_____ Information_____

_____ _____

Place of burial_____

Point of coordination_____

Description of body_____

_____

Members missing_____

_____

Signed_____

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

* 3.5 Workmanship. The personal effects bag shall conform to the quality of product established by this document. Occurrence of defects shall not exceed the applicable acceptable quality level.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

* 4.3 First article inspection . When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified or qualified in this document or applicable purchase document.

4.4.2 In-process inspection. Inspection of the bag shall be made to determine that holes punches to receive grommets are in compliance with 3.3.2. Whenever nonconformance is noted, correction shall be made to the items affected and to the process.

4.4.3 End item visual examination. The end item shall be examined for the defects listed in below. The lot size shall be expressed in units of one bag. The sample unit shall be one bag. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 10.0 for total (major and minor combined) defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Cloth	Any hole, cut or tear	X	
	Broken or missing yarn, multiple floats clearly visible at normal inspection distance (approximately 3 feet)		X
	Shade bar		X
	Fine or coarse filling bar		X
Tape (draw-strings)	Edge frayed or scalloped		X
Grommets	Broken	X	
	Malformed; fails to perform intended function	X	
	Protective finish omitted, corroded area	X	
	Burr or sharp edge which may cause injury in handling or damage to fabric	X	
Seams and stitching	Open seam on stitch type 301:		
	- for 1/2 inch or less		X
	- for more than 1/2 inch	X	
	Open seam on stitch type 401:		
	- one row of stitching open for 1 inch or less		X
	- one row of stitching open for more than 1 inch	X	
	- both rows of stitching open (not necessarily at the same location)	X	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when one or more skipped or runoff stitches occur. On double stitched seams, a seam shall be classified as open when either one or both sides of a seam are open.		
	Raw edge:		
	- more than 3/4 inch but not more than 1-1/2 inches in length		X
	- more than 1-1/2 inches in length	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Seams and stitching (cont'd)	Thread break:		
	- overstitched less than 1 inch on stitch type 301		X
	- overstitched less than 1-1/2 inches on stitch type 401		X
	NOTE: Thread breaks not overstitched shall be classified as open seams.		
	Skipped stitches:		
	- overstitched less than 1 inch on stitch type 301		X
	- overstitched less than 1-1/2 inches on stitch type 401		X
	NOTE: Skipped stitches not overstitched shall be classified as open seams.		
	Needle chews resulting in cut, tear or hole	X	
	One or more required rows of stitching omitted	X	
Stitching ends	Overstitched less than 1 inch (except where ends are turned under in a hem or are held down by other stitching)		X
Seam type	Wrong seam type	X	
Stitch type	Wrong stitch type	X	
Stitch tension	Loose resulting in exposed bobbin or top thread for more than 2 inches		X
	Tight, as evidenced by puckering of fabric for more than 2 inches	X	
Stitches per inch	Less than minimum specified:		
	- one stitch		X
	- two or more stitches	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Stitches per inch	More than maximum specified:		
	- one stitch		X
	- two or more stitches	X	
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy places or in turning corners shall be classified as follows:		
	a. Within the minor defect classification - no defect		
	b. Within the major defect classification - minor defect		
Stitching indicated by "Z" on drawing	Chain portion of stitching shows on outside of bag		X
Components and assembly	Any component part not fabricated of applicable referenced material	X	
Construction details:			
Hems	Formed on outside of bag in lieu of inside	X	
	Seams badly pleated or puckered		X
Drawstrings	One or both caught in hem stitching failing to allow complete closing of bag	X	
	Loops not threaded through grommets	X	
Bartacking	Dimensions of any bartack not as specified		X
	One bartack omitted on either side seam		X
	Two bartacks omitted on either side seam	X	
	Loose or tight, incomplete or broken		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Construction details:			
Body of bag	Formed with more than 2 pieces of fabric	X	
Bottom of bag	Ends of seam joining bottom halves staggered at seams joining bottom to body by more than 3/8 inch		X
Label	Omitted, incorrect, illegible, misplaced, or characters not as specified	X	
Cleanness	Grease or oil stains clearly noticeable; thread ends not trimmed to 1/2 inch or less		X

4.4.4 Dimensional examination. The bag shall be examined for the defects listed below. The lot size shall be expressed in units of bags. The sample unit shall be one bag. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

Examine	Defect	Classification Major	Minor
Grommets	Set off-center of hem by more than 1/4 inch		X
	Set off-center of closing seam by 1/8 inch or more		X
Hem	Width of hem less than specified by more than 1/4 inch		X
Bartacks	Set beyond location indicated on drawing by more than 1/4 inch		X
Overall dimensions	Not within tolerances specified on drawing	X	
	NOTE: The diameter of the finished bottom shall be taken from the bottom edge of body across bottom sections		

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

4.4.5 Packaging inspection. An inspectiion shall be made to determine that preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.4.6 Palletization inspection. An inspection shall be made to determine that the palletization complies with section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length,width, or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Ten bags shall be neatly stacked in a bundle with labels facing up and securely tied with cotton tape or twine.

* 5.1.2 Commercial. Bags shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

* 5.2.1 Level A packing. Six hundred bags, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

* 5.2.2 Level B packing. Six hundred bags, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-626. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

* 5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the fiberboard shipping container shall be grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

* 5.2.3 Commercial packing. Bags preserved as specified in 5.1 shall be packed in accordance with ASTM D 3951.

* 5.3 Palletization. When specified (see 6.2), bags packed as specified in 5.2, shall be palletized on a four-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The bag is used to store delivery mail and personal effects, such as wallet, watch, ring and other valuables pending inventory and return of the next of kin of deceased military personnel.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this document.
b. When a first article is required (see 3.1.2, 4.3 and 6.3).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. When weather-resistant boxes required for level B packing (see 5.2.2.1).
e. When palletization is required (see 5.3).

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample consisting of at least one completed finished bag assembly. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

* 6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

6.5 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - NU

Preparing activity:

Army - GL

Project No. 8465-0771

Review activities:

Army - MD
DLA - CT

User activity:

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-3759E	Bag, Personal Effects

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
3b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP: 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:25Z
Check the source to verify that this is the current version before use.