MIL-B-002619B(DM)
13 August 1964
USED IN LIEU OF
MIL-B-2619A
30 December 1957

MILITARY SPECIFICATION

BAG, PATIENT'S EFFECTS

This limited coordination Military specification has been prepared by the Defense Medical Supply Center based upon currently available technical information, but it has not been approved for promulgation as a coordinated revision of Military Specification MIL-B-2619A. It is subject to modification. However, pending its promulgation as a coordinated Military specification, it may be used in procurement.

1. SCOPE

1.1 This specification covers a patient's effects bag, olive drab color, in one type and size, approximately 10 inches in diameter and 12 inches deep, containing an inserted waterproof pocket 9-1/2 inches deep. The bag is closed by means of drawstrings in the top of the bag.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

Federal

V-T-276	Thread, Cotton.
CCC-T-191	Textile Test Methods.
DDD-L-20	Label; For Clothing, Equipage, and Tentage, (General Use).
DDD-T-86	Tape, Textile; Cotton, General Purpose (Unbleached, Bleached, or Dyed).
PPP-B-636	Box, Fiberboard.

FSC 6530

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:24Z
Check the source to verify that this is the current version before use.

Military

JAN-C-380	Cloth, Cotton, Sheeting, Coating-Quality.
MIL-G-16491	Grommet, Metallic.

STANDARDS

Federal

FED. STD. No. 751	Stitches, Seams, and Stitchings.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MS16686	Medical Services Symbol.

DRAWING

Defense Medical Supply Center

Drawing 20717	Bag, Patient's Effects (2 sheets).

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. Except as herein specified, materials shall conform to the applicable portions of the specifications, standards, and drawing listed in section 2, and shall be capable of meeting the requirements shown therein. When materials to be used are not specifically designated, those used shall be of the highest commercial quality, and entirely suitable for the purpose intended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:24Z
Check the source to verify that this is the current version before use.

3.1.1 Basic cloth for bag. The basic cloth for the body of the bag shall be cotton cloth, coating-quality sheeting, vat dyed olive drab No.7 shade, conforming to type II, class A, B, C, D, E, or F of Specification JAN-C-380. No other coating or finish shall be applied to the cloth, the pocket being the only portion of the bag which is coated as hereinafter specified.

3.1.2 Basic cloth for pocket. Basic cloth for pocket shall be the same as specified in 3.1.1.

3.1.2.1 Coating compound. The coating compound shall be a suitable polymerized or copolymerized vinyl resin, or synthetic rubber suitably pigmented and plasticized. The compound shall be nontoxic, non-irritating and shall contain no water soluble material. Thermoplastic polyvinyl butyral is not permitted. If polyvinyl butyral is used, it shall be so compounded and modified as to permit the material to undergo thermosetting or heat conversion. After conversion, the finished coating shall not have thermoplastic properties and shall not be sensitive to ethanol.

3.1.2.2 Coated fabric. The coated fabric shall be cotton cloth, coating-quality sheeting olive drab No.7 shade, synthetic resin coated or synthetic rubber coated. The fabric, before coating, shall meet the requirements of 3.1.1. After coating, it shall be suitable for fabricating into a pocket to protect material contained therein from moisture. The coating compound shall be applied on one side of the cloth. The compound shall have good adhesion to the cloth, shall be flexible, free of tackiness, resistant to abrasion and scratching, and shall not tender the fabric. When subjected to a temperature of 0°Fahrenheit (F.), the coating shall not crack when folded sharply. The coated fabric shall be free of pinholes, free of windows, and shall conform to the requirements specified in table I. When tested as specified in table II, the loss in tensile strength of the cloth shall not exceed 25 percent of original, and material shall neither become stiff and brittle nor soft and tacky. If the coating on the fabric is thermosetting plastic or thermosetting rubber, the fabric shall be cured before being fabricated into pockets.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:24Z
Check the source to verify that this is the current version before use.

Table I.

Weight of coating per sq. yd in ounces	Tearing strength scale reading		Water resistance hydrostatic test	Resistance to blocking at 180°F.	Low temperature effect	Adhesion of coating
	Warp	Filling				
4.0 minimum 8.0 maximum	25(min)	20(min)	15 pounds	No adhesion exudation or damage to surface	Shall neither crack nor lose more than 50 percent hydrostatic resistance	6 pounds(min)

3.1.3 Draw tape. The draw tape shall be cotton, vat-dyed olive drab shade No.7, 5/8-inch wide, conforming to type I, class 3 of Specification DDD-T-86.

3.1.4 Thread, cotton. The cotton thread used for all stitching shall be vat-dyed olive-drab shade S-1. The dyed thread shall show good fastness to chlorine bleaching and laundering as tested as specified in Specification V-T-276. The thread shall conform to the following types and sizes:

For needle - type IB3, 3-ply, ticket No. 40.
For bobbin or looper - type IA3, 3-ply, ticket No. 50.

3.1.5 Cloth, label. The cloth label shall be a 2-1/2 (± 1/8) by 2-1/2 (± 1/8) inches conforming to type I of Specification DDD-L-20, except that the label shall be blank. The label shall be stitched to the front of the bag in the location as shown in the drawing. The blocking temperature shall be 104.4°± 1 Centigrade (220°± 1.8°Fahrenheit) as tested as specified in Specification DDD-L-20.

3.1.6 Indentification markings. The identification markings shall conform to type IV of Specification DDD-L-20. The identification markings shall bear the legends size characters and be located as shown in the drawing. The Medical Services Symbol shall conform to type I of Standard MS16686.

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:24Z
Check the source to verify that this is the current version before use.

3.1.7 Grommets, metallic, brass, black chemical finish, with toothed washers, No. 0. The grommets with washers shall conform to type II, class 3 of Specification MIL-G-16491.

3.2 Construction. The construction shall conform in all respects to the drawing and as specified herein. The coated side of the fabric shall be on the inside of the pocket. Both ends of the pocket shall be bartacked along the inside stitch. The two draw tapes shall be not less than 38 inches long.

3.2.1 Stitching - machine.

3.2.1.1 Types of stitching. Stitching, except bartacking, shall conform to Federal Standard No. 751, as follows:

For all stitching, except stitching indicated by "Z" on the drawing:

Stitch type 301, 8 to 10 stitches to the inch.

For stitching indicated "Z" on the drawing:

Stitch type 301 or 401, 8 to 10 stitches to the inch. When stitch type 401 is used, the chain portion of stitching shall not appear on the outside of the bag.

3.2.1.1.1 Stitch type 301 stitching. All thread breaks in stitching shall be backstitched not less than 1-inch at each break (with the exception of bartacking). All stitching shall be backstitched at the ends to prevent raveling, except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained so that there will be no loose stitching and the lock will be embedded in the center of the material sewed.

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:24Z
Check the source to verify that this is the currentversion before use.

3.2.1.1.2 Stitch type 401 stitching. All thread breaks in stitching, stitch type 401, shall overstitched not less than 1 inch at each break. Thread tension shall be maintained so that there will be no loose stitching.

3.2.1.2 Bartacking. Bartacking for draw tapes shall be not less than 5/8 inch in length with 1/8 inch bight, and shall contain not less than 28 stitches, on superimposed tape, as shown on drawing. Bartacking for both ends of pocket shall be not less than 1/2 inch in length with 1/8 inch bight and shall contain not less than 28 stitches. Bartacking shall be free of thread breaks and loose stitching. All thread ends shall be trimmed and removed from the bag.

3.2.2 Setting of grommets. Holes punched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommets shall be tightly clinched without cutting the materials.

3.3 Workmanship. The finished bag shall conform to the quality of product established by this specification. The occurrence of defects shall not exceed the limits set by the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 20261O-16T21:24Z
Check the source to verify that this is the current version before use.

4.2 Inspection for acceptance. Inspection shall be conducted in accordance with Standard MIL-STD-105 unless otherwise specified hereinafter.

4.2.1 Inspection of components. An inspection (examination and testing) of components shall be made in accordance with the quality assurance provisions contained in the applicable subsidiary specifications referenced herein to the extent applicable, except that this specification shall govern in the event of conflict. In addition inspection shall be performed on components listed in table II for the characteristics noted.

4.2.2 Inspection of the end item. An examination shall be made on the finished bag for visual and dimensional defects.

4.2.2.1 Examination for visual defects. The defects found during this examination shall be classified in accordance with the defects listed in 4.2.2.2 and 4.2.2.3. The sample unit for this examination shall be one bag. The lot size shall be expressed in units of one bag. The sample size shall be selected in accordance with inspection level II of Standard MIL-STD-105. The acceptable quality levels shall be as specified below:

Major	2.5 defects per 100 units
Total(Major and minor combined)	10.0 defects per 100 units

4.2.2.2 General defects.

	Classification	
	Major	Minor
Fabric defects:		
a. Any hole, cut, tear, or any seriously weakening defect such as smash, float, loose slub and needle chew expected to develop into holes..	X	
b. Any mend, patch	X	
c. Coating tacky, cracked, blistered, flaky, or thin.	X	
Seams and stitching:		
a. Wrong seam or stitch type:		
—Seriously affecting serviceability.....	X	
—Slightly affecting serviceability.....		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:24Z
Check the source to verify that this is the current version before use.

		Classification Major	Minor
b.	Open seams:		
	On stitch type 301:		
	— More than 3/8 inch		X
	— More than 1 inch	X	
	On stitch type 401; except run-offs	X	
	Run-offs:		
	— More than 3/8 inch		X
	— More than 1 inch	X	
	Raw edges more than 3/4 inch when securely caught in stitching (except on label and on edge of pocket opening)		X
c.	Seams badly puckered or pleated		X
d.	Loose tension resulting in loose seam	X	
e.	Loose tension resulting in loosely exposed bobbin or top thread		X
f.	One to two stitches per inch less than minimum specified		X
	Three or more stitches per inch less than minimum specified	X	
	One or more stitches in excess of maximum specified		X
g.	Stitching gage or double needle stitching under or over specified width by more than 1/16 inch		X
h.	Thread breaks overstitched or backstitched less than 1 inch		X
i.	Stitching ends not backstitched (except where ends are held down by other stitching or turned under in a hem)		X
j.	Chain portion of 401 stitching appearing outside bag		X
k.	One bartack omitted on either side seam, or misplaced, not properly securing draw strings		X
l.	Bartacks not as specified (see 3.4.1.2)	X	
m.	More than one bartack omitted on either side seam, or misplaced, not properly securing draw strings	X	
n.	Bartack stitching loose or broken		X
	Cleanness:		
	Grease or oil stains clearly noticeable; threads ends not trimmed throughout and loose threads not removed		X

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:24Z
Check the source to verify that this is the current version before use.

	Classification Major	Minor
Components and assembly:		
a. Any defect of components or assembly (not specifically classified in this section), seriously affecting serviceability.....	X	
b. Any defect of components or assembly (not specifically classified in this section), slightly limiting serviceability.....		X
4.2.2.3 Detailed defects		
Top hem:		
Construction not as specified, width less than specified by 1/4 inch or more.....		X
Grommets:		
a. Size not as specified, misplaced, set with barrel extending beyond edge of body seams or set with rim extending to top of bottom edges of hem, improperly clinched.....		X
b. Omitted, unfinished, broken, cracked, or distorted failing to serve purpose; burrs or sharp edges.....	X	
Drawstrings:		
a. Omitted or caught in hem stitching.....	X	
b. Looped end of drawstrings extend less than 2 inches from grommets with top of bag fully extended.....		X
Marking:		
Omitted, incorrect, illegible, misplaced, or dimensions not as specified.....		X
Label:		
a. Omitted.....	X	
b. Misplaced more than 1 inch from location specified...		X
c. Printing on label.....	X	X

Source: https://assist.dla.mil -- Downloaded: 202640-16T21:24Z
Check the source to verify that this is the current version before use.

	Classification Major	Mino
Inside pocket:		
a. Omitted	X	
b. Top edge not caught in body hem stitching	X	
c. Misplaced, coated side on outside of pocket, dimensions less than specified by more than 1/2 inch		X

4.2.3 Examination for dimensional defects. Any measurement deviating from the nominal dimensions and tolerances included on the drawing shall be scored as a measurement defect. The sample unit for this examination shall be one bag. The lot size shall be expressed in units of one bag. The sample size shall be selected in accordance with inspection level S-3 of Standard MIL-STD-105. The acceptable quality level shall be 4.0 (one class) defects per 100 units.

4.2.4 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packed, selected just prior to the closing operations. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of containers in the end item inspection lot. The sample size shall be selected in accordance with inspection level S-2 of Standard MIL-STD-105. The acceptable quality level shall be 4.0 (one class) defects per 100 units.

Examination	Defects
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence, or method of application.
Materials	Any component missing. Any component not as specified. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, loose strapping, inadequate stapling, bulging or distortion of containers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:24Z
Check the source to verify that this is the current version before use.

Examination	Defect
Content	Number of items per container is more or less than specified.

4.3 Tests. The method of testing specified in Specification CCC-T-191, wherever applicable shall be followed. The physical and chemical values specified in section 3 apply to the average of the determinations made on a sample unit for test purposes as specified in the applicable test methods. The lot shall be unacceptable if one or more sample units fail to meet any of the test requirements specified. The selection of the sample size shall be as follows:

Lot size	Sample size
800 or less	2
801 to 22,000	3
22,001 and over	5

The unit of product for lot formation and the unit of product for testing shall be as shown below:

Component	Lot size expressed as	Sample unit for testing
Cloth, cotton sheeting(coated)	Yard	2 square yards.

Table II. Instructions for testing

Component	Characteristic	Reference requirement	Spec. CCC-T-191 Test method
Coated cloth	Weight	Table I	5041
	Tearing strength	Table I	5132
	Water-resistance Hydrostatic method	Table I	5512
	Resistance to blocking	Table I	5872
	Low-temperature effect	Table I	5874
	Adhesion of coating	Table I	5970
	Accelerated aging	3.1.2.2	5852

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:24Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Level A

5.1.1.1 Unit package. Each bag shall be wrapped with kraft paper of uitable weight. Wrapping shall be adequately secured to prevent accidental pening.

5.1.1.2 Intermediate package. Ten bags, wrapped as specified, shall be ackaged in a fiberboard box constructed and closed to conform to class 2, 5c or W5s, style RSC of Specification PPP-B-636.

5.1.2 Level C. Bags shall be packaged in accordance with the manufacturer's ormal practice.

5.2 Packing.

5.2.1 Level A. Twenty-four (24) fiberboard boxes (240 bags, packaged as pecified in 5.1.1) shall be packed within a snug-fitting shipping container onstructed and closed in accordance with class 2, V3c or V3s, style RSC of pecification PPP-B-636, except that strapping shall not be required.

5.2.1.1 Packing variation permitted. If the required number of units to e shipped is less than the number of units specified to be overpacked in an xterior container, such units shall be packed in an exterior container of uitable size and design acceptable to a common carrier, which shall insure safe elivery to destination.

5.2.2 Level C. Bags, packaged as specified in 5.1.2 shall be packed in manner acceptable to common carriers for safe transportation to point of estination specified in shipping instructions at the lowest transportation rate or such supplies.

5.3 Marking.

5.3.1 Interior packages. Each unit package and each intermediate package hall be marked in accordance with Standard MIL-STD-129. When labels are utilized, aterproofing shall be required only when applicable carton is fabricated of ater-resistant material. Contract or purchase order number and name of contractor hall be shown.

Source: https://assist.dla.mil -- Downloaded: 202640-16T21:24Z
Check the source to verify that this is the currentversion before use.

5.3.2 Exterior container. Exterior container shall be marked in accordance with Standard MIL-STD-129. In addition, the letter "L" shall precede the Federal stock number. One space shall be allowed between the letter "L" and the first digit of the stock number. The terms "Stock number" or "FSN" shall not be indicated.

6. NOTES

6.1 Intended use. The bag covered by this specification is used at a patient's bedside to contain allowed personal effects and toilet articles in a convenient and orderly manner during the time the patient is undergoing treatment in a medical field installation. A blank label shall be provided on the front of the bag on which the patient's identification and any other desired information can be written at the time the bag is issued to the patient.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2)

6.3 Bag, Patient's Effects, weighs approximately 4 ounces

6.4 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Military requirements.

Custodians:
Army. - MD
Navy. - MS
Air Force. - 03

Review activities:
Army. - MD
Navy. - MS
Air Force. - 13

Preparing activity:
Defense Supply Agency. - DM

Review information is current as of the date of this document For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 202610-16T21:24Z
Check the source to verify that this is the current version before use.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES" IN WHAT WAY?

4. REMARKS (ATTACH ANY PERTINENT DATA WHICH MAY BE OF USE IN IMPROVING THIS SPECIFICATION. IF THERE ARE ADDITIONAL PAPERS, ATTACH TO FORM AND PLACE BOTH IN AN ENVELOPE ADDRESSED TO PREPARING ACTIVITY)

SUBMITTED BY (PRINTED OR TYPED NAME AND ACTIVITY)	DATE

DD FORM 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:24Z
Check the source to verify that this is the current version before use.

CAUTION

NOTICE TO BIDDERS/OFFERORS

DO NOT CONDITION OR BASE YOUR BID/OFFER ON ANY CURRENT PROCUREMENT ON THE INFORMATION SUBMITTED ON THIS FORM SINCE ANY CHANGES OR DELETIONS IN THE SPECIFICATIONS MAY RENDER YOUR BID/OFFER NON-RESPONSIVE IN WHICH CASE IT CANNOT BE CONSIDERED FOR AWARD.

Fold Under

DEFENSE SUPPLY AGENCY
DEFENSE MEDICAL SUPPLY CENTER
3RD AVENUE AND 29TH STREET
BROOKLYN, N.Y., 11232

OFFICIAL BUSINESS

POSTAGE FEES PAID
DEFENSE SUPPLY AGENCY

Defense Supply Agency
Defense Medical Supply Center
ATTN: Directorate of Technical Operations (Code T-M5)
3rd Avenue and 29th Street
Brooklyn, N.Y., 11232

Source: https://assist.dla.mil -- Downloaded: 202640-16T21:24Z
Check the source to verify that this is the current version before use.