GG-N-775C
May 20, 1974
SUPERSEDING
Int. Fed. Spec. GG-N-007758(GSA-FSS)
February 3, 1971,
Fed. Spec. GG-M-61
March 25, 1937, and
Fed. Spec. GG-M-71
May 27, 1930

FEDERAL SPECIFICATION

NUMBERING MACHINES, OFFICE TYPE, HAND-OPERATED

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers hand-operated numbering machines for general office use (see 6.1).

1.2 Classification. The numbering machines shall be of the following types, number of wheels, and number of movements as specified (see 6.2, 6.3, 6.4 and 6.5).

Type I. Automatic number advancing.

Six wheels.
3 Movements.
5 Movements.

Seven wheels.
8 Movements.

Eight wheels.
4 Movements.

Nine wheels.
5 Movements

Ten wheels.
4 Movements.

Type II. Manual number advancing (lever operated).

Six wheels.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

GG-I-550 - Inking Pad, Office Type Numbering Machine.
TT-I-540 - Ink, Numbering Machine.
UU-P-121 - Paper, Bond and Writing, White and Colored.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Stayed (Included Stay Material).
PPP-B-676 - Boxes, Setup.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Table for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza., Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Qualification. The numbering machines furnished under this specification shall be products which have been inspected, tested and have passed the qualification requirements specified herein, and have been listed on, or approved for listing on the applicable Qualified Products List (see 6.3).

3.2 Standard product. All numbering machines furnished under this specification shall be the manufacturer's commercial product, except for changes necessary to comply with the requirements of this specification.

3.3 Material. Material shall be as specified. Where material is not definitely defined it shall be of a quality and composition best suited for the intended purpose, and shall insure satisfactory operation in conformity with the requirements of this specification.

3.4 Design, construction, and performance. The numbering machines shall conform to the design, construction, and performance requirements specified hereinafter. The machines shall essentially consist of a frame, housing, base plate, numbering wheels, operating mechanism, handle, and inking pad. The numbering machines shall function properly, when tested as specified in 4.6. All machines shall print legible impressions for not less than 300,000 actuations without mechanical or structural failure, when tested as specified in 4.7. The design of type II machine shall emable the user to operate the machine with one hand.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

3.4.1 Frame, housing, and base plate. At the option of the manufacturer, the frame, housing, and base plate shall be manufactured of sheet steel, cast metal, or a combination thereof. Alternatively, the frame may be made of plastic. The parts shall be of such design, construction and strength to assure that the assembled parts will securely hold together, and plastic parts will not break, or crack, when tested as specified in 4.6 and 4.7. The machine shall be of such design to permit an unobstructed view of the printing opening in the base plate when the machine is in operating position with the plunger raised. The printing opening in the base plate shall be equipped with a guide to indicate the printing line.

3.4.2 Type wheels. The type wheels shall be made of cold-finished carbon or alloy steel of such composition, design, and construction to assure compliance with the performance requirements and tests of this specification. Each wheel, except the last one, shall contain the characters 0 through 9; the last wheel is not required to have an 0. The characters shall be Gothic or Roman type, 11/64 inch high. A plus tolerance of 1/32 inch, and minus tolerance of 1/64 inch will be permitted. The characters shall be engraved on the wheels or produced by another method provided they are of equal quality. Character faces shall be unbroken, of uniform thickness of line, free from dents and burrs, and shall not be knife-edged. The wheels shall permit adjustments to print the desired figures.

3.4.3 Operating mechanism, type I machines. Machines specified as having 3 movements shall operate to (1) repeat any setting any number of times, (2) consecutively print numbers from any initial setting to its capacity, and (3) print any setting twice then advance to the next consecutive number from any setting to its capacity. Machines with four, five, and eight, movements shall perform the three operations of 3-movement machines, and in addition the four movement machine shall print any setting from once through three times (triplicate), the five movement machine from once through four times (quadruplicate), and the eight movement machine from once through seven times (septuplicate), respectively, before advancing to the next consecutive setting. The numbers to be printed in any operation shall automatically come in contact with the inked pad immediately preceding each stroke of the machine. Machines shall be equipped with wheels that are automatic up to at least six wheels (up to 999,999). Additional wheels above six may be automatic, or may be designed to operate by manual manipulation.

3.4.3.1 Selector device. A mechanical selector device to obtain the desired movements shall be provided. The selected movements shall be manually set, and the setting shall not accidentally change, when tested as specified in 4.6.1, and 4.6.2. The settings shall be permanently indicated and visible with the machine in the printing position.

3.4.4 Operating mechanism, type II machines. The operating mechanism shall be lever-operated to advance the wheels. When the machine plunger handle is in the released position the lever shall advance the wheels in proper consecutive order, one numeral for each operation of the lever, when tested as specified in 4.6.3. The number to be printed in any one operation shall automatically come in contact with the inked pad immediately preceding each stroke of the machine. The lever shall be smoothly finished and shaped to permit comfortable operation.

3.4.5 Handle. The plunger handle shall be made of smoothly finished suitable hardwood or plastic. It shall be of a size and shape which will comfortably fit the hand.

3.4.6 Inking pad. The inking pad material shall be one piece of felt conforming to the material and thickness requirements of GG-I-550. The pad shall be readily accessible for inking and shall be replaceable.

3.4.7 Stylus. Each machine shall be furnished with a stylus or other appropriate device for manual advancing of individual wheel.

3.5 Finish. Plastic frames and handles shall be smooth and polished. Hardwood handles shall be sanded and coated with an even coat of appropriate varnish, paint or lacquer. The metal parts of the machine shall have a decorative protective finish in accordance with manufacturer's commercial practice.

3.6 Identification marking. Numbering machines shall be legibly and permanently marked with the manufacturer's name or trademark, model number, serial number of the machine, and, when specified (see 6.2), the words "U.S. Property".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. All wood and plastic parts shall be free from chips, cracks, rough or sharp edges. Metal parts shall be devoid of rust, dents, burrs, rough or sharp edges. The numbering machines shall be free from defects or imperfections which may affect appearance, impair serviceability, or constitute a hazard to the user.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspections and tests. The inspection and testing of numbering machines shall be classified as follows:

a. Qualification inspections and tests. Qualification inspections and tests are performed on sample numbering machines submitted for listing in the Qualified Products List (QPL). The qualification inspections and tests shall consist of all visual inspections of 4.5.1, the applicable performance tests of 4.6, and the life test of 4.7.
b. Acceptance inspections and tests. Acceptance inspections and tests are performed on sample numbering machines selected to determine acceptance of the lot under contract. The acceptance inspections and tests shall consist of the visual inspections and the applicable tests of section 4 , except 4.7.

4.3 Instructions for qualification inspections and tests.

4.3.1 Testing activity. Qualification inspections and tests, or any re-inspection or retesting that may be required, shall be conducted at a laboratory designated by the General Services Administration.

4.3.2 Testing cost. The cost of the inspections and tests shall be borne by the applicant, and shall be payable to the General Services Administration as directed by the Federal Supply Service. Samples for inspections and tests shall be supplied by the applicant at no expense to the Government. The Government will not be responsible for any expense resulting from the following:

a. Shipment of the sample to or from the laboratory.
b. Damage during testing.
c. Damage or loss of sample while at the laboratory.

4.3.3 Samples for qualification inspections and tests. For each of the numbering machines of the same type, number of wheels, and number of movements intended for inclusion in the QPL, two machines shall be supplied at a time and place designated by the General Services Administration. The samples shall be identified by securely attached durable tags, legibly marked, as follows:

a. Title, number, and date of this specification.
b. Type, number of wheels and movements.
c. Date of manufacture.
d. Manufacturer's name and address.
e. Location of manufacturer's plant, if other than above address.

4.3.4 Inspection and test procedures. The following procedures shall govern the inspections and testing of all products submitted for qualification under this specification:

a. Samples shall be submitted for qualification only after the applicant has obtained written authorization from the General Services Administration.
b. Samples will be inspected and tested in sequence of their receipt at the testing facility.
c. One numbering machine shall be utilized for visual examination and applicable performance tests, and one for the life test.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:53Z
Check the source to verify that this is the current version before use.

d. Qualification inspections and tests may be discontinued at any time the product fails to meet one or more of the requirements set forth in this specification. The manufacturer may be permitted to make modification on samples during the inspection and testing phase where such modification, in the judgment of the General Services Administration and the testing facility, are clearly in the interest of the Government.
e. In case of failure of sample, consideration will be given to the request by the manufacturer for resubmission for re-inspection and retesting only after it has been clearly shown that changes have been made in the product which the Government considers sufficient to warrant re-inspection or retesting.

4.3.5 Changes in design or construction. Once the numbering machines have been inspected and tested and approved for listing in the QPL, no changes shall be made in its design or construction unless prior authorization is obtained from the Federal Supply Service, General Services Administration.

4.4 Sampling for acceptance inspections and tests.

4.4.1 Size of lot. All numbering machines of the same type, number of wheels and movements presented for inspection at one time shall be considered a lot for the purpose of examinations and tests.

4.4.2 Sampling for inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise specified.

4.4.3 Sampling for visual examination. Numbering machines shall be taken at random from each lot in accordance with MIL-STD-105. A sample unit shall be one numbering machine. The numbering machines shall be examined for defects listed in table I. The Inspection Level shall be S-4, and the Acceptable Quality Level (AQL) shall be 4.0 percent defective.

4.4.4 Sampling for preparation for delivery requirements. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed and shall be examined for defects listed in table II. The lot shall be the number of shipping containers offered for delivery at one time. The Inspection Level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

4.4.5 Sampling for performance tests. Numbering machines shall be taken at random from each lot in accordance with MIL-STD-105. The sample unit shall be one numbering machine and shall be tested as specified in 4.6. The Inspection Level shall be S-2, and the AQL shall be 4.0 percent defective.

4.5 Examination.

4.5.1 Visual examination. Samples taken in accordance with 4.4.3 shall be examined for defects listed in table I. Any sample having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number of the sample, the entire lot represented by the sample shall be rejected.

TABLE I. Classification of defects

Examine	Defects
Type, number of wheels, and movements.	Not as specified (see 1.2).
Material.	Not as specified (see 3.3 and section 3.4).
Design and construction.	Not in accordance with section 3.4.
	Any part missing or not securely attached (see section 3.4).
	Housing does not permit visibility of printing opening (see 3.4.1).
	Base plate not equipped with guide to indicate the printing line (see 3.4.1).
Type wheels	Not as specified (see 3.4.2).
Selector device (type I only).	Not as specified (see 3.4.3.1).
Lever (type II only).	Not as specified (see 3.4.4).
Handle.	Not as specified (see 3.4.5).
Inking pad.	Inking pad missing, or not as specified (see 3.4.6).
Stylus.	Stylus missing, (see 3.4.7).
Finish.	Not as specified (see 3.5).
Identification marking.	Not as specified (see 3.6).
Workmanship.	Not in accordance with 3.7.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:53Z
Check the source to verify that this is the current version before use.

4.5.2 Inspection of preparation for delivery. Samples selected in accordance with 4.4.4 shall be examined for defects listed in table II, to determine that packaging, packing and marking comply with the requirements of section 5. Defects of closure listed shall be examined on shipping containers fully prepared for delivery.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Marking (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence or method of application.
Materials	Any component missing, or not as specified. Any component damaged, or affecting serviceability.
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling. Bulging or distortion of containers.
Contents	Number per container is more, or less than required. Gross weight exceeds the requirements of the box specification.

4.6 Performance tests. Samples taken in accordance with 4.4.5 shall be subjected to the following tests to assure compliance with the applicable requirements in 3.4 through 3.4.4 of this specification. Any numbering machine having one or more defects shall be rejected. If the number of defective numbering machines exceeds the acceptance number for the sample, the lot represented by the sample shall be rejected. The inking pad of each sample machine shall be inked in accordance with the manufacturer's recommendation, with ink conforming to UU-T-540. The printing shall be performed on bond paper conforming to type III of UU-P-121 (17 x 32 inches, 1,000 sheets - 32 pounds). During the printing process the paper shall be placed on a smooth, even, and rigid surface.

4.6.1 Consecutive number printing, type I machine only. The machine shall be set at "consecutive" movement and operated to print the numbers 1 through 10, and thereafter the unit shall be operated and set so that each wheel will be indexed by the previous wheel through each numeral on the wheel. Advancing may be accomplished by setting the wheel preceding the wheel to be advanced on the numeral 8 and advancing it by operating the machine to the numeral 1. For example, in testing the "tens" wheel, the first two wheels would be set at the following numbers 18, 28, 38, 48, 58, 68, 78, 88, and 98, and the machine operated until the following numbers appears, in respective order: 21, 31, 41, 51, 61, 71, 81, 91, and 101. The numbers set for testing the "hundreds" wheels would likewise be 198, 298, 398, et cetera; and the remaining wheels tested in similar manner (see 3.4.3).

4.6.2 Movement test, type I machine only. The machine shall be operated two times to test the operation of each movement of the machine (duplicate, triplicate, et cetera). Operate the machine a minimum of 20 cycles for each movement (excluding "repeat" movement) and check for proper advancement of the numbers for the applicable movements (see 3.4.3). A cycle shall consist of moving the plunger handle down to the position where the number prints legibly and has returned to the original position.

4.6.3 Manual number advancing, type II machine only. The test cycle in 4.6.1 shall be duplicated except that number advancing shall be accomplished by manipulation of the lever. Sufficient numbers shall be repeated to determine that advancement is accomplished only by manipulation of the lever.

4.6.4 Legibility of print. The machine shall be operated to print ten impressions within a period of ten seconds. Each wheel shall print a character, and the wheel setting shall be in the following order (as far as the number of wheels allows): 4567890123. The tenth impression shall be sharp, of uniform density, free from impressions other than the type faces, free from excessive ink, and the characters shall be in line.

4.7 Life test. Machines shall be put into operation to print the number of cycles specified in 3.4. A cycle shall consist of moving the plunger handle down once, to the position where the number is printed legibly, and returned to the original position. Total elapsed time for one cycle shall not exceed one second, but the testing need not be continuous. The pad shall be inked as required, and the machine secured in proper position in the testing apparatus. For type I machines the first 200,000 cycles of the life test shall consist of operating the machine at the "consecutive" movement. The machine shall then be operated 5000 cycles at each of the remaining movements (including "repeat"). At the completion of this testing phase, the machine shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

reset to the "consecutive" movement and operated until a total of 300,000 cycles for all movements has been completed. The test apparatus shall be equipped with a counter to count the number of cycles performed, which shall be periodically compared with the actual number printed by the numbering machine to determine that the latter is advancing properly (NOTE: At the completion of the 300,000 cycling operations the actual number printed by the machine will not be 300,000 due to the operation of movements other than "consecutive", such as "duplicate", "repeat", et cetera.) The numbers of type II machine shall be reset every 10,000 cycles.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each numbering machine shall be packaged in a close-fitting box conforming to PPP-B-566, PPP-B-665 or to PPP-B-676. The manufacturers commercially marked box shall be acceptable providing that it meets the intent of any of these specifications. Each box shall be secured to prevent accidental opening.

5.1.2 Level C. The numbering machines shall be individually packaged to insure protection during shipment and safe delivery to destination.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Thirty numbering machines of like stock number packaged as specified in 5.1 shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant. Closure and waterproof sealing of the boxes shall be in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Thirty numbering machines of like stock number packaged as specified in 5.1 shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. Closure of boxes shall be in accordance with method II of the appendix to PPP-B-636.

5.2.3 Level C. The numbering machines packaged as specified in 5.1 shall be packed to comply with the National Motor Freight Classification rules or the Uniform Freight Classification rules.

5.3 Marking. In addition to any special marking required by the contract or order, all marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. Marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The numbering machines covered by this specification are intended for office use to imprint numbers on correspondance and forms.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type, number of wheels, and number of movements required (see 1.2).
(c) Whether the words "U.S. Property" are required (see 3.6).
(d) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).
(e) Whether civil or military marking is required (see 5.3).

6.3 Qualified Products List. With respect to the products requiring qualification, awards will be made only for such products as having, prior to the time set for opening of bids, been tested and approved for inclusion on the applicable Qualified Products List whether or not such products have actually been so listed by that date. The attention of the suppliers is called to this requirement, and manufacturers are urged to arrange to have the products they propose to offer to the Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Federal Supply Service, General Services Administration, Washinton, D.C. 20406, and information pertaining to qualification of products may be obtained from that activity.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:53Z
Check the source to verify that this is the current version before use.

6.4 Movements. Automatic number advancing machines normally perform the movements indicated below.

TABLE III. Movements of type I machines

Number of Movements	Movements performed
3	Consecutive, Duplicate, Repeat.
4	Consecutive, Duplicate, Triplicate, Repeat.
5	Consecutive, Duplicate, Triplicate, Quadruplicate, Repeat.
8	Consecutive, Duplicate, Triplicate, Quadruplicate, Quintuplicate, Sextuplicate, Septuplicate Repeat.

6.5 Change of classification. This specification includes changes in the classification of numbering machines. The following numbering machines were deleted:

Type I, six wheels, 4, 8, and 9 movements.
Type I, seven wheels, 3, 4, 5, and 9 movements.
Type I, eight wheels, 3, and 9 movements.
Type II, seven wheels.

DOD HAS WAIVED COORDINATION INTEREST

User activity:

Army - GL

Preparing activity:

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 25 cents each.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:53Z
Check the source to verify that this is the current version before use.