GG-S-00750B(GSA-FSS)
January 7, 1970
SUPERSEDING
Int. Fed. Spec. GG-S-00750a(GSA-FSS)
March 17, 1965

INTERIM FEDERAL SPECIFICATION

STENCIL DUPLICATING PRINT KIT, HAND STAMP

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D.C., 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers two types of hand stamp stencil duplicating print kits.

1.2 Classification. The stencil duplicating print kits covered by this specification shall be of the following types, as specified (see 6.2).

Type I - Stencil duplicating area under 15 square inches.

Type II - Stencil duplicating area of 15 square inches and over.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

QQ-C-585 - Copper-Nickel-Zinc Alloy Plate, Sheet, Strip and Bar (Copper Alloy Numbers 735, 745, 752, 762, 766, and 770).
UU-P-121 - Paper, Bond and Writing, White and Colored.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:52Z
Check the source to verify that this is the current version before use.

Military Specification:

MIL-P-116 - Methods of Preservation.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. The material shall be as specified. When the material is not definitely defined, it shall be of good quality and of such composition best suited for the intended purpose.

3.1.1 Nickel silver. Nickel silver used in any component of the kit shall conform to QQ-C-585, copper alloy number 735, 752, or 770.

3.2 Design. The stencil duplicating print kits shall include all components specified hereinafter. The stencil duplicators shall be designed to stamp clear imprints, when tested as specified in 4.4.1.1. Paper stencil and ink shall be used as the printing medium. Unless otherwise specified, the ink pad shall not be preinked. A completely saturated ink pad shall be capable of producing a minimum of 750 clear imprints without re-inking.

3.2.1 Type I. The type I print kit shall be designed to use stencils having a duplicating area under 15 square inches and of the size specified in the invitation to bid, and shall include the following components (see 3.4):

Hand stamp	Stylus
Ink	Tray
Stencils	Typing board 1/
Brush	Instruction pamphlet

3.2.2 Type II. The type II print kit shall be designed to use stencils have a duplicating area of 15 square inches or over and of the size specified in the invitation to bid, and shall include the following components (see 3.4):

Hand Stamp	Stylus
Ink	Tray
Stencils	Instruction pamphlet
Brush	

1/ When required by the design of the stencil duplicator or stencil, a typing board shall be furnished with the kit.

3.3 Construction. The components of the hand stamp stencil duplicating print kit shall be manufactured to assure compliance with the requirements specified hereinafter. The components shall withstand heavy duty usage and continue to function satisfactorily.

3.4 Components.

3.4.1 Hand stamp. The stencil duplicator shall have a suitable handle shaped for convenient holding. The frame shall securely hold the stencil, of the size specified in the invitation for bids, in the proper position during printing operation. The design and construction of the hand stamp shall permit placement and removal of the stencil with ease and without tools, and inking of the ink pad shall be accomplished with little effort. The ink pad shall provide the proper flow of ink to insure clear and even imprints.

3.4.2 Tray. The tray shall be manufactured from metal. It shall serve as a base on which the hand stamp rests when not in use. The tray shall hold the hand stamp upright and keep the marking medium from contact with other surfaces, and protect attached stencil from damage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

3.4.3 Ink. The ink shall be suitable for the stencil duplicators and stencils, and the ink shall not dry or cake. Each type I kit shall be supplied with not less than two fluid ounces of ink, and each type II kit shall be supplied with not less than four fluid ounces of ink. Unless otherwise specified, the ink shall be black.

3.4.4 Stencil. The stencils shall be of good quality capable of producing a minimum of 5000 reproductions. When required by the design of the hand stamp, the stencil paper shall be suitably framed, or the backing or stencil paper shall be properly marked to indicate the reproduction area. A minimum of twenty-four stencils shall be supplied in type I kit, and a minimum of twelve stencils and not less than six stencil cushion sheets shall be supplied in type II kit, of the size specified in the invitation for bids.

3.4.5 Typing board. When required (see 3.2.1), a typing board shall be included in the kit to serve as a holding and backing device for typing on stencil.

3.4.6 Stylus. The stylus shall have a medium non-rotating ball point designed for writing, ruling, and drawing. The metal part of the stylus shall be firmly embedded in the handle.

3.4.7 Brush. The brush shall be designed for spreading ink when replenishing the ink pad.

3.4.8 Instruction pamphlet. The instruction pamphlet shall contain all necessary instructions in the use of the hand stamp and accessories. The instructions shall be clear, concise and easily followed to enable persons unfamiliar with the stencil duplicator to correctly use and maintain the kit.

3.5 Finish. All metal surfaces, except corrosion resistant steel, and nickel-silver shall be treated to resist corrosion and present a good appearance. All non-metallic surfaces shall be appropriately finished.

3.5.1 Hand stamp. Ferrous metal parts, except corrosion resistant steel, shall be nickel or chrome plated (see 4.4.2). Non-ferrous parts, except nickel-silver parts, shall be anodized or coated with a baked enamel finish of good quality.

3.5.2 Tray. Ferrous metal trays, except corrosion resistant steel, shall be nickel or chrome plated (see 4.4.2). Non-ferrous metal trays, except nickel-silver trays, shall be anodized or coated with a baked enamel finish of good quality.

3.5.3 Stylus. The stylus point, if other than corrosion resistant steel, shall be nickel or chrome plated (see 4.4.2). If the handle is other than plastic, it shall have an enamel coating.

3.6 Identification marking. Each hand stamp stencil duplicating print kit shall be permanently and legibly marked with the name or trademark of the manufacturer.

3.7 Workmanship. All components and parts shall be of good quality, and shall be devoid of defects which adversely affect the appearance or might impair the serviceability or durability of the duplicating print kit. All parts and components shall be devoid of burrs, slivers, sharp edges or other defects which might constitute a hazard to the user.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Size of lot. All hand stamp stencil duplicating print kits presented for inspection at one time shall be considered a lot for the purpose of examinations and tests.

4.2.2 Sampling for inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise specified.

4.2.3 Sampling for visual and dimensional inspection. A random sample of hand stamp stencil duplicating print kits shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one kit. The components shall be examined for defects listed in table I. The Inspection Level shall be S-3, and the Acceptable Quality Level (AQL) shall be 4.0 percent defective.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:52Z
Check the source to verify that this is the currentversion before use.

4.2.4 Sampling for preparation for delivery. Sampling shall be in accordance with MIL-STD-105. For examination of contents the sample unit shall be one shipping container fully prepared for delivery, selected just prior to closing operation. The inspection level shall be S-1 and the AQL shall be 2.5 defects per hundred units.

4.2.5 Sampling for performance test. A random sample of hand stamp stencil duplicating print kits shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one kit. The components shall be tested as specified in 4.4.1. The inspection level shall be S-1, and the AQL shall be 6.5 percent defective.

4.2.6 Sampling for plating test (nickel and chrome). When applicable, one sample unit shall be taken from each lot and tested as specified in 4.4.2.

4.3 Examination.

4.3.1 Visual and dimensional examination for end items. Samples taken in accordance with 4.2.3 shall be examined for defects listed in table I. Any hand stamp stencil duplicating print kit in the sample containing one or more defects shall be rejected. If the number of defective print kits exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

TABLE I. Examination for defects

Examine	Defects
Type	Type not as specified.
Material	Material not as specified.
Design and Construction	
Hand Stamp	Hand stamp missing. Handle not shaped for convenient holding (see 3.4.1). Stencil not securely held by hand stamp (see 3.4.1). Stencil not easily placed and removed without tools (see 3.4.1).
Tray	Tray missing. Tray does not hold hand stamp upright (see 3.4.2). Tray does not prevent marking medium from contacting other surfaces (see 3.4.2). Tray does not properly support hand stamp to prevent damage to stencil (see 3.4.2).
Ink	Quantity of ink not as specified (see 3.4.3). Color of ink not as specified (see 3.4.3).
Stencil	Required number of stencils not furnished (see 3.4.4). Stencil cushion sheets not included in type II kit (see 3.4.4). Stencils not as specified (see 3.4.4).
Typing board (when required)	Typing board missing (see 3.2.1 and 3.4.5). Typing board not as specified (see 3.4.5).
Stylus	Stylus missing. Point of stylus not medium and non-rotating ball-point suitable for writing, ruling, and drawing (see 3.4.6). Point not firmly embedded in handle (see 3.4.6).
Brush	Brush missing. Brush not suitable for spreading ink on ink pad (see 3.4.7).
Instruction pamphlet	Instruction pamphlets not written in accordance with 3.4.8.
Finish	Finish not as specified (see 3.5).
Identification marking	Identification marking not as specified (see 3.6).
Workmanship	Not in accordance with 3.7.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:52Z
Check the source to verify that this is the currentversion before use.

4.3.2 Examination of preparation for delivery requirements. Samples selected in accordance with 4.2.4 shall be examined for defects listed in table II, to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.

4.4 Tests.

4.4.1 End item test. Samples taken in accordance with 4.2.5 shall be tested as described in 4.4.1.1. Any kit having one or more defects shall be rejected. If the number of defective kits exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected.

4.4.1.1 Performance test. A performance test shall be conducted on the hand stamp stencil duplicating print kit as directed in the instruction pamphlet. Strictly adhering to the instructions given in the pamphlet, two stencils shall be prepared and used to make 25 imprints from each stencil. One stencil shall be prepared with a stylus and shall contain a minimum of three lines, and the other stencil shall be prepared with a typewriter and shall have minimum of four lines of typing. The impression shall be made on sheets of 32-pounds (17 X 22--1,000 sheets) bond paper conforming to the requirements for type III of UU-P-121. Examination of the imprints shall assure compliance with 3.2, and that the instruction pamphlet complies with the requirements of 3.4.8.

4.4.2 Test for plating (nickel or chrome). Component(s) from the sample kit selected in accordance with 4.2.6 having nickel or chrome plating shall be subjected to one of the following tests applicable to the finish of the component. Failure to identify an authorized plating shall be cause for rejection of the entire lot.

4.4.2.1 Identification for presence of nickel. Using a medicine dropper, apply several drops of nitric acid (HNO_3), Sp. gr. 1.42 to the metal surface. At the end of one minute observe acid drop; a clear pale green color indicates presence of nickel.

4.4.2.2 Identification for presence of chrome. Using a medicine dropper, apply several drops of concentrated hydrochloric acid (HCl), Sp. gr. 1.18. A green solution identifies presence of chromium.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. The components (see 3.4) each commercially packaged and comprising one complete kit shall be packaged together, method IC-2 in accordance with MIL-P-116. Fiberboard meeting the requirements of PPP-F-320 shall be provided as full size compartments or half-slotted separators.

5.1.2 Level B. The components (see 3.4) each commercially packaged and comprising one complete kit shall be packaged in a close-fitting fiberboard box. The box shall be manufactured from material conforming to PPP-F-320. Fiberboard compartments or half-slotted fiberboard separators shall be provided for the components in the box. The box shall be so designed to provide ready access to all components of the kit in the compartments or separators. The lid or cover shall be capable of repetitive opening and closing without a rupture or tearing at the score lines.

5.1.3 Level C. The kits shall be packaged in accordance with the suppliers commercial practice.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:52Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Kits of like description shall be packed in a close-fitting box conforming to PPP-B-585, class 3, PPP-B-591, class II, PPP-B-601, type III, PPP-B-621, class 2, PPP-B-636, W5c or PPP-B-640, class 2, grade A. The boxes shall be closed and strapped in accordance with the requirements of the applicable specification or appendix thereto. The gross weight of the triple-wall fiberboard box and the wood boxes shall not exceed approximately 200 pounds. The gross weight of the PPP-B-636 fiberboard box shall not exceed the weight limitations of the box specification.

5.2.2 Level B. Eighteen unit packages of kits of like description shall be packed together in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 Level C. The kits shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Standard pack (civil agency procurements). The standard pack for civil agency procurements shall be as specified in paragraphs 5.1.2 and 5.2.2 (see 6.2).

5.4 Marking.

5.4.1 Civil agencies. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.4.2 Military agencies. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The hand stamp stencil duplicating print kit is intended for use as a readily available and quickly prepared means of duplicating and applying addresses, notes, cautions, etc., to shipping tags, boxes, envelopes, packages and other objects or may be used for printing cards, forms, notices, memorandums, etc.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Type (see 1.2).
(c) Size of stencil (see 3.2.1, 3.2.2 and 3.4.4).
(d) Color of ink, if other than as specified (see 3.4.3).
(e) Whether ink pads should be preinked (see 3.2).
(f) Levels of packaging, packing and any special marking required (see 5.1, 5.2 and 5.4).

GSA DC 79-9092

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, fold, staple, and mail.

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

GG-S-00750B(GSA-FSS) Stencil Duplicating Print Kit, Hand Stamp

2. CONTRACT NO. *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC.	10. ADDRESS *(Number, Street, City, State and Zip Code)*

11. NAME AND TITLE OF SUBMITTER	12. DATE

FORM GSA FEB 80 2200

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:52Z
Check the source to verify that this is the currentversion before use.

FOLD

GENERAL SERVICES ADMINISTRATION

OFFICIAL BUSINESS

POSTAGE & FEES PAID
GENERAL SERVICES ADMINISTRATION

General Services Administration
Federal Supply Service (FMSO)
Washington, D. C. 20406

FOLD

GSA FORM FEB 68 2200

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.