GG-S-745a
JULY 25, 1956
SUPERSEDING
Fed. Spec. GG-S-745
March 29, 1954

FEDERAL SPECIFICATION

STAPLERS AND STAPLES, PAPER FASTENING, OFFICE TYPE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. CLASSIFICATION

1.1 Staplers.

1.1.1 *Types, classes, and styles.*—Staplers covered by this specification shall be of the following types, classes, and styles, as specified (see 6.3):

Type I.—Desk type.
Class A.—Preformed-staple type.
Style 1.—Combination standard-duty stapler and tacker. (The tacker feature is not applicable to long-reach style 1 machines.)
Style 2.—Heavy-duty stapler.
Class B.—Wire-spool stapler, standard duty.
Type II.—Plier type, preformed-staple type, standard duty.

1.1.2 *Reach or range.*—(See 3.3.1.2.)

1.2 Staples, preformed. (See 3.3.2 for wire-spool staples.)

1.2.1 *Sizes.*—Preformed staples covered by this specification shall be of the following sizes, as specified:

Size 1 (standard duty).—One-half-inch crown width with a plus tolerance of 0.005 inch and a minus tolerance of 0.001 inch. Leg length, ¼ inch with a plus tolerance of $\frac{1}{64}$ inch. (See 3.6.1.1.)

Size 2 (heavy duty).—One-half-inch crown width, with a plus or minus tolerance of 0.025 inch, when so specified in the invitation for bids. Leg lengths, ¼, ⅜, and ½ inch, as specified in the invitation for bids. (See 3.6.1.2.)

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and standards.—The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification:

Federal Specifications:

P-S-661—Solvent, Dry-Cleaning.
GG-S-746—Staple Removers, Office Type.
NN-B-591—Boxes, Fiberboard, Wood-Cleated (for Domestic Shipment).
NN-B-621—Boxes, Wood, Nailed and Lock-Corner.
UU-T-116—Tape, Paper, Gummed, Water-Resistant.
LLL-B-631—Boxes; Fiber, Corrugated (for Domestic Shipment).
LLL-B-636—Boxes; Fiber, Solid (for Domestic Shipment).
PPP-B-566—Boxes, Folding, Paperboard.
PPP-B-585—Boxes; Wood, Wirebound.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

PPP–B–601—Boxes, Wood, Cleated-Plywood.
PPP–B–676 — Boxes, Set-Up, Paperboard.
PPP–T–76—Tape, Paper, Water-Resistant, Pressure-Sensitive.

Federal Test Method Standard:

No. 151—Metals; Test Methods.

Military Specifications:

JAN–P–103—Packaging and Packing for Overseas Shipment — Boxes; Wood Cleated; Solid Fiberboard.
JAN–P–106—Packaging and Packing for Overseas Shipment — Boxes; Wood Nailed.
JAN–P–108—Boxes, Fiberboard, Corrugated and Solid (Military Type).
MIL–P–116—Preservation, Methods of.
MIL–B–121—Barrier Material, Greaseproof, Flexible (Waterproofed).
MIL–B–4229—Boxes, Paperboard, Metal-Stayed.
MIL–B–10377 — Boxes; Wood-Cleated, Veneer, Paper Overlaid.
MIL–L–10547 — Liners, Case, Waterproof.

Military Standards:

MIL–STD–105 — Sampling Procedures and Tables for Inspection by Attributes.
MIL–STD–129—Marking for Shipment and Storage.

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards from established distribution points in their agencies.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

2.2 Other publication.—The Consolidated Freight Classification Rules, of the issue in effect on date of invitation for bids, forms a part of this specification.

(Application for copies of the referenced publication should be addressed to the Consolidated Classification Committee, 202 Chicago Union Station, Chicago 6, Ill.)

3. REQUIREMENTS

3.1 Material.—The steel, rubber, rivets, bolts, screws, and other material used in the manufacture of paper-fastening staplers and staples shall be of a quality suitable for manufacture of staplers and staples. Material shall be free from all defects and imperfections which might affect the serviceability of the finished products, and shall meet the quality and performance requirements of this specification.

3.2 Design, construction, and operation of staplers.—Staplers shall be designed for paper fastening for use with the type and size of preformed wire staples or spool of wire as further specified in 3.3.2 and 3.6. The staplers shall be suitable for desk use or hand operation and shall operate smoothly and easily when driving and clinching or tacking a proper-size staple to a firm seat. (See 3.7.) After each stapling operation the operating lever, plunger or other device shall automatically spring back to the starting position and the base of the vertical chute shall return to its normal position, which shall be not less than ¼ inch above the top of the anvil. The feeding mechanism shall operate automatically so as to feed the new staple or sufficient wire to form a new staple beneath the plunger after each stapling operation. The machine shall be jam-free, provided with

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

an automatic stroke control, or designed so as to permit clearing should a jam occur under normal operating conditions. Assembly of parts shall be welding, riveting, or by bolts, nuts, and screws. All removable parts of stapling machines of the same make and model shall be interchangeable. All machines shall be constructed so that repair and interchange of parts may be effected. Type I, class A, style 1, standard-duty staplers and other than long-reach shall be designed so that a tacker may be obtained therefrom without the use of tools.

3.2.1 *Springs.*—All springs used in the types of staplers described herein shall be made of spring steel containing not less than 0.6 percent carbon. The springs shall be heat-treated to sufficient hardness to provide the necessary spring properties for satisfactory functioning of the staplers. Attachment of spring to follower shall be of such design as to obviate a bending fatigue point which, with repeated flexure, would tend to cause rupture of the spring at this point.

3.2.2 *Staple drivers.*—Staple drivers shall be made of spring steel containing not less than 0.6 percent carbon and hardened equally over the whole length to a Rockwell hardness of not less than 48, C scale. Type I, class B wire-spool staple drivers shall be of cold-rolled casehardened steel.

3.2.3 *Anvils.*—Anvils shall be a separate unit attached to the base and shall not be an integral part of the base. The anvil shall be made of steel, either hardened throughout or casehardened. The thickness of the case shall be not less than 0.010 inch and the hardness shall be not less than 85 (15–N–85) Rockwell superficial. Steel hardened throughout shall have equivalent hardness.

3.2.4 *Follow-blocks, hinge pins, and plungers (or other device activating the staple driver).*—Follow-blocks and hinge pins shall be made from iron or steel having a Rockwell hardness of not less than 65, B scale. Plungers (or other devices activating the staple drivers) shall be of iron or steel as specified above or of zinc alloys suitable for the purpose. However, if the machine is of the enclosed follow-block type in which the staples are inserted directly against the follow-block and where in normal operating position, it is impracticable to push the follow-block against the staples with the hand, a Rockwell hardness of not less than 50, B scale, will be permitted in the follow-block. Hinge pins for bases shall be made of steel not less than $\frac{5}{32}$ inch in diameter at the bearing surface.

3.2.5 *Handles.*—The striking surface of the handles shall be of suitable material for the purpose intended. If a plastic material or hard rubber is used, it shall have toughness, resiliency, and ability to withstand shock.

3.2.6 *Bases, bearings, and channels.*

3.2.6.1 *Bases.*—Bases shall be constructed of steel or commercial zinc cast. Thickness of steel shall be not less than 0.060 inch; commercial zinc cast, if used, shall be of equivalent structural strength. Each base shall be provided with durable rubber pads or feet to protect desk or table surfaces, except long-reach stapling machines which may be designed for fastening to a desk or table.

3.2.6.2 *Bearings.*—Bearings shall be constructed of steel, unless an integral part of a commercial zinc cast base. Thickness of steel shall be 0.060 inch; commercial zinc cast, when used, shall be of equivalent structural strength.

3.2.6.3 *Channels.*—Channels shall be constructed of steel not less than 0.035 inch thick.


3.3 Type I, desk-type stapler.

3.3.1 *Class A, preformed-staple type.*—Type I, class A stapler shall be constructed for use of preformed staples cemented in


Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

strip form and shall be considered a standard-duty desk stapler. It shall consist of a base, a staple channel and follower spring to hold the staples tight at all times, a staple driver, attached to a plunger or striking arm, clinching anvil, and other components found necessary for proper functioning and operation, and as specified in 3.2 through 3.2.6.3.

3.3.1.1 *Clinching anvil.*—Unless otherwise specified, provision shall be made in the construction of the style 1 stapler (see 3.3.1.4) to provide a clinching anvil to produce the "standard" clinch and either the "temporary" or the "pin" clinch (see fig. 1). The procuring agency shall have the option of ordering staplers with anvils to produce any of the three kinds of clinches. The style 2 stapler (see 3.3.1.5) shall have one anvil, standard clinch.



Pin clinch



Temporary clinch



Standard clinch

FIGURE 1.—Clinches.

3.3.1.2 *Range of stapling.*—Unless otherwise specified, reach or range of stapling shall be not less than 2 inches for stapler loading 105 staples, and shall be not less than 3¼ inches for stapler loading 210 staples. At the option of the procuring agency, 8-inch, 12-inch, or 16-inch reach may be specified for style 1 staplers. When specified in the invitation for bids, an adjustable depth gage shall be furnished with the 8-, 12-, and 16-inch-reach machines.

3.3.1.3 *Vertical chute.*—The vertical chute, through which the staples are ejected by the driver, shall be not less than 0.0215 inch nor more than 0.025 inch wide. All parts of the vertical chute with which the staples come in contact shall be of through-hardened or casehardened steel. The surfaces of the vertical chute shall be sufficiently smooth to provide efficient operation.

3.3.1.4 *Style 1, combination standard-duty stapler and tacker.*—The stapler shall accommodate size 1 preformed staples as specified in 1.2.1 (see 3.2). It shall have the capacity to accept a strip of staples containing 210 staples.

3.3.1.5 *Style 2, heavy-duty stapler.*—The stapler shall accommodate size 2 preformed staples as specified in 1.2.1 (see 3.3.1.1). It shall have the capacity to accept a strip of staples containing at least 100 staples.

3.3.2 *Class B, wire-spool stapler (standard duty).*—Type I, class B stapler shall be constructed so as to accommodate a spool of wire to make its own staples and shall be considered a standard-duty desk stapler. Adequate provision shall be made to prevent the wire from loosening on the spool. The stapler shall be capable of cutting a sufficient section of wire, forming it properly, inserting it into the vertical chute, and admitting it into the clinching device for each stapling operation. Unless otherwise specified, the remainder of the construction of the wire-spool stapler shall be substantially the same as that of the type I, class A stapler. Staples shall consist of spools which contain sufficient wire of a nonferrous metal (brass) for making approximately 5,000 staples with a crown width of 5/16 inch and leg length of 3/16 inch. The diameter of wire shall be 0.0165 inch ± 0.001 inch. The diameter of sides of spool shall be 1¾ inches. The width of spool shall be ¾ inch plus or minus 1/32 inch. Diameter of hole in spool shall be approximately ¾ inch. Wire shall be wound on spool

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

so as to unwind easily without tangling or becoming taut on spool as wire is pulled forward by stapler. The wire shall be such as to permit penetration and clinching to a firm seat without buckling or fracturing of the staple when tested as specified in 4.3. Clinched staples shall be extracted without fracturing when tested as specified in 4.3.

3.3.2.1 *Clinching mechanism.*—The clinching mechanism shall be substantially the same as that of the type I, class A stapler and as described in 3.3.1.1.

3.3.2.2 *Range of stapling.*—The range of stapling or reach shall be not less than 3 inches nor more than 4 inches.

3.3.2.3 *Vertical chute.*—The vertical chute and mechanism shall be of proper dimensions and shall be nonclogging and nonjamming.

3.4 Type II, plier-type stapler.—Type II, plier-type stapler shall be designed and constructed for hand operation and shall house the staple strip in such a position as to make a compact stapler.

3.4.1 *Jaw opening.*—The jaws shall automatically open to a width of ⅜ inch to ½ inch.

3.4.2 *Stapling range.*—The stapling range or throat depth shall be not less than 1 inch.

3.4.3 *Capacity.*—The plier stapler shall hold a minimum of 105 staples.

3.4.4 *Size of staples.* — The plier stapler shall use a "standard" staple appropriate for general office use, such as fastening papers and the like.

3.4.5 *Clinching mechanism.*—The clinching mechanism shall be such as to produce a "standard" clinch as shown in figure 1 or both the standard and pin clinches.

3.4.6 *Staple chute and plunger.*—The staple chute through which staples are ejected and the plunger mechanism shall be designed and constructed to operate smoothly and without clogging or jamming.

3.5 Finish.

3.5.1 *Cleaning.*—All metal surfaces shall be thoroughly cleaned and free from dirt, oil, grease, and moisture, before applying the finish.

3.5.2 *Surfaces.*—All metal surfaces shall be either painted or plated. If painted, sufficient coats of paint shall be applied and shall conform to best commercial standards of quality and method of application. Plating, if used, shall be cadmium, chrome or nickel, and application shall be in accordance with best commercial practice for this type of commodity. All unpainted or unplated metal parts shall have a corrosion-resisting finish or protective coating.

3.6 Staples.—Unless otherwise specified by the procuring agency, staples shall conform to the requirements specified below. Preformed paper-fastening staples shall be made of tinned, galvanized or liquor-finished steel. (See 3.3.2.)

3.6.1 *Staples (preformed) for plunger or lever-type staplers.*

3.6.1.1 *Size 1, standard-duty.* — Size 1, standard-duty staples shall be preformed, unless otherwise specified, and cemented together in strip form, one behind the other. Leg of staple shall have blunt or chisel-point end. Cement shall be applied smoothly and shall adhere to each staple sufficiently to insure its exit from the vertical chute without accumulation therein. Staples shall be made from wire 0.0195 inch in diameter. After fabrication no face of the wire shall measure less than 0.017 inch nor more than 0.0205 inch. The temper and carbon content of the wire shall be such as to permit penetration and clinching to a firm seat without buckling or fracturing of the crown or leg when tested as specified in 4.3. Clinched

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

staples shall be extracted without fracturing when tested as specified in 4.3. Unless otherwise specified, staples shall be supplied in strips of 210 staples; minimum of 5,000 staples per box.

3.6.1.2 *Size 2, heavy-duty.*—Size 2, heavy-duty staples shall be preformed and shall have a wire cross section of approximately 0.020 inch by 0.030 inch. Staples shall be cemented together in strip form, one behind the other. Cement shall be applied smoothly and shall adhere to each staple sufficiently to insure its exit from the vertical chute without accumulation therein. Leg shall have blunt or chisel-point end. The temper of the wire (high carbon content) shall be such as to permit penetration and clinching to a firm seat without buckling or fracturing of the crown or leg when tested as specified in 4.3. Clinched staples shall be extracted without fracturing when tested as specified in 4.3. Unless otherwise specified, staples shall be supplied in strips of 100 to 140 staples.

3.6.2 *Staples for wire-spool staplers.*— (See 3.3.2.)

3.6.3 *Staples for plier staplers* shall be same as used for type I, class A staplers and as described in 3.6.1.1.

3.7 Performance.

3.7.1 *Standard duty.*—Type I, class A, style 1 and class B, and type II staplers shall be capable of driving and clinching preformed staples to a firm seat through the required thickness of paper when tested as specified in 4.3.4.1. This shall be accomplished without malformation of the staple. Machines shall also meet the striking test requirement of 4.3.4.3.

3.7.2 *Heavy duty.*—Type I, class A, style 2 staplers shall be capable of driving and clinching staples to a firm seat through the required thickness of paper when tested as specified in 4.3.4.2. This shall be accomplished without malformation of the staple. Machine shall also meet the striking test requirement of 4.3.4.3.

3.8 Identification marking.—The manufacturer's name or trade-mark shall be stamped in a conspicious place on each stapler.

3.9 Workmanship.—The alignment of parts of staplers and close tolerance of operating components shall be in keeping with the quality and performance requirements of this specification. Staplers and staples shall be free from burrs and sharp or rough edges, and other defects which affect the appearance or which might affect the serviceability of the items.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Sampling.

4.1.1 *Lot.*—Unless otherwise specified in the invitation for bids, contract, or order, a lot shall consist of all staplers and staples submitted for inspection at the same time and under the same conditions of manufacture and assembly.

4.1.2 *Visual and dimensional inspection.*—A random sample shall be taken from the lot in accordance with Military Standard MIL–STD–105, Inspection Level I.

4.1.3 *Samples for tests* shall be taken at random from each lot in accordance with Military Standard MIL–STD–105, Inspection Level L–6.

4.2 Inspection.

4.2.1 *Visual and dimensional.* — Staplers and preformed staples taken as specified in 4.1.2 shall be inspected for conformance to design, construction, operation, dimensions, capacity, finish, marking, and workmanship. The acceptable quality level shall not exceed 4.0 percent defective in accordance with Military Standard MIL–STD–105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

4.2.2 *Tests.*—Staplers and preformed staples taken as specified in 4.1.3 shall be tested as specified in 4.3. The acceptable quality level shall not exceed 2.5 percent defective in accordance with Military Standard MIL–STD–105.

4.3 Tests.

4.3.1 *Rockwell hardness.*—Hardness shall be determined in conformity with Federal Test Method Standard No. 151.

4.3.2 *Clinching.*—(See note 1 and 4.3.4.)

4.3.2.1 *Standard duty, except class B.*—The clinching anvil of the standard-duty paper-fastening machine shall be set to produce the standard clinch. A full strip of size 1 staples conforming to this specification shall be inserted in the machine and at least 20 staples shall be driven and clinched to a firm seat through 2 sheets of 16-pound good-quality sulphite bond paper (basis weight 17 by 22—500 sheets). This test shall be repeated, using 30 sheets of the same type paper, and at least 100 stapling operations shall be performed. Clinched staples shall be examined for proper clinch and for fracture.

4.3.2.2 *Standard duty, class B.*—A paper-fastening machine and spool of wire conforming to this specification shall be used for this test. At least 20 stapling operations shall be performed, driving and clinching staples to a firm seat through 2 sheets of bond paper as specified in 4.3.2.1. This test shall be repeated, using 16 sheets of same type paper, and at least 100 stapling operations shall be performed. Clinched staples shall be examined for proper clinch and for fracture.

4.3.2.3 *Heavy duty.*—A heavy-duty paper-fastening machine shall be used for this test. At least sixty size 2, ¼-inch-leg-length staples conforming to this specification shall be driven and clinched to a firm seat through 40 sheets of bond paper as specified in 4.3.2.1. This test shall be repeated, using seventy-five ⅜-inch-leg-length staples and 80 sheets of same type paper, and again, using one hundred ½-inch-leg-length staples and 100 sheets of same type paper. Clinched staples shall be examined for proper clinch and for fracture.

4.3.3 *Removal.* — The stapled sheets of paper used in the respective clinching tests of 4.3.2 shall be used for this test. Staples clinched as specified in 4.3.2.1 and 4.3.2.2 shall be extracted with a staple remover conforming to the requirements for type II of Federal Specification GG–S–746. Staples clinched as specified in 4.3.2.3 shall be extracted with a staple remover conforming to type I of Federal Specification GG–S–746. Extracted staples shall be examined for fracture.

NOTE 1.—Staples used in the clinching and removal tests are to be considered fractured when broken into two or more pieces. Malformation of the staple shall be considered as improper clinch.

4.3.4 *Performance.*—(See 4.3.2.)

4.3.4.1 *Standard-duty staplers.*

4.3.4.1.1 *Type I, class A, style 1, and type II.*—Using 2 sheets and then 30 sheets of 16-pound, good-quality sulphite bond paper (basis weight 17 by 22—500 sheets), stapler shall drive and clinch preformed staples to a firm seat without malformation of the staples.

4.3.4.1.2 *Type I, class B.*—The test specified in 4.3.4.1.1 shall be performed for type I, class B wire-spool stapler using 16 sheets of bond paper as specified above.

4.3.4.2 *Heavy-duty (type I, class A, style 2) staplers.*—Using bond paper as specified in 4.3.4.1.1, 40 sheets for ¼-inch leg length, 80 sheets for ⅜-inch leg length, and 100 sheets for the ½-inch-leg-length staples, stapler shall drive and clinch each size staple to a firm seat without malformation of the staples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

4.3.4.3 *Striking test.* — Staples shall be properly clinched in six sheets of ordinary bond paper when machine knob is struck a sharp blow by operator. Staples shall clinch without malformation of the stapler or staple.

4.3.5 *Shock test.* — Sample staplers with plastic or hard rubber handles shall be tested by dropping the machine onto a concrete floor or slab from a height of 3 feet. The machine shall be dropped twice so as to strike on top of handle on one end of machine, twice to strike on the base of opposite end of machine, and once to strike on side of machine. The machine shall not be damaged in any way by this test.

5. PREPARATION FOR DELIVERY (For definitions and levels see 6.2.)

5.1 Preservation and packaging.—Preservation and packaging shall be level A, B, or C, as specified in the invitation for bids, contract, or order (see 6.3 and 6.4).

5.1.1 *Level A.*

5.1.1.1 *Preservation.*—All uncoated metal surfaces of machines shall be cleaned with dry-cleaning solvent conforming to Federal Specification P–S–661. The cleaned machines shall be lubricated with lubricant as recommended by the manufacturer. The dried metal surfaces shall be coated with P-7 preservative conforming to Military Specification MIL–P–116 and wrapped with type III, grade A, greaseproof barrier-material conforming to Military Specification MIL–B–121.

5.1.1.2 *Unit packaging.* — Staplers, preserved as specified in 5.1.1.1, shall be individually packaged in folding paperboard boxes, set-up paperboard boxes, or metal-stayed boxes conforming to Federal Specifications PPP–B–566 and PPP–B–676, and Military Specification MIL–B–4229, respectively. The type, style, and class shall be optional. Staples and staple wire shall be packaged in standard commercial chipboard or fiberboard containers designed to fit the contents in a compact manner.

5.1.1.3 *Intermediate packaging.* — When specified, unit packages of one type only shall be intermediately packaged in fiberboard boxes conforming to Federal Specification LLL–B–631, LLL–B–636, or Military Specification JAN–P–108, W6s or W6c, in quantities not to exceed 20 pounds. The boxes shall be closed and sealed in conformance with the applicable box specification. In addition, fiberboard boxes shall have all joints and seams covered with gummed tape or pressure-sensitive paper tape conforming to Federal Specifications UU–T–116 and PPP–T–76, respectively.

5.1.2 *Level B.* — Staplers and staples or staple wire shall be packaged as specified in 5.1.1.1 and 5.1.1.2, except that no preservation will be required. Intermediate packaging, when specified, shall be in accordance with 5.1.1.3.

5.1.3 *Level C.* — Staplers and staples or staple wire shall be packaged in accordance with commercial practice.

5.2 Packing.—Packing shall be level A, B, or C, as specified in the invitation for bids, contract, or order (see 6.3).

5.2.1 *Level A.* — Stapling machines and staples or stapling wire, packaged as specified in 5.1, shall be packed in wood-cleated fiberboard, nailed wood, wood-cleated plywood or fiberboard boxes conforming to Military Specifications JAN–P–103, JAN–P–106, Federal Specification PPP–B–601 (overseas type), and Military Specification JAN–P–108, V3c or V3s, respectively. Only one type, style, and size container shall be used on any one contract or order. Wood and wood-cleated boxes shall be fitted with a waterproof case liner conforming to Military Specification MIL–L–10547 with seams and closures sealed in accordance with the appendix thereto. The gross weight of wood and wood-cleated

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

containers shall not exceed 100 pounds; of fiberboard boxes, 70 pounds. Boxes shall be closed and strapped in accordance with the appendix to the applicable box specification.

5.2.2 *Level B.*—Stapling machines and staples or stapling wire, packaged as described in 5.1, shall be packed in wood-cleated fiberboard, nailed wood, wood wirebound, wood-cleated veneer paper overlaid, wood cleated-plywood, corrugated or solid fiberboard boxes conforming to Federal Specifications NN–B–591, NN–B–621, PPP–B–585, class 2, Military Specification MIL–B–10377 (domestic type), and Federal Specifications PPP–B–601 (domestic type), LLL–B–631, and LLL–B–636, respectively. Fiberboard boxes shall conform to the special requirements of the applicable box specification. Only one type, style, and size container shall be used on any one contract or order. The gross weight of wood and wood-cleated boxes shall not exceed 100 pounds. Boxes shall be closed in accordance with the appendix to the applicable box specification.

5.2.3 *Level C.* — Stapling machines and staples or stapling wire, packaged as specified in 5.1, shall be packed in containers of the type, size, and kind commonly used for the purpose, in a manner that will insure acceptance by common carrier and safe delivery at destination. Shipping containers shall comply with the Consolidated Freight Classification Rules or regulations of other carriers as applicable to the mode of transportation.

5.3 Marking.

5.3.1 *Nonmilitary agencies.*

5.3.1.1 *Packages.*—Unless otherwise specified, packages of staplers shall be marked with the name, type, class, and style of the commodity, the quantity contained therein, and the names of the contractor and the manufacturer, if different, and such other marking as is standard commercial practice. Packages of staples shall be marked in accordance with standard commercial practice.

5.3.1.2 *Shipping containers.*—Unless otherwise specified, shipping containers shall be marked with the name, type, class, and style of staplers as defined by the contract or order under which shipment is made, the quantity contained therein, the name of the contractor, the number of the contract or order, the name and address of the consignee, the gross weight, and such other marking as is standard commercial practice for staplers and staples.

5.3.2 *Military agencies.* — In addition to any special marking required by the contract or order, marking shall be in accordance with Military Standard MIL–STD–129.

6. NOTES

6.1 Intended use.—The various types of staplers covered by this specification are intended for paper fastening and stapling or tacking to other materials.

6.1.1 *Type I, class A stapler* is the "standard" type of machine used on desks in offices and other places to staple or fasten papers together and for tacking or pinning papers or other materials to wood, cork, paper, etc.

6.1.2 *Type I, class B stapler* is a wire-spool stapler intended for desk use in offices where a large load of staples, in the form of a spool of wire, is supplied to last a long time without reloading.

6.1.3 *Type II, plier-type stapler* is intended for light work for use in fastening boxes, books, papers, etc.

6.2 Federal Standard 102, for Preservation, Packaging, and Packing Levels, should be referred to for definitions and applications of the various levels of packaging protection for supplies and equipment.

6.3 Ordering data.—Purchasers should specify the type, class, and style of commod-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.

ity required, reach or range required for type I, class A, style 1 staplers (if 8-, 12-, or 16-inch-reach, standard-duty, non-tacker machines are required), whether an adjustable depth gage is required, size of staple (preformed), and kinds of clinch. Purchasers should also specify levels of packaging and packing required, and when intermediate packaging is desired, so state, and should exercise any desired options offered herein. (See 1.1.1, 1.1.2, 1.2.1, 3.3.1.1, 3.3.1.2, 3.3.2, 3.6, 3.6.1.1, 3.6.1.2, 4.1.1, 5.1, 5.1.1, 5.1.2, 5.1.3, 5.2, 5.2.1, 5.2.2, 5.2.3, 5.3.1.1, 5.3.1.2, and 6.4.)

6.4 Level B.—This level of packaging and packing may be used for shipment of the commodity for normal overseas supply where favorable storage conditions exist; for immediate use overseas where the destination is known; or for domestic storage when it is known that the commodity will be ultimately used at a domestic activity.

6.5 Transportation description.—Transportation description applicable to this item is:

Staplers:

Machines, not otherwise indexed by name.
(Specify set-up or knocked-down).
Carload minimum weight 24,000 pounds, subject to Rule 34, Uniform Freight Classification.
Truckload minimum weight 24,000 pounds.

Staples:

Staples, stapling machine.
Carload minimum weight 30,000 pounds.
Truckload minimum weight 36,000 pounds.

Patent notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

MILITARY INTERESTS:
Army—E Q
Navy—S MC
Air Force.

Copies of this specification may be purchased for 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.