GG-S-745A
INTERIM AMENDMENT-4 (GSA-FSS)
August 29, 1973
SUPERSEDING
Interim Amendment-3
January 26, 1970

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

STAPLERS AND STAPLES,
PAPER FASTENING, OFFICE TYPE

This interim amendment was developed by the General Services Administration, Federal Supply Service, Standardization Division, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification GG-S-745A, dated July 25, 1956.

PAGE 3

Paragraph 3.2.2: Delete the first sentence and substitute: "Staple drivers shall be made of spring steel containing not less than 0.6 percent carbon, and hardened equally over the whole length to an equivalent of a Rockwelo hardness of not less than 48, C scale (see 4.3.1)."

Paragraph 3.2.3:

Delete the first sentence.

After the third sentence, insert the following: "The hardness of the anvil for type I, class B wire-spool stapler shall be not less than 68(15-N-68) Rockwell superficial."

PAGE 4

Paragraph 3.3.1.1: Delete and substitute:

3.3.1.1 Clinching anvil.

FSC 7520/7510

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:52Z
Check the source to verify that this is the currentversion before use.

3.3.1.1.1 Style 1. The clinching anvil for the style 1 stapler (see 3.3.1.4) shall be a separate unit attached to the base, and shall not be an integral part of the base. Unless otherwise specified, provisions shall be made in the constructuon of the style 1 stapler to provide a clinching anvil to produce the "standard" clinch, and either the "temporary" or the "pin" clinch (see figure 1). The clinching anvil for 8-inch, 12-inch, or 16-inch reach staplers (see 3.3.1.2) shall be a separate unit permanently riveted to the base. The clinching anvil shall produce the "standard" clinch.

3.3.1.1.2 Style 2. The clinching anvil for the style 2 stapler (see 3.3.1.5) shall be a separate unit permanently riveted to the base. The clinching anvil shall produce the "standard" clinch (see figure 1).

PAGE 5

Paragraph 3.3.2.1: Delete and substitute:

3.3.2.1 Clinching anvil. The clinching anvil for the type I, class B, stapler shall be substantially the same as that specified for the type I, class A, style 1 stapler, and as described in 3.3.1.1.1.

Paragraph 3.4: At the end of the sentence, add the following: "The over-all length shall be not more than 5-1/2 inches."

Paragraph 3.4.5: Delete and substitute:

3.4.5 Clinching anvil. The clinching anvil shall be either a separate unit permanently riveted to the base, or it shall be an integral unit pressed into the base. The clinching anvil shall produce the "standard" clinch or both the "standard" and the "pin" clinches (see figure 1).

Add new sub-paragraph:

"3.5.3 Colors. The painted surfaces of all Type I, Class A, style 1, staplers shall be the color specified (see 6.3)."

PAGE 7

Paragraph 4.3.1: Following the first sentence, insert "In determining the hardness of the staple driver (see 3.2.2), another scale on the Rockwell hardness tester or a Rockwell superficial tester may be used if required, with conversion of the result obtained to a Rockwell C scale result. Both results shall be reported".

PAGE 10

Paragraph 6.3 (cont'd), line 11: Delete "3.3.1.1" and substitute "3.3.1.1.1".

Paragraph 6.3 (cont'd), add the following sentence at end of paragraph:

"Request color required for type I, Class A, style 1 staplers." (See 3.5.3.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:52Z
Check the source to verify that this is the current version before use.