GG-S-773D
June 9, 1978
SUPERSEDING
Fed. Spec. GG-S-773C
January 5, 1966

FEDERAL SPECIFICATION

STRAIGHTEDGES: PLASTIC AND WOOD

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers plastic and wood straightedges.

1.2 Classification.

1.2.1 Types and classes. The straightedges shall be furnished in the following types and classes, as specified (see 6.2):

Type I--Solid wood blade with transparent plastic edges.
Type II--Plastic.
Class A--Opaque blade.
Class B--Opaque blade with transparent plastic edges.
Class C--Transparent blade.

1.2.2 Sizes. The straightedges shall be 18, 24, 30, 36, 42, 48, 60, and 72 inches in length, as specified (see 6.2).

FSC 6675

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

L-P-535 - Plastic Sheet (Sheeting); Plastic Strip; Vinyl Chloride-Vinyl Polymer and Vinyl Chloride-Vinyl Acetate Copolymer, Rigid.
QQ-S-781 - Strapping, Steel, and Seals.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-636 - Boxes, Shipping, Fiberboard.

Federal Standards:

FED. STD. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

Military Specifications:

MIL-P-116 - Preservation-Packaging, Methods of.
MIL-P-8184 - Plastic Sheet, Acrylic, Modified.
MIL-P-18177 - Plastic Sheet, Laminated, Thermosetting, Glass Fiber Base, Epoxy-Resin.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Description. The straightedges shall be straight strips of plastic, or plastic and wood combination as specified herein. A hole 0.5 inch in diameter shall be centered near one end to permit hanging of the straightedge.

3.2 Material. Material shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.5).

3.2.1 Wood. The wood shall be hard maple, cherry, mahogany, walnut, or yellow birch, and free from defects. Slope of grain shall be not more than 1 inch in 15 inches.

3.2.2 Plastic, transparent. Transparent plastic shall conform to MIL-P-8184, Finish A, or L-P-535, Composition A, Type I, Class 1. Light transmission for transparent plastics shall be not less than 78 percent.

3.2.3 Plastic, opaque. Opaque plastic shall conform to MIL-P-18177, Type GEE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

3.3 Shape. The shape of the working edge shall be square with one side beveled or two sides beveled as specified (see 6.2). The working edges shall be straight to within 0.003 inch per foot of length. The straightedges shall be free from bow or twist.

3.4 Finish. Unless otherwise specified (see 6.2), the surface finish for plastic straightedges shall be polished or semigloss. Semigloss shall be as produced by the molding or laminating process. Wood surfaces shall have a dull finish protective coating.

3.5 Size. The straightedges shall conform to the length, width, and thickness listed in Table I. A tolerance of not more than ± 0.125 inch will be permitted in length.

TABLE I. Dimensions.

Length	Width	Thickness of blade
Inches	Inches	Inches
18	2.0 to 2.25	.094 to .125
24	2.25 to 2.50	.094 to .125
30	2.25 to 2.75	.094 to .156
36	2.25 to 2.75	.094 to .156
42	2.50 to 3.0	.125 to .156
48	2.50 to 3.0	.125 to .156
60	2.75 to 3.25	.156 to .188
72	3.0 to 3.25	.156 to .188

3.6 Identification marking. When specified (see 6.2), the name of the manufacturer, trademark, or both, and the words "Property of U.S. Gov't." shall be permanently marked on each straightedge.

3.7 Type I, wood. The Type I straightedges shall be one continuous piece of hardwood, and shall have transparent plastic working edges. The edges shall be of equal and uniform width not less than 0.25 inch and not more than 0.50 inch on lengths of 18, 24, and 30 inches, and not less than 0.375 inch and not more than 0.50 inch on all other lengths. The transparent edges shall be permanently secured to the wood by means of tongue-and-groove or corrugated joints. Ends of the hardwood blade shall be reinforced with strips or "bridges" of the same material as the working edges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

3.8 Type II, plastic.

3.8.1 Class A, opaque blade. The Class A straightedge shall be opaque plastic.

3.8.2 Class B, opaque blade with transparent edges. The Class B straightedge shall be opaque plastic and shall have working edges of transparent plastic. The working edges shall be of equal and uniform width not less than 0.25 inch and not more than 0.50 inch on lengths of 18, 24, and 30 inches, and not less than 0.375 and not more than 0.50 inches on all other lengths. The transparent edges shall be permanently secured to the opaque plastic blades by means of tongue-and-groove or corrugated joints.

3.8.3 Class C, transparent blade. The Class C straightedge shall be made of transparent plastic.

3.9 Workmanship. The straightedges shall be free from warpage, cracks, scratches, bubbles, imbedded particles, and other defects that affect their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of packaging (see 4.5).

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:53Z
Check the source to verify that this is the currentversion before use.

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined as specified in 4.4.1. AQL shall be 2.5 percent defective.

4.3.3 Tests. Samples selected in accordance with 4.3.1, shall be examined as specified in 4.4.2. AQL shall be 2.5 percent defective.

4.4 Inspection procedure.

4.4.1 Examination. The straightedges shall be examined as specified herein for the following major defects:

101. Classification not as specified.
102. Materials not as specified.
103. Slope of grain not as specified.
104. Edges not as specified.
105. Dimensions not as specified.
106. Finish not as specified.
107. Identification marking not as specified.
108. Workmanship not as specified.

4.4.2 Test. Place the ruling edge of the straightedge against a precision straightedge, surface plate, bench block, or other precision flat. Measure the points of noncontact between the precision flat and the ruling edge. Nonconformance to 3.3 shall constitute failure of this test.

4.5 Inspection of packaging.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.5.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

4.5.1.3 Examination. Samples selected in accordance with 4.5.1.2 shall be examined for the following major defects. AQL shall be 2.5 percent defective.

109.	Materials, methods, and containers not as specified for Level A or Level B. Each incorrect material, method, or container shall be considered one defect.
110.	Straightedges of unlike description, consolidated together or packed together for Level A or Level B.
111.	Quantities consolidated together or packed together exceed the weight limitations of the box for Level A or Level B.
112.	Strapping not as specified for Level A.
113.	Marking missing, illegible, incorrect, or incomplete for Level A, Level B, or Commercial.

5. PREPARATION FOR DELIVERY

5.1 Preservation. Preservation shall be Level A, Level B, or Commercial as specified (see 6.2).

5.1.1 Level A. Each straightedge shall be preserved in accordance with MIL-P-116, Method IC-1, except straightedges furnished in a manufacturers carton shall be preserved Method IC-2, using the carton as the container.

5.1.1.1 Consolidation. Straightedges of like description shall be consolidated together in a close-fitting box conforming to PPP-B-636, W5c or W6c, style optional, in quantities not to exceed the weight limitation of the box as specified in the box specification. The box shall be closed and sealed as specified for Method V in the appendix to the box specification.

5.1.2 Level B.

5.1.2.1 Military. Preservation shall be as specified in 5.1.1 and 5.1.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

5.1.2.2 Civil agencies. The straightedges shall be individually preserved in accordance with MIL-P-116, Method III. Straightedges of like description shall then be placed in a close-fitting box conforming to PPP-B-636, Class Domestic, style optional. The quantities shall not exceed the weight limitations of the box specification. Closure of the box shall be in accordance with the appendix to PPP-B-636.

5.1.3 Commercial. Each straightedge shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be Level A, Level B, or Commercial, as specified (see 6.2).

5.2.1 Level A. Straightedges of like description, preserved as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-601, Overseas Type, Grade B, style optional, in quantities not to exceed the weight limitation of the box specification. Box closure and strapping shall be in accordance with the appendix to the box specification. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be Finish B. When specified (see 6.2), strapping shall be Finish A.

5.2.2 Level B.

5.2.2.1 Military agencies. Straightedges of like description, preserved as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-636, V3c or V3s, style optional, in quantities not to exceed the weight limitation of the box.

5.2.2.2 Civil agencies. Packing shall be as specified in 5.2.2.1 except boxes shall be Class Domestic.

5.2.3 Commercial. Straightedges, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Marking.

5.3.1 Military agencies. Marking for military levels of protection shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.

5.3.2 Civil agencies. Marking shall be in accordance with FED. STD. No. 123.

5.3.3 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The straightedges are intended for general drafting use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in the procurement documents:

(a) Title, number, and date of this specification.
(b) Type, class, and size required (see 1.2).
(c) Type of edges required (see 3.3).
(d) Finish required if other than specified (see 3.4).
(e) When identification marking is required (see 3.6).
(f) Degree of preservation and degree of packing required (see 5.1 and 5.2).
(g) When Finish A strapping is required (see 5.2.1).

6.3 Federal Govenment requirements. Federal Specifications do not include all types, classes, and sizes of the commodities indicated by the titles of the specifications or which are commercially available, but are intended to cover the types, classes, and sizes which are suitable for Federal Government requirements.

6.4 Qualification. For military procurements, the straightedges covered by this specification include qualified components or materials, and the contracting officer should include the requirements of ASPR 1-1107.2(b) in the solicitation.

6.5 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:53Z
Check the source to verify that this is the current version before use.

GG-S-773D

Custodians:
Army - ME
Air Force - 99

Review activity:
DLA - GS

Preparing activity:
Army - ME

Civil Agency Coordinating Activities:
GSA - FSS
VA - DMS

Project 6675-0467

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 70 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:53Z
Check the source to verify that this is the current version before use.