INCH−POUND

MIL−D−51091J(EA)
AMENDMENT 4
22 April 1994

SUPERSEDING
AMENDMENT 3
28 February 1990

MILITARY SPECIFICATION

DECONTAMINATING APPARATUS, POWER DRIVEN, SKID−MOUNTED, MULTIPURPOSE, NONINTEGRAL, 500−GALLON, M12A1

This amendment forms a part of MIL−D−51091J(EA), dated 16 December 1986, and is approved for use by the U.S. Army Edgewood Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1: Under "SPECIFICATIONS, MILITARY": Delete "MIL−H−51171 − Heater, Water, Liquid Fuel, Skid−Mounted, 600 GPH, M2."

2.1.2: Under the list of drawings add the following:

"SPECIAL PACKAGING INSTRUCTIONS (SPI)

P5−59−200 − Heater, Water, Liquid Fuel, Skid−Mounted 600 GPH, M2."

PAGE 3

3.3.2: Delete in its entirety and substitute the following:

AMSC N/A FSC 4230

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:49Z
Check the source to verify that this is the current version before use.

"**3.3.2 Fuel tank.** The unpainted tank shall not leak, except at the fuel quantity transmitter screw holes, when subjected to an internal air pressure of 2 to 3 pounds per square inch gage (psig) when tested as specified in 4.4.4.1."

PAGE 8

5.1.1.2:

Lines 3, 4 and 5: Delete the following sentence: "The interior surfaces of the tanks and fittings including the gasoline tank, shall be completely coated with preservative oil conforming to grade 2, MIL−L−21260."

PAGE 9

5.1.1.4: Delete in its entirety and substitute the following:

"**5.1.1.4 Water heater unit.** The water heater shall be preserved and packaged in accordance with the level A requirements of SPI P5−59−200."

5.1.1.7, lines 6, 7, 8 and 9: Delete "The blending−agitator hose shall then be stowed within the suction hose. Both hoses, together, shall then be installed, coiled, within the holding brackets on top of the tank unit." and substitute "The blending−agitator hose shall then be coiled and stowed within the hopper assembly. The suction hose shall then be installed, coiled, within the holding brackets on top of the tank unit."

PAGE 10

5.2.1.3: Delete in its entirety and substitute the following:

"**5.2.1.3 Water heater unit.** The water heater, preserved as specified in 5.1.1.4, shall be packed in a wood crate in accordance with the level A requirements of SPI P5−59−200."

Custodian:

Army − EA

Preparing activity:

Army − EA

Project No. 4230−A101

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:49Z
Check the source to verify that this is the current version before use.