INCH-POUND


MIL-F-28861/13A
2 November 1988
SUPERSEDING
MIL-F-28861/13
29 August 1986

MILITARY SPECIFICATION SHEET


FILTERS AND CAPACITORS, RADIO FREQUENCY/ELECTROMAGNETIC INTERFERENCE SUPPRESSION, HERMETICALLY SEALED ON ONE END ONLY, STYLE FS72

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-F-28861.



CONFIGURATION A




CONFIGURATION B

FIGURE 1. Case and hardware dimensions and circuit diagrams.

(A) denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:10Z
Check the source to verify that this is the current version before use.



CIRCUIT DIAGRAMS

Circuit diagram	A ±.005	B Ref
L	.300	.800
C	.200	.700

Inches	mm
.002	0.05
.005	0.13
.025	0.64
.03	0.8
.050	1.27
.200	5.08
.25	6.4
.300	7.62
.400	10.16
.450	11.43
.700	17.78
.800	20.32

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.005 (0.13 mm).
4. Circuit diagrams are for information only.
5. Filters shall be supplied with 60/40 solder preform.
6. Potting on nonhermetically sealed end shall not extend beyond .030 inch (0.76 mm) from the filter body.
7. Filters shall be installed using the recommended installation methods (solder-in style) of MIL-F-28861.

FIGURE 1. Case and hardware dimensions and circuit diagrams - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:10Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1. Filters and capacitors shall be hermetically sealed on one end as shown on figure 1 for the respective style.

Weight: .25 gram maximum for C circuit parts.
.75 gram maximum for L circuit parts.

Case and lead finish: G only (gold plated).

Terminals: Solderable.

Operating temperature range: -55°C to +125°C.

Rated voltage: See table I.

Rated current: 15 amperes maximum.

Capacitance to ground: See table I for capacitance value.

Dissipation factor: 3.0 percent maximum.

Voltage and temperature limits of capacitance: +15 percent, -40 percent.

Insulation resistance:

At +25°C: 1,000 megohm-microfarads or 100,000 megohms minimum, whichever is less.

At +125°C: 100 megohm-microfarads or 10,000 megohms minimum, whichever is less.

Insertion loss:

At +25°C: In accordance with table I.

At -55°C and +125°C: A 3 dB degradation from the +25°C value shall be allowed.

Voltage drop: .15 volt dc maximum, .234 volt ac maximum for dash numbers 007, 008, 015, and 016.

DC resistance: 0.01 ohm maximum.

Seal: Not applicable.

Temperature rise: +35°C maximum.

Solderability of terminals: In accordance with MIL-F-28861, except temperature of solder shall be 300°C ±5°C.

(A) Resistance to soldering heat: In accordance with MIL-F-28861, except temperature of solder shall be 300°C ±5°C.

Solderability of mounting termination: In accordance with MIL-F-28861, except temperature of solder shall be 300°C ±5°C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:10Z
Check the source to verify that this is the current version before use.

Ⓐ Quality assurance provisions:

Class B and class S filters: In accordance with MIL-F-28861.

Class A filters:

Qualification inspection: Initial qualification may be granted based on qualification to class B. Baseline documentation in accordance with MIL-F-28861 is required and shall be submitted to the qualifying activity prior to completion of quality conformance inspection on the initial lot. Retention of qualification shall be in accordance with class S requirements.

In-process inspection: In accordance with class S requirements, except that the requirements of MIL-C-123 shall not apply.

Quality conformance inspection: The inspection lot definition and inspection of product for delivery shall be in accordance with the class S requirements.

Ⓐ TABLE I. Electrical characteristics.

Dash number		Circuit	Product assurance level			Rated voltage volts dc		Capacitance (µF) -0, +100 percent	Minimum insertion loss (dB) in accordance with MIL-STD-220 1/ 2/					
Configuration			Class											
A	B		A	B	S	DC	AC rms		500 kHz	1 MHz	10 MHz	100 MHz	1 GHz	10 GHz
001	009	L	---	X	---	50	---	1.2	33	38	53	70	70	70
002	010	C	---	X	---	50	---	1.2	33	37	52	70	70	70
003	011	L	X	X	X	70	---	0.70	30	38	42	62	70	70
004	012	C	X	X	X	70	---	0.70	30	36	41	60	70	70
005	013	L	X	X	X	100	---	0.50	26	34	44	60	70	70
006	014	C	X	X	X	100	---	0.50	26	34	42	58	70	70
007	015	L	X	X	X	300	115	0.05	7	15	34	44	70	70
008	016	C	X	X	X	300	115	0.05	7	15	34	42	70	70

Ⓐ 1/ For C circuits, insertion loss measurements shall be made under no load. For L circuits, insertion loss measurements shall be made under full load over the frequency range of 1 MHz to 10 MHz. Insertion loss measurements above and below this frequency range shall be made under no load.

2/ The insertion loss requirements between any two adjacent specified frequencies shall be that of the lower of the two frequencies in order to accommodate resonant dips.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:10Z
Check the source to verify that this is the current version before use.

Ⓐ Product assurance level: In accordance with table I.

Ⓐ Part or identifying number: The part or identifying number shall be as follows:

M28861/13 - XXX G X

- XXX: Dash no. per figure 1 and table I
- G: Case finish
- X: Product assurance level per MIL-F-28861 and table I

Ⓐ Marking: Classes B and A capacitors and filters shall not be marked. Class S filters and capacitors shall be marked with a green dot in accordance with color number 14187 of FED-STD-595. Full marking, in accordance with MIL-F-28861, shall be marked on the unit package.

Cataloging information: Dash numbers 002, 004, 006, 008, 010, 012, 014, and 016 shall be cataloged under FSC 5910 as feed-through ceramic capacitors. Dash numbers 001, 003, 005, 007, 009, 011, 013, and 015 shall be cataloged under FSC 5915 as radio frequency interference filters.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, MI
Air Force - 11, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - AS, CG, MC, OS, SH
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 59GP-0074-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:10Z
Check the source to verify that this is the current version before use.