MILITARY SPECIFICATION SHEET

FILTERS AND CAPACITORS, RADIO FREQUENCY/ELECTROMAGNETIC INTERFERENCE SUPPRESSION, HERMETICALLY SEALED ON ONE END ONLY, STYLE FS72

This amendment forms a part of MIL-F-28861/13A, dated 2 November 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Solderability of terminals: Delete "300°C ±5°C" and substitute "300°C +0°C, -5°C".

Resistance to soldering heat: Delete "300°C ±5°C" and substitute "300°C +0°C, -5°C".

Solderability of mounting termination: Delete "300°C ±5°C" and substitute "300°C +0°C, -5°C".

PAGE 5

After marking paragraph add the following:

"Soldering temperature. Caution: These devices shall not be exposed to soldering temperatures exceeding 300°C. Exposure time to soldering temperature of 300°C shall not exceed 1 minute.

"Installation note: These devices are intended to be installed into hermetically sealed packages with the glass seal oriented toward the outside world."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, MI
Air Force - 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - AS, CG, MC, OS, SH
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 59GP-0089)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:10Z
Check the source to verify that this is the current version before use.