MILITARY SPECIFICATION SHEET

FILTERS, RADIO FREQUENCY/ELECTROMAGNETIC INTERFERENCE SUPPRESSION, HERMETICALLY SEALED, STYLE FS50

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the filters described herein shall consist of this specification and the latest issue of MIL-F-28861.





FIGURE 1. Case and hardware dimensions and circuit diagrams.

*U.S. GOVERNMENT PRINTING OFFICE: 1982—505-022/804

FSC 5915

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:07Z
Check the source to verify that this is the current version before use.



CIRCUIT DIAGRAMS

Dash no.	A dimension (±010)
001 thru 012	.187
0013 thru 024	.312

INCHES	MM	INCHES	MM
.003	.08	.115	2.92
.005	.13	.145	3.68
.007	.18	.187	4.75
.010	.25	.200	5.08
.015	.38	.250	6.35
.022	.56	.312	7.92
.035	.89	.395	10.03
.045	1.14	.400	10.16
.050	1.27	.408	10.36
.070	1.78	.410	10.41
.093	2.36	.793	20.14

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Circuit diagram is for information only.
4. All filters shall be supplied with mounting hardware (hex nut and lockwasher). Mounting hardware shall be furnished with the same finish as the filter case.
5. Terminal identification (non-symmetrical filters): The case shall be marked at the threaded end of the filter, with the symbol "C" or the symbol "L", as follows, or the circuit diagram shall be marked on the case.

Circuit	Symbol
L_1	C
L_2	L

6. Optional slot may be supplied, .050 ±.010 inches x .070 ±.010 inches.
7. Imperfect thread or undercut optional .050 inches maximum.
8. One imperfect thread allowed .035 inches maximum.
9. Recommended mounting torque: 44 oz-in ±4 oz-in.

FIGURE 1. Case and hardware dimensions and circuit diagrams - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:07Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1.

Weight: 10 grams, maximum.

Case finish:

Class B filters, T only (tin-plated or tin-lead plated).

Class S filters, T or G only (tin-plated or tin-lead plated, or gold plated).

Terminals: Solderable.

Operating temperature range: -55° to +125°C.

Rated voltage: 200 Vdc/125 Vac 0 to 400 Hz.

Rated current: See table I.

Capacitance: See table I for capacitance value.

Voltage and temperature limits of capacitance: +15, -40 percent.

Insulation resistance:

At +25°C: 1,000 megohms, minimum.

At +125°C: 100 megohms, minimum.

Insertion loss: See table I.

Voltage drop: See table I.

DC resistance: See table I.

Seal: In accordance with MIL-F-28861. Leakage rate for class S filters shall not exceed 1×10^{-7} atm cc/sec.

Temperature rise: 25°C, maximum.

Solderability of terminals: In accordance with MIL-F-28861.

Product assurance level: In accordance with table I.

Part number: The part number shall be as follows:

M28861/05 - XXX X . X

Dash no. per figure 1 and table I	Case finish	Product assurance level per MIL-F-28861 and table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:07Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics.

Dash number	Product assurance level Class S	Product assurance level Class B	Circuit	Maximum current (amps)	Capacitance (µF) +100% -0	Maximum voltage drop (volts)	Maximum DC resistance (ohms)	Minimum insertion loss (dB) in accordance with MIL-STD-220 1/2/ At +25°C: 100 kHz	150 kHz	300 kHz	1 MHz	10 MHz	100 MHz	1 GHz	At -55° and +125°C: 100 kHz	150 kHz	300 kHz	1 MHz	10 MHz	100 MHz	1 GHz
001, 013	X	X	L1	0.25	0.15	0.375	1.5	22	28	40	60	60	60	70	20	26	38	58	60	60	70
002, 014	X	X	L2	0.25	0.15	0.375	1.5	22	28	40	60	60	60	70	20	26	38	58	60	60	70
003, 015	X	X	π	0.25	0.30	0.375	1.5	34	44	62	80	80	80	80	32	42	60	78	80	80	80
004, 016	X	X	L1	1.0	0.15	0.250	0.25	8	13	24	45	60	60	70	6	11	22	43	60	60	70
005, 017	X	X	L2	1.0	0.15	0.250	0.25	8	13	24	45	60	60	70	6	11	22	43	60	60	70
006, 018	X	X	π	1.0	0.30	0.250	0.25	18	32	50	80	80	80	80	16	30	48	78	80	80	80
007, 019	X	X	L1	3.0	0.15	0.150	0.05	5	8	16	30	60	60	70	3	6	14	28	58	60	70
008, 020	X	X	L2	3.0	0.15	0.150	0.05	5	8	16	30	60	60	70	3	6	14	28	58	60	70
009, 021	X	X	π	3.0	0.30	0.150	0.05	-	-	19	59	80	80	80	-	-	17	57	80	80	80
010, 022	X	X	L1	5.0	0.15	0.075	0.015	5	8	14	26	55	55	70	3	6	12	24	53	55	70
011, 023	X	X	L2	5.0	0.15	0.075	0.015	5	8	14	26	55	55	70	3	6	12	24	53	55	70
012, 024	X	X	π	5.0	0.30	0.075	0.015	-	-	-	51	80	80	80	-	-	-	49	80	80	80

1/ Insertion loss measurements shall be made under full-load over the frequency range of 100 kHz to 10 MHz. Insertion loss measurements above this frequency range shall be under no-load.

2/ The insertion loss requirements between any two adjacent specified frequencies shall be that of the lower of the two frequencies in order to accommodate resonant dips.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:07Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 11
NASA - NA

Review activities:
Army - AR, MI
Air Force - 17, 85, 99
DLA - ES

User activities:
Army - ME, AT, AV
Navy - CG, MC, AS, OS, SH
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5915-0219-5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-F-28861/5

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:07Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commander
Naval Electronic Systems Command
Defense Standardization Program Branch
Department Of The Navy
Washington, D.C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:07Z
Check the source to verify that this is the current version before use.