MILITARY SPECIFICATION SHEET

# FILTERS AND CAPACITORS, RADIO FREQUENCY/ELECTROMAGNETIC INTERFERENCE SUPPRESSION, NONHERMETICALLY SEALED, STYLE FS60

This amendment forms a part of MIL-F-28861/6A, dated 29 August 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Case finish; delete in its entirety and substitute:

"Case finish: Class B filters, S only (silver-plated).
Class S filters, S or G only (silver-plated or gold plated).
In accordance with MIL-F-28861."

PAGE 4

TABLE I, delete footnote 1/ in its entirety and substitute:

" 1/ For C circuits, insertion loss measurements shall be made under no load. For L2 circuits, insertion loss measurements shall be made under full load over the frequency range of 1 MHz to 10 MHz; above this frequency range, insertion loss measurements shall be made under no load."

Custodians
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, MI
Air Force - 11, 99
DLA - ES

User Activities:
Army - AT, AV, ME
Navy - AS, CG, MC, OS, SH
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 59GP-0066-01)


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:08Z
Check the source to verify that this is the current version before use.