W-L-00215B
January 7, 1977
SUPERSEDING
Int. Fed. Spec. W-L-00215A (GSA-FSS)
March 15, 1970 and
Interim Revision of
Fed. Spec. W-L-215
January 24, 1957

INTERIM FEDERAL SPECIFICATION

LANTERN, ELECTRIC, HEAD

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification as a valid exception to Federal Specification W-L-215, dated January 24, 1957.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers lanterns with an adjustable focus reflector-type light equipped with a switch and mounted on an elastic band to be worn on the user's head or hat. The lantern is connected by a flexible cord to a battery case that is fitted to be carried on the belt. The battery case shall accommodate four standard "D" type dry cell batteries connected in series.

1.2 Classification.

1.2.1 Type and classes. The portable electric lanterns covered by this specification shall be of one type and two classes:

Class 1 - With 0.15-ampere lamps (see 6.1.1).
Class 2 - With 0.30-ampere lamps (see 6.1.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

W-B-101	-	Battery, Dry.
MMM-A-250	-	Adhesive, Water Resistant.
PPP-B-566	-	Boxes, Folding, Paperboard.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-665	-	Boxes, Fiberboard, Metal Stayed.
PPP-B-676	-	Boxes, Setup, Paperboard.

Federal Standards:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Underwriters' Laboratories, Inc., (UL) Standard:

UL 817 - Cord Sets and Power Supply Cords.

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 General. Head lanterns specified herein shall be designed for use in an adverse weather, outdoor environment, producing useable illumination when tested as specified in 4.5.2.

3.2 Materials. The materials used in the lanterns shall be as specified. Materials not definitely specified, shall be of the quality best suited for the purpose intended. Metal parts shall be suitably protected against corrosion. Dissimilar metals shall not be used in intimate contact with each other unless protected against electrolytic action.

3.3 Construction. The complete lantern shall be as rugged and as simple in construction as possible. The assembly shall consist of a battery case, lamp-reflecting unit, and connecting cable. The assembly shall be furnished with lamps. The construction shall be such that the lantern may be safely worn as a head lantern.

3.4 Component parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

3.4.1 Battery case. The battery case shall be corrosion resistant and shall be constructed of high impact resistant material. There shall be no permanent deformation, breakage, malfunction or loosening of parts when tested as specified in 4.5.3, 4.5.4, and 4.5.5. The case shall be designed to accommodate four standard "D" type dry cell batteries that are in accordance with Federal Specification W-B-101, connected in series with required contact strips and terminals. Additionally, the case shall be no larger than 6 inches x 3 inches x 2 inches and shall be designed to preclude water collection, having drainage holes or other means to prevent water containment.

3.4.1.1 Lid. The battery case shall have a lid designed to permit easy access to batteries within the case. The lid shall be of a hinge design with a latch or equivalent device for securely holding lid in a closed position. There shall be no indication of lid, hinge, or latch damage when tested as specified in 4.5.6.

3.4.1.2 Belt clip. A belt clip of oil tempered spring steel not less than 0.020-inch thick or tempered spring plastic not less than 0.125-inch thick shall be securely attached to the back face of the battery case to permit wearing of the case on belts up to 2 inches in width.

3.4.1.3 Instruction data. Plainly visible instructions for placing the batteries in the proper position in the case shall be inscribed on battery case by embossing or other permanent means.

3.4.1.4 Batteries. Unless otherwise specified (see 6.2 and 6.3), the four standard "D" type dry cell batteries are not to be furnished with the lantern.

3.4.2 Lamp-reflector unit assembly. The lamp-reflector unit assembly shall consist of the following parts: reflector, lens, lampholder, spare lampholder, casing, retaining rings, lamp, spare lamp, and switch.

3.4.2.1 Reflector. The reflector shall be conical or parabolic in shape. The reflector surface shall be of a material that resists corrosion and retains a specular reflecting surface.

3.4.2.2 Lens. The lens shall be of a clear material not less than 0.093- inch thick and free from bubbles, striae, checks, wrinkles, or other defects which would affect the light distribution.

3.4.2.3 Lampholder. A miniature lamp holder shall be securely attached within the lamp-reflector unit. The axis of rotation of the lampholder to be coincident with the optical axis of the reflector.

3.4.2.4 Spare lampholder. A clip, or other suitable device, shall be provided behind the reflector within the lamp-reflector unit to hold a spare lamp of the same electrical rating as that provided with the lantern (see 3.4.2.7).

3.4.2.5 Reflector casing. The reflector casing shall be corrosion resistant and constructed of a high impact resistant material designed to preclude permanent deformation breakage, malfunction or loosening of parts when tested as specified in 4.5.3, 4.5.4, and 4.5.5. The case shall contain the parts of the lamp-reflector unit assembly. The overall diameter of the casing with retaining ring (see 3.4.2.6 below) in place shall not exceed 2.750 inches. The casing shall be provided with an opening for the cord, support for a switch, and means of attachment to the headplate bracket. Additionally, casing shall be designed to preclude water collection, having drain holes or other means to prevent water containment.

3.4.2.6 Retaining ring. A retaining ring of the same material as the reflector casing shall be provided to retain the lens and reflector within the lamp-reflector unit. The ring shall be threaded onto the casing and shall provide an area not to be less than 1.625 inches in diameter for the lens to transmit light. The retaining ring shall be of a design that precludes unintentional movement relative to the casing during normal use. Additionally, the retaining ring and reflector casing threads and design shall be such that retaining ring, after removal from reflector casing, can be quickly and easily reassembled to the reflector casing. Also, the retaining ring shall hold the lens and reflector in such manner as to permit lens and reflector movement in relation to the lamp filament, for focus adjustment, by rotation of the retaining ring on its thread.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:25Z
Check the source to verify that this is the currentversion before use.

3.4.2.7 Lamp.

3.4.2.7.1 Class 1, lantern lamp. The class 1 lantern shall be provided with a minature screw-base lamp having an electrical rating of 5.1 volts, 0.15-ampere, trade No. 502, or equal.

3.4.2.7.2 Class 2, lantern lamp. The class 2 lantern shall be provided with a minature screw-base lamp having an electrical rating of 4.9 volts, 0.30-ampere, trade No. 27, or equal.

3.4.2.8 Spare lamp. A spare lamp having the same electrical rating as the lamp furnished in accordance with 3.4.2.7, shall be furnished in the spare lamp-holder in the lamp-reflector unit assembly.

3.4.2.9 Switch. A smoothly actuating two-position switch shall be provided with the actuating member on the outside of the lamp-reflector unit casing. The switch shall open and close the lamp circuit. The two positions of the switch shall be "ON" and "OFF" and the switch action shall be such that the actuating member shall resist accidental movement from one position to the other when the lantern is subjected to the abuses of normal use. The switch shall be capable of 8,000 cycles of operation without malfunction when tested as specified in 4.5.12. A cycle shall consist of movement from "OFF" position to full "ON" position and back to "OFF" position.

3.4.3 Headplate. A headplate of steel, brass, or high impact resistant plastic shall provide support for the lamp-reflector unit and a means of fastening the headband in place about the head or hat. The headplate material shall not be less than 0.025 inches in thickness. The plate shall be curved to fit the forehead or the front of a protective hardhat and have a slot or permanently attached clip on one end for attachment of the headband to prevent loss yet permit detachment or replacement of the band. The opposite side of the headplate shall have a post or slot for attaching the headband.

3.4.3.1 Headplate bracket. The lamp-reflector unit shall be attached to the headplate by means of a bracket of steel, brass, or high impact resistant plastic. The bracket shall be permanently attached to the headplate and shall be designed to permit lamp-reflector adjustment in a vertical plane. The adjustment shall be such as to permit positioning of lamp-reflector optical axis to any angle within the range of from 45 or more degrees below horizontal to 45 or more degrees above horizontal when lantern is worn in the normal manner. The bracket shall be of a design that permits smooth and even lamp-reflector adjustment, without binding, within the above adjustment range. Additionally, the design shall be such as to preclude unintentional movement from adjusted position during normal field use.

3.4.3.2 Headplate pad. There shall be a pad of fine-grain crepe rubber not less than 0.125-inch thick or polyester urethane not less than 0.250-inch thick permanently attached to the concave side of the headplate. The pad shall be attached by rivets or a moisture proof adhesive in accordance with MMM-A-250, having holding qualities equivalent to those of rivets.

3.4.4 Headband. An adjustable headband of woven or braided elastic webbing 22 inches long (free length overall, at maximum adjustment, including attaching clip) by 1-inch wide shall be attached at one end of the headplate (see 3.4.3), and have at the other end a clip for positive attachment to the opposite end of the headplate. There shall be a permanently attached clip on the band for holding the conductor cord (see 3.4.5), at the back of head when the lantern lamp-reflector unit is in place on the head or hat.

3.4.4.1 Clips and attachments. Headband clips and attachments shall be of corrosion-resistant metal or high impact resistant plastic and shall, in combination with the headband elastic webbing, be capable of supporting the headplate and lamp-reflector unit when in place about the head or hardhat. The clips and attachments shall be free of burrs, sharp edges, or other defects.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:25Z
Check the source to verify that this is the currentversion before use.

3.4.5 Conductor cord. The conductor cord connecting the batteries and lamp through the switch shall be two conductor No. 18 AWG, integral construction, trade designation type SP-1, or SPT-1 (in accordance with UL 817) with a minimum free length of 4 feet between the top of the battery case and the point of entry into the lamp-reflector unit casing.

3.4.5.1 Terminals. The conductor cord shall be provided with terminals for attachment to the lampholder and switch by soldering or by screws. The cord terminals at the battery case shall be screw or other removable type as required to permit replacement of the batteries.

3.4.5.2 Strain relief. To prevent mechanical strain on the cord from being transmitted to cord terminals, the cord shall be provided with strain relief at the entry points of the cord to the battery case and lamp-reflector unit casing. Strain relief shall be accomplished by knotting cord, clamping cord or other equivalent means.

3.4.5.3 Protection from chafing. The cord shall be protected from chafing by an insulating rubber, sleeve or grommet, or equivalent means where it passes through any case opening.

3.4.5.4 Current-carrying parts. All current-carrying parts shall be retained in position and insulated from other lantern parts.

3.5 Performance.

3.5.1 Electric circuit. Lantern shall be designed to preclude voltage on any exterior surface. The electrical circuit of the lantern shall be such that the battery circuit cannot be closed by making contact between any metallic points on the exterior of the lantern (see 4.5.7).

3.5.2 Light-beam. The light beam projected by the lamp-reflecting unit shall be free of shadows and filament images and the spread of the beam shall be adjustable by movement of the reflector and lens in relation to the lamp filament to produce a beam of light conforming to the requirements of 4.5.8, 4.5.9, and 4.5.10.

3.5.3 Illumination. The light produced by the lantern shall have illuminating characteristics at least equal to those specified in 4.5.11.

3.6 Weight. The weight of the lamp-reflector unit and headplate (excluding cord, headband, and battery case) shall be not more than 5.750 ounces.

3.7 Finish.

3.7.1 General. All plating and paint finishes and method of application shall be those accepted as being in accordance with good commercial practice for the purpose intended.

3.7.2 Battery case. The battery case, if of corrosion-resistant treated metal, shall receive at least one exterior coat of bright-red enamel or lacquer. If the battery case is not of corrosion-resistant metal, it shall receive at least one coat of bright-red enamel or lacquer on both the interior and exterior. If the battery case is made of plastic, no enamel or lacquer need be applied but the case shall be bright-red in color.

3.7.3 Lamp-reflector unit. Unless otherwise specified elsewhere in this specification, all metal parts of the lamp-reflector unit, except current-carrying parts, shall be chromium or nickel plated or receive at least one coat of enamel or lacquer, or shall be of stainless steel.

3.7.4 Headplate. The headplate, if of metal, shall be chromium or nickel plated or receive at least one coat of enamel or lacquer, prior to attaching of headplate pad, or shall be of stainless steel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

3.7.5 Headband clips and attachments. All metal parts of headband shall be finished as specified in 3.7.3, prior to assembly.

3.8 Identification marking. The manufacturer's name or trademark and part number shall be permanently and legibly marked on the outside of the battery case.

3.9 Workmanship and design. Head lantern shall be free of workmanship or design defects that impair serviceability or appearance and workmanship or design defects that may pose a safety hazard to the user.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspections requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspection are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Lot acceptance inspection as cited in 4.4.
(b) Inspection for preparation for delivery as cited in 4.6.

4.3 Sampling for lot acceptance inspection. Sampling for lot acceptance inspection shall be in accordance with MIL-STD-105. The inspection level for the examination cited in 4.4.1 shall be level S-4 and the Acceptable Quality Level (AQL) shall be 2.5 expressed in percent defective. The inspection level for tests cited in 4.4.2 shall be S-3 and the Acceptable Quality Level (AQL), except as noted, shall be 2.5 expressed in percent defective.

4.4 Lot acceptance examination and tests. Lot acceptance inspection shall consist of the examination and tests cited in 4.4.1 and 4.4.2.

4.4.1 Examination. Samples selected in accordance with 4.3 shall be examined, on a production lot basis, to determine compliance with all requirements of section 3 above that do not require a specific section 4.5 test.

4.4.2 Tests. Samples selected in accordance with 4.3 shall be subjected, on a production lot basis, to all tests specified in 4.5.1, 4.5.3, 4.5.4, 4.5.7, 4.5.8, 4.5.9, 4.5.10, and 4.5.11. The tests specified in 4.5.2, 4.5.5, 4.5.6, and 4.5.12 shall be conducted on only one sample from the first production lot. Subsequent production lot testing in accordance with 4.5.2, 4.5.5, 4.5.6, and 4.5.12 will not be required provided test failure does not occur. Failure of any test specified in 4.5.2, 4.5.5, 4.5.6, or 4.5.12 shall be cause for product rejection.

4.5 Tests.

4.5.1 Operational test. Sample lanterns shall be fitted with batteries and operated in the dark to determine if switch and circuit function properly and if any obvious defects in light emission are present. Any indication of improper operation or presence of an obvious defect shall be considered as a test failure.

4.5.2 Rain test. The completely assembled head lantern, including conductor cord, headplate, headplate bracket, headplate pad, headband, battery case, batteries, lamp-reflector unit and reflector casing, shall be turned on and placed in a rain testing chamber not less than 36 inches high, 36 inches wide, and 36 inches deep. The chamber shall be equipped with water spray nozzles to provide a uniform flow of water over the test area at a rate of 3 inches, plus or minus 1 inch per hour. The direction of rainfall shall be variable from vertical to 45 degrees from the vertical. Water temperature shall be within the range of 4°F to 68°F. The head lantern shall be placed in test chamber in such manner that water will be most likely to enter battery case and reflector casing and then subjected to simulated

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:25Z
Check the source to verify that this is the current version before use.

rainfall at the above flow rate. The direction of flow shall be from vertical for a period of 5 minutes, then from a direction of 45 degrees from the vertical for a period of 5 minutes. Subsequently, the lantern shall be removed from test chamber, turned off, and allowed to dry for four hours at room temperature. At the end of the four hour period, fresh batteries shall be installed and lantern shall be turned on. Failure to produce useable illumination at any time during rain test or after four hour drying period shall be considered a test failure.

4.5.3 Rigidity test. The assembled lantern and battery case shall be subjected to an evenly distributed compressive load of 50 pounds applied randomly without shock to each unit, excepting lens. The load shall remain for 5 minutes, whereupon the lantern and battery case shall be examined. Permanent deformation or breakage of parts shall be considered a test failure.

4.5.4 Drop test. The completely assembled head lantern with batteries, lamp, and spare lamp shall be dropped six times in a random manner from a height of 3 feet into a box of loose, dry sand having a minimum depth of 1 foot and resting on a stable horizontal base. Subsequently, the lantern shall be examined. Permanent deformation, breakage, malfunction or loosening of any part of head lantern, including lamps, shall be considered a test failure.

4.5.5 Impact test. The following test shall be made on a completely assembled lantern and battery case, including batteries. The lantern shall be subjected to a temperature of 150°F dry heat for 2 hours and shall then be immediately subjected to a 12 inch-pound impact using a 1 pound steel ball. The impact shall be applied to all exterior surfaces of the battery case and lantern excepting the lens. The complete lantern shall then be subjected to a temperature of -20°F for 2 hours and again subjected to the impact test as described above. Subsequently, after impact, the lantern shall function as specified in paragraph 3.5. Inability to function as specified in 3.5 or permanent deformation, breakage, or loosening of parts shall be cause for test failure (see 3.4.1 and 3.4.2.5). Note: Batteries may be replaced prior to determining compliance with 3.5.

4.5.6 Lid, hinge, and latch test. The completely assembled lantern shall be subjected to a temperature of +150°F dry heat for 2 hours. Immediately after exposure to the above temperature the battery case lid shall be subjected to 100 cycles of lid openings and closings, a cycle to consist of unlatching the battery case lid, opening lid to widest extent permitted by case design, then closing and latching lid. Subsequently, the completely assembled lantern shall then be subjected to a temperature of -20°F for two hours. Immediately after exposure to the -20°F temperature, the battery case lid shall be subjected to 100 cycles of lid openings and closings in the manner cited above. After testing as described above, the lid, hinge and latch shall be examined for compliance with 3.4.1.1. Indication of damage to lid, hinge, latch or any other component shall be cause for test failure.

4.5.7 Short circuiting test. With batteries and lamp installed and switch in the off position, the lantern shall be wrapped in all possible positions in a conductive surface composed of steel wool pad whereupon compliance with 3.5.1 shall be determined. Closing of the lamp circuit as evidenced by lamp lighting when testing as cited above shall be considered a test failure.

4.5.8 Concentrated light-beam test. The light-beam shall be projected onto a screen whose plane is perpendicular to the optical axis of the lamp-reflector unit and 5 feet distant from the lens. The reflector and lens shall be moved in relation to the lamp filament by rotation of the retaining ring to a point which will produce a concentrated light-beam image on the screen of no more than 9 inches in diameter. Inability to produce the concentrated beam described above shall be considered a test failure (see 3.5.2).

4.5.9 Diffused light-beam test. With the lantern lamp-reflecting unit meeting the same position requirements with respect to a screen as in 4.5.8, the retaining ring shall be capable of being rotated to produce a light-beam image on the screen of 36 inches or more in diameter. Fringe lighting shall be discounted. Inability to produce a light-beam image of 36 inches or more shall be considered a test failure (see 3.5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

4.5.10 Focus-adjustment test. The rotation of the retaining ring from the position which satisfied the light-beam test of 4.5.8 to that which satisfied the light-beam test of 4.5.9 shall have been accomplished in one direction only and the light-beam image diameter shall have increased only during the rotation. The lamp-reflecting unit retaining ring shall have not less than two full threads engaged with the casing at any focus-adjustment within the limits required in 4.5.8 and 4.5.9, and when the lamp-reflector unit is subjected to movements of a magnitude at least as great as those encountered when the lantern is in use, the focus shall not change. Inability to perform as described shall be considered a test failure (see 3.5.2).

4.5.11 Illumination test. With the lantern containing fresh batteries yielding a circuit voltage of 5.0 to 5.1 volts and equipped with a lamp having an electrical rating of 5.1 volts, 0.15 amperes, the focusing adjustment shall be adjusted to produce a light-beam image 12 inches in diameter (excluding fringe lighting) on a screen whose plane is perpendicular to the optical axis of the lamp-reflector unit 5 feet distant from the lens. When measured with a suitable light meter, the brightest portion of the image shall have not less than 5-foot candles when measured over unit areas of not less than 2 square inches. The darkest portions of the image shall have an illumination value of not less than 0.08 of the value of the brightest portion of the image. Inability to obtain the illumination values specified above shall be considered a test failure (see 3.5.3).

4.5.12 Switch-life test. The switch mechanism shall be operated in a normal manner with batteries and lamp through 8,000 cycles with "OFF" to "ON" to "OFF" constituting a cycle, at a rate not to exceed 20 cycles per minute. The switch shall not fail mechanically nor become electrically inoperative during the test. Failure of the battery or lamp shall not be grounds for rejection, however, inability of switch to operate without malfunction shall be considered a test failure (see 3.4.2.9).

4.6 Inspection for preparation for delivery requirements. An inspection shall be made to determine whether the packaging, packing, and marking comply with the requirements of section 5 of this specification. Defects shall be scored in accordance with table I below. For inspection of interior packaging, the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item production lot. The inspection level shall be S-2 with an Acceptable Quality Level (AQL) of 4.0 expressed in percent defective.

TABLE I. Classification of defects

Examine	Defects
Marking	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Material	Any component missing, damaged, or not conforming to the applicable specification or requirements stated herein.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling, or distortion of container.
Contents	Quantity per container is more or less than required. Note: If order is less than the standard pack multiple, the container quantity required shall equal the order quantity. Gross weight exceeds the requirements of the box specification.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:25Z
Check the source to verify that this is the currentversion before use.

5.1.1 Level A and B. Each lantern shall be packaged in a box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. Each box shall be closed to prevent accidental opening.

5.1.2 Level C. Lanterns shall be packaged in accordance with the supplier's commercial practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Unit packages shall be packed in a box conforming to PPP-B-636, class weather-resistant. The box shall be closed, waterproofed, and strapped in accordance with the appendix to the box specification.

5.2.2 Level B. Forty-eight unit packages shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 Level C. The lanterns shall be packed in accordance with the National Motor Freight Classification, item 109477 or the Uniform Freight Classification, item 55725, as applicable.

5.3 Marking. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129, as applicable.

6. NOTES

6.1 Intended use.

6.1.1 Class 1, lanterns. Class 1 lanterns are intended to be worn on the head or hat and provide illumination while walking, climbing, or working, such as in forest fire fighting, for periods up to 10 hours duration without servicing or replacement of parts, except lamp.

6.1.2 Class 2, lanterns. The class 2 lanterns are intended to be worn on the head or hat and provide illumination for the wearer while working in unlighted areas such as tanks, compartments, or other enclosed space where greater illumination for a shorter period of time is required than the class 1 lantern will provide.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Class lantern required (see 1.2.1 and 3.4.2.7).
(c) Batteries, if desired (see 3.4.1.4).
(d) Responsibility for inspection, if other than specified (see 4.1).
(e) Selection of applicable levels of packaging and packing required (see 5.1 and 5.2).
(f) Marking, if other than specified (see 5.3).

6.3 Batteries. Purchasing officers should note that batteries are not furnished with the lanterns covered by this specification unless otherwise specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.