AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

LIGHT, DESK (FLUORESCENT, PEDESTAL)

This amendment was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. The General Services Administration has authorized the use of this amendment as a valid exception to Interim Federal Specification W-L-00310B, dated June 15, 1967.

PAGE 1

Paragraph 1.2, change the reference "W-L-116" to "W-L-00116".

Paragraph 2.1, under "Federal Specifications:", delete the following specifications:

"J-C-580 - Cord, Flexible, and Wire, Fixture, (Electrical, 0- to 600- Volt Service).
W-B-30 - Ballasts, Fluorescent Lamp.
W-L-116 - Lamps, Fluorescent.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall."

Paragraph 2.1, under "Federal Specifications:", add the following:

"J-C-175 - Cable Assembly, Power, Electrical, (3-Wire, 3-Prong, Grounding Plug Connector for 125-Volt Equipment).
W-L-00116 - Lamps, Fluorescent."

Paragraph 2.1, "Military Specification:", delete this section in entirety.

PAGE 2

Paragraph 2.1, under "Military Standards:", delete "MIL-STD-129 - Marking for Shipment and Storage."

Paragraph 2.2, under "Other publications.", insert the following documents:

"National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)"

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 20260-26T11:25Z
Check the source to verify that this is the current version before use.

PAGE 2 (con.)

Paragraph 2.2, also under "Other publications.", delete the last sentence in the first paragraph and substitute "Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply."

Paragraphs 3.1, 3.1.1 and 3.1.2, delete in entirety and replace with the following:

"3.1 Fire and casualty hazards. Each contractor shall submit proof that the desk lights he proposes to supply under this specification conform to the requirements of Underwriters' Laboratories, Inc., Standards UL-153 and UL-542. Evidence of conformance with UL Standards No. 153 and No. 542 shall be the Underwriters' Listing Mark affixed to desk light. In lieu of the Underwriters' Listing Mark, the contractor may submit a test report from an independent laboratory, acceptable to the Government, indicating that desk light conforms to applicable requirements of the published standards, including method of tests of UL Standards No. 153 and No. 542. Compliance with the above preliminary requirements in regard to fire, safety and casualty hazards does not absolve the contractor from complete compliance with the other requirements of this specification in order to secure acceptance of his material or equipment."

Paragraph 3.2.3, delete the first sentence without replacement.

PAGE 3

Paragraph 3.2.9, delete in its entirety and replace with the following:

"3.2.9 Ballast. The ballast furnished with the light shall be suitable for operation on the current specified and shall be in accordance with UL-153. Additionally, ballast(s) shall not contain polychlorinated biphenyl (PCB) insulating fluids."

Paragraph 3.2.12, delete in its entirety and replace with the following:

"3.2.12 Electrical cord. Each light shall be provided with an electrical cord having an exposed length of not less than 9 feet with a molded on parallel blade, three wire grounding, straight-type attachment plug. The cord shall be three conductor, including the equipment grounding conductor. The color of the cord shall be specified in the invitation to bid (see 6.1)."

Paragraph 3.4, third sentence, delete in its entirety and replace with the following:

"Reflecting surfaces other than aluminum shall be white and all other enameled surfaces shall be either smooth or crackle finish, the color of which shall be specified in the invitation to bid (see 6.1)."

PAGE 4

Paragraph 4.4.1, fourth sentence, delete in its entirety and replace with the following:

"The illumination on the horizontal surface shall be measured for compliance with a cosine corrected illuminometer or other suitable instrument capable of being read in foot-candles within the range of illumination values given in 3.3.1 and 3.3.2."

Paragraph 4.4.1, last sentence, delete in its entirety and replace with the following:

"This test shall be conducted on preproduction models only."

PAGES 5 and 6

Paragraph 5, delete in its entirety and replace with the following:

"5. PREPARATION FOR DELIVERY

5.1 Packaging. The packaging shall be level A or commercial as specified (see 6.1).

5.1.1 Level A. Each desk light assembly shall be padded and secured as necessary to prevent abrasion and covered or enclosed in a polyethylene bag.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:25Z
Check the source to verify that this is the current version before use.

PAGES 5 and 6 (con.)

5.1.2 Commercial. Each light shall be preserved and packaged in accordance with normal commercial practice. The complete package shall be designed to protect the item against damage during shipment, handling and storage.

5.2 Packing. The packing shall be level A or commercial as specified (see 6.1).

5.2.1 Level A.

5.2.1.1 Unit pack. Each desk light, packaged as specified in 5.1.1, shall be packed in a fiberboard box made from corrugated fiberboard with a bursting test strength of not less than 275 pounds per square inch. Interior packing forms shall be used to suspend and cushion the unit, prevent movement and provide protection against damage during shipment, handling and storage.

5.2.1.2 Shipping container. Six unit packs (5.2.1.1) of like description shall be packed in a fiberboard box made from weather resistant corrugated fiberboard with a bursting test strength of not less than 275 pounds per square inch. The box flaps shall be secured with water resisting adhesive applied to not less than 75 per cent of the surface area of contact between the flaps or with 3-inch wide water resistant tape applied to the full length of the center seams and extending down over the ends of the box not less than 3 inches. Acceptable alternatives to the fiberboard shipping container are wirebound, cleated plywood, or nailed boxes when lined with a waterproof barrier material. The barrier material shall be sealed at the edges with waterproof tape or adhesive to protect the contents.

5.2.2 Commercial. Each light packaged as specified in 5.1.2 shall be packed in containers to insure safe delivery at destination, to provide for safe redistribution by the initial receiving activity, and shall be acceptable by common carrier under the National Motor Freight Classification or Uniform Freight Classification.

5.3 Unitization. When shipments to Government depots are full car or truck load, the packed lights shall be unitized for shipment and handling in accordance with normal commercial practice. The unitized load shall not exceed 2,500 pounds in weight, 63 inches in height, 56 inches in length, and 45 inches width.

5.4 Marking. Unless otherwise specified (see 6.1), marking shall be in accordance with Fed. Std. No. 123."

PAGE 6

Paragraph 6.1, add the following at end of paragraph:

"(i) Color of cord required (see 3.2.12).
(j) Color of finish required (see 3.4)."

GSA-DC-79-1200

Source: https://assist.dla.mil -- Downloaded: 20260-26T11:25Z
Check the source to verify that this is the current version before use.