W-L-210A
Interim Amendment-1
November 19, 1976

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

LANTERN, ELECTRIC, HEAVY-DUTY
(RECHARGEABLE BATTERY)

This interim amendment was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification W-L-210A, dated May 13, 1975.

PAGE 1

Paragraph 1.1, "Scope.", delete in its entirety and replace with:

"1.1 Scope. This specification covers hand carried, self-contained, battery operated electric lanterns designed with integral (built-in) battery chargers as described in below paragraph 3.6.1."

PAGE 2

Paragraph 2.2, include the following references immediately after the references presently cited:

"Underwriters' Laboratories (UL), Inc. Standards:

No. 153 - Portable Electric Lamps.
No. 498 - Electrical Attachment Plugs and Receptacles.
No. 817 - Cord Sets and Power Supply Cords.
No. 1012 - Power Supplies.

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)"

Paragraph 3.1, delete in its entirety.

Paragraph 3.3, delete in its entirety and replace with the following:

"3.3 Construction. The lantern shall be self contained, consisting of a housing, rechargeable battery, battery charger, lamp, switch, and all other components necessary to constitute a complete, functioning product. Lantern shall meet all applicable requirements of Underwriters' Laboratories, Inc. Standards UL-153 and UL-1012 and shall be "Raintight" as defined in paragraph 64 of the UL 1012 Standard. Additionally, lantern shall be of sturdy construction, capable of withstanding the strains, jars, and vibrations incident to use and shall be designed for use in adverse weather. All parts subject to wear shall be readily accessible for adjustment, repair, and replacement and all components shall be held securely in place. The Listing Mark of Underwriters' Laboratories (UL) affixed to product or test reports from an independent laboratory, acceptable to the Government, indicating compliance with UL Standards cited herein, shall be provided, prior to delivery, as evidence that product conforms to UL Standards. Compliance with Underwriters' Laboratories Standards does not absolve the contractor from complete compliance with the other requirements of this specification in order to secure acceptance of his material or equipment."

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

Paragraph 3.6.1, delete in its entirety and replace with the following.

"3.6.1 Charger. The charger shall be designed to operate on 120 volts, 60 Hz, alternating current (AC), shall be protected against overheating by a device that can be readily reactivated, and shall be furnished as an integral part of lantern assembly with charging circuit built into lantern. Charging shall be accomplished by means of a cord conforming to Underwriters' Laboratories, Inc., Standard UL 817, not less than 6 feet in length. One end of the cord shall be designed to mate with a recessed receptacle mounted in the lantern assembly. The other end of the cord shall be furnished with a 15 ampere, 125 volt connector plug conforming to Underwriters' Laboratories, Inc., Standard UL 498. For preclusion of shock hazard when charging on 120 volts AC, all accessible dead metal parts of lantern assembly shall be provided with a grounding path through charger cord and connector plug. Charger cord shall be furnished as a part of lantern assembly and provision shall be made for cord storage within lantern assembly in such manner that cord will be readily accessible when charging is required. The charger shall be capable of fully recharging the lantern battery within 24 hours at 70°F. Additionally, charger shall be designed to preclude battery damage due to overcharging and battery discharge through the charging circuit. Also, an indicator shall be provided to indicate when a full charge state has been attained. When specified (see 6.2), charger shall be designed to operate on both 120 volts AC, as cited above, and 12 volts direct current (DC) via a charger cord, not less than 6 feet in length, and integral cigarette lighter adapter plug. Both the 120 volt AC and 12 volt DC charger cords and connector plugs shall be furnished as part of lantern assembly, provision for cord storage being made as described above."

Paragraph 3.6.5, add the following sentence at end of paragraph:

"The reflector surface shall be of a material that retains reflectivity."

Paragraph 3.6.5.1, add the following sentence at end of paragraph:

"Light sources of other than sealed beam design may be used provided that these sources are commercially available and have a rated candlepower of not less than 17,000 and a service life of at least 100 hours, and provided that all other requirements of this specification, including the requirements of paragraph 3.8.1 are adhered to."

Paragraph 3.6.5.2, third line, delete the word "of" and replace with the word "on".

Paragraph 3.6.8, delete the maximum weight designation "7 pounds" and replace with the wording "8-1/2 pounds including battery."

Paragraph 3.7.1, delete the last sentence in its entirety.

Paragraph 3.8.2, delete in its entirety and replace with the following:

"3.8.2 Switch. The switch shall be of a design that will insure 1,000 cycles of operation without breakage or otherwise becoming inoperative, one cycle being construed as switch operation from "off" to "on" position and back to "off" position. Testing to determine compliance with the above requirements shall be in accordance with 4.5.1."

Paragraph 3.8.5, delete in its entirety and replace with the following:

"3.8.5 Workmanship and design. Workmanship and design shall be such as to preclude any defect affecting the appearance, serviceability, or safety of the product."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

PAGES 4 and 5

Paragraphs 4.2, 4.2.1, 4.2.2, 4.2.3 (including table I), 4.3, and 4.4, delete in entirety and replace with the following:

"4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Quality conformance (lot acceptance) inspection (see 4.4).
(b) Inspection of preparation for delivery (see 4.6).

4.3 Sampling for quality conformance inspection. Sampling for quality conformance inspection shall be in accordance with MIL-STD-105. The inspection level for the examination cited in 4.4.1 shall be level II and the Acceptable Quality Level (AQL) shall be 2.5, expressed in percent defective. Except as noted, the inspection level for all tests cited in 4.4.2 shall be S-2 and the Acceptable Quality Level shall be 4.0, expressed in percent defective.

4.4 Quality conformance examination and tests. Quality conformance inspection shall consist of the examination and tests cited in 4.4.1 and 4.4.2.

4.4.1 Examination. Samples selected in accordance with 4.3 shall be examined, on a production lot basis, for workmanship, material, general design, insulation, operation of switch mechanism, dimensions, weight, marking, and other requirements of this specification not requireing a section 4.5 test.

4.4.2 Tests. Samples selected in accordance with 4.3 shall be subjected, on a production lot basis, to all tests specified in 4.5.2 thru 4.5.6 inclusive. The test specified in 4.5.1 shall be conducted on only one sample from the first production lot. Subsequent production lot testing in accordance with 4.5.1 will not be required provided test failure does not occur. Failure of the test specified in 4.5.1 shall be cause for product rejection."

PAGE 6

Paragraph 6.2, delete the existing option "(b)" and substitute the following in its place:

"(b) If charger operation on both 120 volt AC and 12 volts DC, via charge cord and cigarette lighter adapter plug, is desired (see 3.6.1)."

GSA OC 77.4243

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.