W-L-311a
INT. AMENDMENT-3
February 16, 1968

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

LIGHT, DESK, INCANDESCENT, FLEXIBLE COLUMN

This interim amendment was developed by the General Services Administration, Federal Supply Service, Washington, D. C. 20405, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification W-L-311a, dated January 14, 1959.

PAGE 1

Delete "FSC 6530" and substitute "FSC 6230."

Paragraph 2.1. Under "Federal Specifications" add the following:

J-C-175 - Cable Assembly, Power, Electrical, (3-Wire, 3-Prong, Grounding Plug Connector, for 125-Volt Equipment).
J-C-580 - Cord, Flexible, and Wire, Fixture, (Electrical, 0- to 600- Volt Service).

PAGE 4

Paragraph 3.5.5, line 5, after the word "by" delete the remainder of the sentence and substitute, "clamp, snap-on or screw-on method."

Paragraph 3.5.6.2. Delete in its entirety and substitute the following:

3.5.6.2 Electrical cord. Unless otherwise specified (see 6.2) each light shall be provided with an electrical cord having an exposed length of not less than 9 feet with a molded-on, clamped-on, parallel-blade attachment plug. The cord shall be type SP-2 or SPT-2, in accordance with J-C-580. When specified (see 6.2), the 3 conductor cord shall be supplied and shall be in accordance with type I of J-C-175. The color of the cord shall be brown or gray as specified (see 6.2).

PAGES 7 and 8

Paragraph 5. Delete in its entirety and substitute:

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each light shall be packaged in accordance with MIL-P-116, method IC-5, utilizing containers conforming to class 2, W5C of PPP-B-636. The containers shall be closed with adhesive and stitching as specified in the appendix to the box specification, and in addition, all cr ·s and joints shall be waterproof sealed with 2 inch minimum width tape conforming to type II, class 1 of PPP-T-60.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:25Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. Each light shall be packaged in a fiberboard box conforming to PPP-B-636, type I, class 1, style optional. Bursting strength of the fiberboard shall be not less than 200 p.s.i. Blocking and bracing shall be provided within the container to prevent movement of the light. Closure shall be in accordance with the appendix to PPP-B-636.

5.1.3 Level C. The lights shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Twelve packages (12 lights of one type and class only, packaged as specified in 5.1) shall be packed in the most compact manner in a snug-fitting shipping container constructed and strapped to conform to class 2, V3C or V3s of PPP-B-636. Alternatively, shipping containers constructed, closed, and strapped to conform to overseas type of PPP-B-591, PPP-B-601, or MIL-B-10377; or class 2, style 2 or 4 of PPP-B-621; or style 1, 2, or 2A, class 3 use of PPP-B-585; or MIL-B-138 may be used. Only one type, style and size shipping container shall be used for any one item on any one contract.

5.2.2 Level B. Six unit packages, of one stock number, shall be packed in a fiberboard box conforming to PPP-B-636, type, class, and style optional. Bursting strength of the fiberboard shall be not less than 275 p.s.i. Closure of the box shall be in accordance with the appendix to PPP-B-636.

5.2.3 Level C. Lights shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.2.4 Standard Pack (civil agency procurement). The standard pack for civil agency procurements shall be as specified in paragraphs 5.1.2 and 5.2.2 (see 6.2 and 6.5).

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123. Unless otherwise specified in the procurement document, the cube shall also be shown.

5.3.2 Military agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

Paragraph 6.2, add:

(f) Type of electrical cord and plug if other than specified (see 3.5.6.2).
(g) Painting method if other than as specified (see 3.5.7).
(h) Cord color required (see 3.5.7).
(i) Finish if other than specified and finish color required (see 3.5.7).

Add new paragraph:

6.5 Standard Pack for civil agencies. The standard pack requirements in 5.2.4 are intended for use in procurements of Stores Stock replenishments. Procuring officers should use the standard pack requirements when it is known that the material will be shipped from a supplier to a domestic warehouse, supply depot or intermediate storage point for temporary storage, subsequent issue and/or shipment to eventual user.

MILITARY INTERESTS:

Army - QMC MCE
Navy - Y
Air Force

GSA DC 68-14766

Source: https://assist.dla.mil -- Downloaded: 20261O-26T11:25Z
Check the source to verify that this is the current version before use.