W-R-101H
March 1, 1995
SUPERSEDING
W-R-00101G (GSA-FSS)
February 17, 1978
W-R-101F
March 13, 1970

FEDERAL SPECIFICATION

RANGES, ELECTRIC (DOMESTIC)

This specification is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers household electric ranges.

1.1.1 Federal specification coverage. Federal specifications do not cover all varieties of the commodity indicated by the title of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government.

1.2 Classification.

1.2.1 Types and sizes. The household electric ranges covered by this specification shall be of the following types and sizes, as specified (see 6.2):

Type I - Single oven

Size 20	-	20-1/2 ± 1 inch wide
Size 24	-	24 ± 1 inch wide
Size 30	-	30 ± 1 inch wide

Type II - Double oven

Class 1 - Side by side

Size 40	-	40 ± 1 inch wide

Class II - Over under

Size 30	-	30 ± 1 inch wide

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

DISTRIBUTION STATEMENT A: APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION IS UNLIMITED

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:22Z
Check the source to verify that this is the current version before use.

Military Specification:

MIL-R-11337 - Range, Packaging and Packing of

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Non-Government publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American National Standards Institute (ANSI):

ANSI Z71.1 - Household Electric Ranges

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

American Society for Testing and Materials (ASTM):

ASTM C 282 - Method of Test for Acid-Resistance of Porcelain Enamel
ASTM D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

Underwriters' Laboratories, Inc. (UL):

UL 858 - Household Electric Ranges

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062-2096.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:22Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Illustrations. Illustrations herein are descriptive and not restrictive and are not intended to preclude the purchase of electric ranges otherwise conforming to this specification.

3.2 Marking. Each item shall be marked with the manufacturer's name or identifying symbol and the state or country of manufacture. The marking shall be engraved, etched, or stamped in such a manner that it will be permanent to the extent that it will remain clear and legible throughout the life of the item.

3.3 Standard product. The electric ranges delivered under this specification shall be the manufacturer's commercially current standard product, except for any changes necessary to comply with the requirements of this specification. All electric ranges of one type and size furnished under this specification for any one contract, including parts and assemblies thereof, shall be interchangeable.

3.4 Standards. The electric ranges shall conform to UL 858 and shall be constructed in compliance with the requirements of ANSI Z71.1.

3.4.1 UL certification. The bidder shall make available to the contracting officer or their authorized representative, that the ranges supplied under this specification meet the applicable requirements of UL 858. Acceptable evidence of meeting the applicable requirements of that standard shall be the UL label, UL listing mark, or a certified test report from a recognized independent testing laboratory acceptable to the Government indicating that the ranges have been tested and conform to UL 858.

3.5 General. The ranges shall comply with the following requirements unless otherwise specified (see 6.2).

1. Design. The ranges shall be free standing, designed for flush-to-wall or slide-in installation, and, except for export ranges, suitable for operation on a nominal 120/240 volt, 60 Hz, 3-wire, single-phase, alternating current (AC) system. All ranges shall be white and, except for size 20 ranges, shall have storage compartments. All storage compartments shall be located beneath the oven. Export ranges shall be designed to operate on 4-wire, three-phase 380/220 "Y connected" AC service. All components must be designed for 220 volt, single-phase power. Maximum power or connected load shall not exceed 11 kilowatts; simultaneous use of the oven broiler shall be prevented by a special blocking switch by which the oven and broiler shall be blocked against each other. The switch shall be designed for the alternate use of either the oven or the broiler unit. Wiring may be in accordance with figure 1 but must be modified for a surface burner indicating light(s).

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:22Z
Check the source to verify that this is the current version before use.

2. Construction and appearance. The ranges shall be sturdy and shall present a pleasing, decorative effect. Asbestos shall not be used as a material in any part of the range.

3. Finish. The front and side exterior surfaces shall be porcelain enamel, baked-on enamel, or a synthetic baked-on enamel capable of withstanding 250°F. Porcelain enamel thickness shall not be greater than 12 mils. The finish shall present a pleasing appearance and all exterior materials shall be compatible and include the manufacturer's standard trim. Removal of accessories or trim not specified, but which will affect the appearance or serviceability of the range(s), is not acceptable.

4. No-drip top. The design of the no-drip cooktop shall prevent spillage from flowing onto the floor or over the side of the range.

5. Cleanability. All ranges shall be designed to permit easy cleaning of all surfaces and cavities where grease and other forms of soil collect. The area beneath the cooking surface shall be porcelain enameled (except size 20 ranges). Where lift-up or lift-off cooktops are not provided, the range design shall provide for ease of cleaning beneath the surface heating elements.

6. Oven light. The oven light shall illuminate the oven interior, be easily replaceable, and protected so as to prevent its being damaged during normal oven use.

7. Oven light switch. The manual switch shall be located in a position which allows for convenient and safe operation.

8. Safety. The range shall be free of sharp edges and shall be designed so that user injury will not occur when the range is cleaned or in operation.

9. Accessibility for repairs. The range shall be designed so that removable parts are accessible from the front and that most repairs can be accomplished without moving the range; i.e., burner elements.

10. Size and shape of the levelers. The levelers shall be of such a size and shape so that during ordinary moving or positioning, the levelers shall not scratch, cut, or otherwise damage a vinyl tile floor.

11. Oven door action. The oven door(s) will operate with a smooth action through that portion of the opening and closing arc not restrained by detent(s); i.e., the hinges shall not bind during opening and closing, nor shall the door open or shut with excessive force.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:22Z
Check the source to verify that this is the current version before use.

12. Ovens. Oven linings shall be the manufacturer's standard porcelain enamel. A "continuous cleaning" oven lining or pyrolytic self-cleaning oven feature shall be used when specified. If a removable oven bottom is used, the parts shall mate securely and no insulation shall be exposed when the bottom is removed. Oven racks and broiler pans and racks shall be constructed of suitable materials and shall adequately perform their intended functions. All ovens shall have at least 10 inches of "usable oven space" measured vertically from the highest projection of an oven rack in its lowest position to the lowest projection of the oven broiler element in its use position.

13. Oven bake and broiler elements. If the bake element is the removable type, it shall be easily removable and replaceable. If the bake element is the fixed-typed, it shall be hinged at the rear and shall be so designed as to prevent any live metal parts; i.e., a part that could cause arcing or shorting, to come into contact with the range body or oven when the element is rotated about the fulcrum point within the confines of the oven. When the elements are in their cooking position, they shall fit securely and shall adequately perform their intended functions.

14. Heating element controls. All heating element controls shall have the various positions suitably, legibly, and permanently marked on, or immediately adjacent to, each control. Surface element control switches shall be either the 6-position (5 heat and one OFF) or the infinite-heat type. Where infinite-heat type controls are provided, detents or some type of frictional device shall be provided to indicate the OFF and HIGH positions.

15. Surface heating elements. Surface heating elements shall seat firmly and securely and shall be centered in the openings provided. Plug-in units shall have "positive" attachment so that plug-in is ensured. Hinged units shall be hinged so that ease of cleaning is ensured.

16. Storage compartments. Storage compartment drawers and doors shall operate smoothly when opening and closing and shall fit securely in their intended openings. Storage drawers shall extend to the full width of the range, below the oven compartment.

17. Backguard. When decorative backguards are specified, they shall present an aesthetically pleasing appearance. All glass used in backguards shall be heat tempered. The placement of range controls, indicating lights, clocks, etc., shall not be acceptable as the sole decorative influence. Finishes that may be damaged by scrubbing are not acceptable.

18. Self Cleaning. When specified (see 6.2) the oven shall be self cleaning in accordance with the applicable requirements of UL 858.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:22Z
Check the source to verify that this is the current version before use.

3.6 Features. Except where otherwise specified, all ranges shall be provided with the following features (see 6.2):

(a) Porcelain enameled oven lining, two corrosion-resisting steel or nickel-plated or chrome-nickel-plated baking racks, and a porcelain enameled (or equivalent) broiler pan and rack.

(b) Recessed (no-drip) cooking top.

(c) Clock and interval timer which sounds an alarm when the preset time has elapsed.

(d) A manual switch-controlled oven light in each oven.

(e) A heat-resisting oven viewing window in all oven doors except the oven door of the size 20 range and the door of the small oven of the type II double-oven range.

(f) When lift-up cooktops are provided, porcelain enameling of the surface below the cooktop, except on size 20 ranges.

(g) A total of four heating elements. At least one shall be 8 inch nominal diameter, all other heating elements shall be 6 inches. The 8 inch elements shall have a minimum rating of 2,000 watts, and the 6 inch elements shall have a minimum rating of 1,200 watts. Reflector pans shall be furnished under each surface heating element.

(h) Porcelain enameled surfaces shall be class A when tested in accordance with paragraph 4.2.1.2. Porcelain enamel thickness shall be no greater than 12 mils (0.012 inch).

(i) A light or equally effective device(s) to indicate when surface elements are energized; a separate light shall be used to indicate an energized oven on all ranges including export models.

(j) A decorative backguard, except on size 20 and 24 ranges.

(k) At least two leveling devices capable of leveling the range(s) when installed.

3.7 Finish on unexposed surfaces. Surfaces of parts not exposed to view in normal usage shall be protected in such a manner that any oxidation which may occur will not interfere with its intended function. An oxide coating is acceptable for these unexposed surfaces.

3.8 Oven door. After being tested as specified in 4.3.2, when in a fully closed position, the oven doors shall show no evidence of gaps or warpage. The oven door and its components shall show no evidence of breakage or permanent distortion.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:22Z
Check the source to verify that this is the current version before use.

3.9 Surface temperature. Surface temperatures on the door handles, knobs, sides, and door panels of the range(s) shall be measured to determine conformance to the requirements of UL 858. The test shall be conducted in accordance with the test procedure set forth in UL 858. Any nonconformance to the specified requirements shall constitute failure of the test (see 4.3.3).

3.10 Electric range efficiency. The total thermal efficiency of the surface burners and ovens shall be not less than those specified below, when tested as specified in paragraph 4.3.4. If disc elements are used, the average surface unit efficiency shall be not less than 70 percent.

Size	Surface units (average)	Oven(s)
20 inch	75 percent	13 percent
24 inch	75 percent	12 percent
30 inch	75 percent	11 percent
40 inch	75 percent	11 percent-Large
		13 percent-Small

3.11 Workmanship. The finished range shall be clean and shall not contain any burrs, slivers, sharp edges, or rough die, tool, gouge, or grind marks. Holes for bolts, screws, rivets, or threaded fasteners shall be accurately punched or drilled, and any obstruction that prevents proper seating of rivets shall be removed. The driven rivets shall be fully peened with the heads in full contact with riveted members. Components shall not be fractured, buckled, kinked, bent, dented, punctured, or malformed. There shall be no evidence of pits or stains, blistering, or flaking, peeling, or large discoloration (exposed surfaces). Components shall be free of areas of no film or rust, foreign matter imbedded in finish, or finish wet or tacky (painted surfaces), sags, or runs. The range shall be designed so that parts mate properly without excessive play.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure that supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. In accordance with 4.1 above, the supplier is responsible for insuring that components and materials used were manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specification and standards to the extent specified, or, if none, in accordance with this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:22Z
Check the source to verify that this is the current version before use.

4.2 Sampling procedures. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 In-process inspection.

4.2.1.1 In-process examination. Examination shall be made of the finishing operations on unexposed surfaces to establish compliance with the requirements of 3.7. Wherever noncompliance is noted, correction shall be made to the affected items and lot in process.

4.2.1.2 Intermediate testing. Porcelain enamel finished parts shall be tested using ASTM C 282 to determine compliance with paragraph 3.6(h). Porcelain enamel thickness shall be measured with a magnetic thickness gauge calibrated to an accuracy of ± 0.001 inch. The lot shall consist of one day's production of cooktops, door panels, front panels, and side panels, as applicable. The inspection level shall be S-1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0.

4.2.2 End item inspection. The unit of product shall consist of all ranges of one type and size offered for inspection at one time. The sample unit shall be one completely fabricated range.

4.2.2.1 Visual examination. Visual examination shall be made of the range for the defects listed in table I. The inspection level shall be level I and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total, major and minor combined, defects.

TABLE I. Classification of defects

Examine	Defects	Classification Major	Minor
Finish (general)	Not as specified		201
	Evidence of pits, stains, peeling, flaking, blistered spots, large dis coloration (exposed surfaces)	101	
	Not finished or coated (where required)	102	
	Area of rust	103	
	Color not as specified, area of no film sags or runs, foreign matter imbedded in finish, or finish wet or tacky (painted surfaces)		202
Porcelain enamel	Bare metal shows through on corners	104	
	Ground coat visible through cover coat on exterior surfaces	105	
	Chipped exterior surface on surface likely to contact food	106	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:22Z
Check the source to verify that this is the current version before use.

Porcelain enamel finish	Chipped surfaces not likely to contact food		203
	Fish scaling or burn-off	107	
	Copperhead accompanied by a pulling away or cutting up of the enamel	108	

TABLE I. Classification of defects (cont'd)

Examine	Defects	Classification Major	Minor
Porcelain enamel finish (cont'd)	Copperheads small or infrequent specks		204
	Crazing, crawling, specking, or tearing affecting appearance	109	
	Enamel lumps, wrinkled, or wavy surface		205
	Hairlines or star marks		206
Construction and workmanship (general)	Any component missing	110	
	Any burr, sliver, sharp edge, rough die or tool gouge, trim, or grind marks		207
	Any component fractured, buckled, warped, loose, kinked, dented, punctured, or malformed	111	
	Top surface of heating units not flat (check with straight edge)	112	
	Top not in line with front and sides	113	
Reflectors or drip trays (as applicable)	Not removable	114	
	Dented or bent		208
Oven	Broiler pan or rack not supplied	115	
	Oven light not as specified	116	
	Less than two baking racks		209
	Rack jams when inserted in, or withdrawn from shelf support		210
	Oven light switch not as specified	117	
Surface heating units	Not as specified	118	
Thermostat	Not protected from direct heat, moisture, or grease	119	
Doors and handles	Opening around doors not in vertical and horizontal alignment	120	
	Handles mounted crookedly		211
	Door will not remain in full open position	121	

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:22Z
Check the source to verify that this is the current version before use.

	Door operation not smooth	212
	Oven door does not stay closed; cannot be adjusted	122

TABLE I. Classification of defects (cont'd)

Examine	Defects	Classification Major	Minor
Thermostat doors and handles (cont'd)	Oven door loose and wobbly when in the full open position or during its opening arc		213
Wiring and switches	Switches broken or jammed	123	
	Surface switches mounted on cooking top	124	
	Surface element switches not at least 6-position (5 heat and one OFF)		214
	Push-on connectors not properly attached to the conductors, or wrong type of wire	125	
	Position not marked as specified	126	
	Loose wiring connection	127	
	Means to prevent accidental turn-on not provided	128	
Marking for identification	Missing, incomplete, or illegible		215

4.2.2.2 Dimensional examination. Examination shall be made of the ranges for compliance with all dimensions specified. Any nonconformance to specified requirements shall constitute a defect. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.2.2.3 First article tests. When required by the contract, the examinations of paragraphs 4.2.2.1 and 4.2.2.2, and the tests of paragraphs 4.3.1, 4.3.2, 4.3.3, and 4.3.4 shall be performed as first article tests.

4.2.2.4 Lot inspection. The lot by lot inspections shall consist of the examinations of paragraph 4.2.2.1, 4.2.2.2, and 4.2.3, and the test of paragraph 4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:22Z
Check the source to verify that this is the current version before use.

4.2.3 Inspection of preparation for delivery requirements. An inspection shall be made to determine that the preservation, packaging, packing, and marking comply with the requirements in section 5 of this specification. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one container fully prepared for delivery. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

TABLE II. Classification of preparation for delivery defects

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling Distortion of container
Contents	Number per container is more or less than required Net weight exceeds requirements

4.3 Test.

4.3.1 Operational test. All end items shall be tested for operation and fit of all controls and moving parts. The unit shall be connected to a rated power source and operated without load. Then, the test operator shall examine all controls, switches, and moving parts for proper fit, and energize and operate controls to ensure that they are properly connected to the designated surface or oven heating element. The Inspection Level shall be 5-2 and the AQL expressed in terms of defects per hundred units shall be 2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:22Z
Check the source to verify that this is the current version before use.

4.3.2 Door hinge test. The oven thermostat shall be set at 330°F ± 5°F above ambient temperature and the oven operated for at least one hour to ensure stabilization of the oven temperature. Then, without adjustment of the oven controls, the oven door shall be operated through 25,000 cycles from an essentially closed position to an essentially fully open position, and returned at a frequency of approximately 15 cycles per minute. Upon completion of the 25,000 cycles, the oven shall be shut down and without adjustment, modification, or disassembly of the oven door, its hinges, or any other component part, the oven door shall be subjected to a load of 25 lbs. (± 5 percent) applied without impact to a 5 square inch area (± 10 percent) for five minutes at one outer corner of the fully open door. The other outer corner shall be supported in its fully open position. The load shall be removed, the door examined for proper fit and closure, and the procedure repeated with the load applied to the other outer corner. After the second loading, the door shall again be examined for proper fit and closure at which time there shall be no warpage of the oven door or evidence of gaps between the oven face and the oven door when in a fully closed position. A distributed load of 50 lbs. (± 5 percent) shall then be applied without impact along a 4 inch strip (± 10 percent) midway between the hinged edge and the outer edge of the fully open door for five minutes. Any nonconformance to the specified requirements (see 3.8) shall constitute failure of the door hinge test. At the conclusion of the door hinge test, without adjustment to the door or its components, the surface temperature and efficiency test shall be conducted (see 4.3.3 and 4.3.4).

4.3.3 Surface temperature test. Surface temperatures on the door handles, knobs, sides, and door panels of the range(s) shall be measured to determine conformance to the requirements of UL 858. The test shall be conducted in accordance with the test procedure set forth in the UL 858 standard. Any nonconformance to the specified requirements shall constitute failure of the test.

4.3.4 Electric range efficiency test.

4.3.4.1 Surface units.

4.3.4.1.1 Test block. Aluminum test blocks with the following specifications shall be used during this test:

> Aluminum alloy 6061, 96 percent pure. The highest degree of purity possible within the limits of economic feasibility and timelessness should be obtained. Two aluminum, handle-support screws are to be placed diametrically opposite each other approximately one-half way up the side of the block. A hole 0.08 inches (2 mm) in diameter and 0.8 inches ((20 mm) deep is to be drilled in the center of the top of the block. The height of the test block is to be adjusted to match weight including screws.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:22Z
Check the source to verify that this is the current version before use.

Small Block	Large Block
Diameter 6.25 " ± 0.05"	Diameter 9.0" ± 0.05"
(158.8 mm ± 1.3 mm)	(228.6 mm ± 1.3 mm)
Height 2.8" (71 mm)	Height 3.0" (76 mm)
Weight 8.5 lb. ± 0.1 lb.	Weight 19.0 lb. ± 0.1 lb.
(3.8556 kg ± 0.05 kg)	(8.6184 kg ± 0.05 kg)

NOTE: The small test block shall be used on electric surface units seven inches or less in diameter. The large test block is to be used for electric surface units over seven inches in diameter.

4.3.4.1.2 Thermal efficiency test. The thermal efficiency of each range surface unit shall be measured as follows: A thermocouple shall be located in the hole of the aluminum test block. The thermocouple shall be connected to a suitable recording instrument. Locate the appropriate test block with handle removed centrally on the unit being tested. The test block shall be at room temperature (68°F ± 9°F). Energize the unit at its highest power setting (100 percent). When the block reaches 212°F, immediately reduce input to 25 percent ± 5 percent. After 15 minutes at the reduced input, record the test block temperature, ambient temperature, and watt hours consumed. The thermal efficiency of each range surface unit shall be determined as follows:

$$E_{1-4} = \frac{(W) \times (CP) \times ({}^{T}F - {}^{T}i)}{(Wh) \times (K)} \times 100$$

E_{1-4} = Individual thermal efficiencies of surface units one through four (percent)

W = Weight of block in pounds (lbs.)

CP = Specific heat of block = (0.23 BTU/lbs. °F)

$({}^{T}F - {}^{T}i)$ = Observed temperature rise of test block (°F)

Wh = Watt hours consumed during test

K = Factor to convert watt hours to BTU (3.413)

E_T = The average total efficiency of the surface units is the arithmetic average of the individual units

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:22Z
Check the source to verify that this is the current version before use.

4.3.4.2 Oven units. For 60 Hz ranges, efficiencies are to be determined in accordance with "Uniform Test Method for Measuring the Energy Consumption of Conventional Ranges, Conventional Cooking Tops, Conventional Ovens, Microwave Ovens, and Microwave/Conventional Ranges" in the Code of Federal Regulations, Title 10, Chapter II, Part 430 (01/01/90).

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing, labeling, and marking. Unless otherwise specified, preservation, packaging, packing, labeling, and marking shall be in accordance with ASTM D 3951.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The electric ranges are intended for use in domestic kitchens of civil and military quarters.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Type and sizes (see 1.2.1).
c. General requirements, if other than specified (see 3.5).
d. Self-cleaning oven, if required (see 3.5 (18)).
e. Electrical requirements, if other than specified (see 3.5).
f. Features, if other than specified (see 3.6).
g. Preservation, packaging, and packing required (see 5.1).

NO DoD INTEREST

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:22Z
Check the source to verify that this is the current version before use.