MIL-C-46411B(MU)
23 APRIL 1965
SUPERSEDING (SEE 6.6)
MIL-C-46411A (MU)
31 MAY 1963

MILITARY SPECIFICATION

CARTRIDGE, 4.2 INCH, SMOKE, WP, M328A1, W/FUZE, PD, M521. LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of smoke cartridge designated as M328A1, for use with 4.2 Inch Mortars.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 — Ammunition and Special Weapons; General Specification for

MIL-I-45607 — Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

MIL-STD-109 — Quality Assurance Terms and Definitions

MIL-STD-1235 — Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ORDNANCE CORPS

7549247 — Container, Fiber M251 for 4.2 Inch Mortar Ammunition, Assembly Details and Packing

7549248 — Box, Packing, Ammunition for 4.2 Inch Mortar Ammunition, Assembly Details and Packing

8797829 — Cartridge, 4.2 Inch WP, Smoke M328A1

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

ORDNANCE CORPS

IEL-8797829 — Index of Inspection Equipment Lists

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 **Material.** Materials shall be in accordance with applicable drawings and specifications.

3.2 **Cartridges.** The cartridge shall comply with all requirements specified on Drawing (dwg.) 8797829, and with all requirements specified in applicable specifications.

3.3 **Proving ground.** The cartridge shall comply with the following requirements when tested as specified in 4.3.1.

3.3.1 *Failure to fire.* The cartridge shall not fail to fire.

3.3.2 *Impact functioning.* There shall be visible evidence of functioning upon impact as indicated by presence of a flash or smoke cloud (see 6.5).

3.3.3 Horizontal range

3.3.3.1 No cartridge shall have a horizontal range less than 90 percent of the average horizontal range.

3.3.3.2 The standard deviation in horizontal range shall be no greater than the maximum lot values shown in table I for the charge value indicated.

TABLE I

Charge increments	Maximum (max.) lot standard deviation (yards)
7	22
41	72

3.3.4 *Delayed functioning.* There shall be no evidence of delayed functioning of the projectile upon impact.

3.3.5 *Premature functioning and security of parts.* There shall be no premature burst or metal parts failure in the bore of the weapon, or in flight before impact.

3.4 **Workmanship**

3.4.1 All processing and assembly operations of the cartridge shall be correctly performed in a thoroughly workmanlike manner. Parts shall be free of chips, dirt, grease, rust and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents.

3.4.2 The painting and marking shall be restored by the assembling contractor on any components furnished to him painted and marked when such painting and marking has been marred or obliterated.

4. QUALITY ASSURANCE PROVISIONS

4.1 **General quality assurance provisions.** Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 *Submission of product.* At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following informa-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.

tion accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

(a) A statement that the lot complies with all of the quality assurance provisions specified within this specification.

(b) Number of units of product inspected.

(c) Results obtained, by defect code, for all inspections performed.

(d) Drawing, specification number and date, together with an identification and date of changes.

(e) Certificates of compliance on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.

(f) Number of items in the lot.

(g) Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.2 *Government verification.* Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 **Inspection provisions**

4.2.1 *Lot formation.* A lot shall consist of cartridge assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance or fit, as determined by the Government, shall not necessitate changing the lot interfix number. Lots shall be submitted for inspection in accordance with Standard MIL-STD-105 (or Standard MIL-STD-1235, when applicable). Each lot shall contain:

(a) WP loaded projectile assemblies from one manufacturer in accordance with the same drawing, same drawing revision, same specification and same specification revision of one loading lot interfix number and of one weight zone.

(b) Loaded ignition cartridges of one lot interfix number from one manufacturer.

(c) Propelling charge assemblies made from not more than one lot from one manufacturer.

(d) Loaded fuzes of one lot interfix number from one manufacturer.

(e) Loaded burster initiators of one lot interfix number from one manufacturer.

(f) Loaded projectile bursters of one lot interfix number from one manufacturer.

(g) Obturating mechanisms from one manufacturer in accordance with the same drawing, same drawing revision, same specification and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.

same specification revision of one lot interfix number.

4.2.2 *Examination.* Inspection for Critical defects shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Projectile loading assembly as received from WP loading facility (see dwg. 8797838 covering a detail of dwg. 8797829).

Categories	*Defects*	*Method of inspection*	*Code No. (see 6.8)*
Critical:			
1.	WP leakage or evidence of leakage	Visual	01001
Major: None defined.			
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	01002

4.2.2.2 Projectile loading assembly, prior to inserting burster (see dwg. 8797838 covering a detail of dwg. 8797829).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical:			
1.	Burster pad missing	Visual	02001
Major:	AQL 0.40 percent		
101.	Zone marking missing, misleading or incorrect	Balance-Visual	02002
Minor:	AQL 1.00 percent		
201.	Foreign matter in burster tube	Visual	02003
202.	Evidence of poor workmanship (see 3.4)	Visual	02004

4.2.2.3 Cartridge prior to inserting fuze (see dwg. 8797829).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Burster charge missing	Visual	03001
102.	Burster initiator missing	Visual	03002
103.	Foreign matter in fuze well	Visual	03003
104.	Ring, snap, in groove	Visual	03004
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	03005

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.

4.2.2.4 Cartridge, prior to assembling pressure plate (see dwg. 8797829).

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Torque test failure of cartridge container	Test	04001
102.	Rotating disc improperly assembled or loose	Visual-Manual	04002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	04003

4.2.2.5 Cartridge, after assembly of pressure plate and pressure plate nut (see dwg. 8797829).

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Pressure plate incorrectly assembled	Visual	05001
102.	Pressure plate nut stake missing or inadequate	Visual-Manual	05002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	05003

4.2.2.6 Cartridge, after assembling ignition cartridge and striker nut assembly (see dwg. 8797829).

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Striker point missing, loose, damaged or extended through striker plate	Visual	06001
102.	Ignition cartridge missing	Visual	06002
103.	Striker nut loose	Manual	06003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	06004

4.2.2.7 Cartridge after assembling cartridge container extension (see dwg. 8797829).

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Pin missing	Visual	07001
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	07002

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.

4.2.2.8 Cartridge (see dwg. 8797829).

Categories	Defects	Method of inspection	Code No.
Critical:			
1.	Warning label missing or unidentifiable	Visual	08001
Major:	AQL 0.65 percent		
101.	Torque test failure of fuze	Test	08002
102.	Fuze stake missing	Visual	08003
103.	Any component missing, damaged or incorrectly assembled	Visual	08004
Minor:	AQL 1.50 percent		
201.	Protective coating with total damaged area in excess of ¼ inch square	Visual	08005
202.	Marking misleading or unidentifiable, including incorrect color code	Visual	08006
203.	Fuze not fully seated	Visual	08007
204.	Evidence of poor workmanship (see 3.4)	Visual	08008

4.2.2.9 Unsealed fiber container (see dwg. 7549247).

Categories	Defects	Method of inspection	Code No.
Critical:			
1.	Propellant increment cut, torn or incorrect number	Visual	09001
Major:	AQL 0.40 percent		
101.	Packing component missing	Visual	09002
102.	Filler component missing	Visual	09003
Minor:	AQL 1.50 percent		
201.	Glue or asphalt on round	Visual	09004
202.	Cartridge improperly assembled into container	Visual	09005
203.	Round cannot be removed by hand	Manual	09006
204.	Evidence of poor workmanship (see 3.4)	Visual	09007

4.2.2.10 Sealed fiber container (see dwg. 7549247).

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Container damaged or cut through all asphalt layers	Visual	10001
102.	Tape incomplete or badly wrinkled	Visual	10002
103.	Meetal end loose or distorted	Visual-Manual	10003
Minor:	AQL 2.50 percent		
201.	Marking misleading or unidentifiable	Visual	10004
202.	Gap between cover and body of container exceeding ⅛ inch	Visual	10005
203.	Cuts, scuffs or gouges in outer layer	Visual	10006
204.	Evidence of poor workmanship (see 3.4)	Visual	10007
205.	Tear tab length inadequate	Manual	10008
206.	Contents loose	Manual	10009

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.

4.2.2.11 Unsealed wood packing box (see dwg. 7549248).

Categories	Defects	Method of inspection	Code No.
Critical:			
1.	Sealing strip end of fiber containers not placed at end of box opposite that marked nose end	Visual	11001
Major: None defined.			
Minor: None defined.			

4.2.2.12 Sealed wood packing box (see dwg. 7549248).

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Box damaged exposing contents	Visual	12001
102.	DOD symbol missing or incorrect	Visual	12002
103.	Board broken or split	Visual	12003
104.	Hardware or strapping missing, broken or loose	Visual-Manual	12004
Minor:	AQL 2.50 percent		
201.	Marking misleading or unidentifiable	Visual	12005
202.	Hardware improperly engaged	Visual-Manual	12006
203.	Car seal missing, unsealed or improperly positioned	Visual-Manual	12007
204.	Contents loose	Visual-Manual	12008
205.	Handle missing or insecure	Visual-Manual	12009

4.2.3 Testing

4.2.3.1 *Check test for possible deterioration of ignition cartridge (see applicable specification) Code No. 06007.* If the total elapsed time between original acceptance of an ignition cartridge lot and the assembly of that lot into complete round cartridges exceeds two years, or if the ignition cartridges have been subjected to adverse conditions, however brief, at any time since previous tests, the applicable lot shall be subjected to and must satisfactorily pass the check list for deterioration specified in the applicable ignition cartridge specification immediately before the ignition cartridges are assembled into the complete round cartridges. The test shall be performed by the contractor on ignition cartridges selected by the Government inspector at the facility assembling the ignition cartridges into the complete round cartridges (see 6.4).

4.2.3.2 *Profile and alignment (see dwg. 8797829)—Major defect—Code No. 08009.* The cartridges, including those which have had the bourrelet repainted (see 3.4.2), shall be gaged 100 percent for profile and alignment. Any cartridge which fails to comply with the applicable requirement shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.3.3 *Proving ground test.* The cartridges shall be observed for compliance with the requirements as classified in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.

TABLE II

	Defect classification	Code No.
(a) Premature functioning or metal parts failure (see 3.3.5)	Critical	08010
(b) Failure to fire (see 3.3.1)	Major	08011
(c) Impact functioning (see 3.3.2)	Major	08012
(d) Horizontal range (see 3.3.3.1)	Major	08013
(e) Delayed functioning (see 3.3.4)	Major	08014

4.2.3.3.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, a sample of 80 cartridges shall be selected from each lot for this test. If a premature burst or metal parts failure occurs (see 3.3.5) or if two or more cartridges fail to comply with the failure to fire requirement (see 3.3.1) or the horizontal range requirement (see 3.3.3.1) or if four or more cartridges fail to comply with the impact functioning requirement (see 3.3.2) or if six or more cartridges fail to comply with the delayed functioning requirement (see 3.3.4), the lot shall be rejected. In addition, if the standard deviation in horizontal range for the sample cartridges fired at increment charge 7 or increment charge 41 multiplied by the factor 0.79 exceeds the applicable maximum limit specified in table I (see 3.3.3.2), the lot shall be rejected. The test shall be performed as specified in 4.3.1.

4.2.3.3.2 After three consecutive lots have met the criteria of 4.2.3.3.1, the sampling plan for this test shall be in accordance with Standard MIL–STD–105, Code letter H (single sampling), utilizing an AQL of 0.40 percent for defects (b) and (d), an AQL of 1.5 percent for defect (c) and an AQL of 2.5 percent for defect (e). The lot shall be rejected if a critical defect occurs during any portion of the test or if the number of defects equals or exceeds the rejection number specified. In addition, if the standard deviation in horizontal range for the sample cartridges fired at increment charge 7 or 41 multiplied by the factor 0.75 exceeds the applicable maximum limit specified in table I (see 3.3.3.2), the lot shall be rejected. The test shall be performed as specified in 4.3.1.

4.2.4 *Inspection Equipment.* Index of Inspection Equipment Number IEL–8797829 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 *Government rights to documentation.* Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 *Supply and maintenance.* Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL–I–45607.

4.2.4.3 *Government use of contractor's inspection and test equipment.* The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.

4.3 Test methods and procedures

4.3.1 *Proving ground tests.* These tests shall be conducted at a Government proving ground in accordance with the applicable Ordnance Proof Manual and acceptance test procedure.

4.3.1.1 *Functioning.* The cartridges for this test shall be divided into two equal groups. Group I shall be fired with 7 increments of propellant at a mortar elevation of 1065 mils. Group II shall be fired with 41 increments of propellant at a motor elevation of 900 mils. The fuzes shall be set superquick and the cartridges shall be fired from a mortar for which the round is standard. The individual velocities and impact ranges shall be recorded. Observation shall be made for compliance with the applicable requirements.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 *Level A.* The cartridge shall be preserved and packaged in accordance with dwg. 7549247.

5.2 Packing

5.2.1 *Level A.* The cartridge in containers shall be packed in accordance with dwg. 7549248.

5.3 Marking of the fiber container shall be in accordance with dwg. 7549247. The wood box shall be marked in accordance with dwg. 7549248.

5.4 Data cards. Data card information shall be prepared for each lot in accordance with the information specified in Specification MIL–A–2550.

6. NOTES

6.1 Ordering data. Procurement documents shall specify title, number and date of this specification.

6.2 Inspection code numbers. The five digit code numbers assigned to the *inspections* herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment. The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.7.

6.3.1 *Inspection equipment lists.* Inspection equipment lists indicate the availability of inspection equipment designs by showing in the number column of the list of inspection equipment (00 Form 1242–3) the numbers of drawings of existing equipment designs or codes as indicated in paragraph 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 *Inspection equipment list codes.* The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5 and 6.3.6 will be designated in the IEL by the following codes:

CDAF — Contractor's design responsibility on Army format in accordance with MIL–D–45608.

CDCF — Contractor's design responsibility on contractor format.

AD — Army design.

ADMU — Army design, mandatory for use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.

CE — Commercial equipment.

SCD — Specification control drawing.

6.3.3 *Army designs.* Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications, mandatory and nonmandatory. When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with nonmandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approbed by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 *Specification control drawing.* Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagrammatic or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 *Commercial equipment.* Commercial equipment is inspection equipment that has universal appliation for a specific function. It is comprised of items commonly used by industry and Government. Contractors are not required to furnish drawings of commercial inspection equipment, but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 *Contractor designs.* Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDAF shall comply with the format and requirements of MIL–D–45608, and in addition, contain the detail and information specified above. Final approved contractor designs identified as CDCF shall be suitable for microfilming. They must be nonreproducible diazo or electrostatic prints of top quality full size with black line on white background and shall provide a legible print produced via the 35mm microfilm process. Contractor shall submit one copy of the final design as a rolled set or flat set.

6.3.7 *Submission of contractor designs.* Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA–ND. Design review normally will be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.

the Arensal completion date for design review will be based on the date of the final submission of designs.

6.4 **Cost of check test.** The contracting officer shall arrange for the contractor to be reimbursed for the expense incurred in the performance of the check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the ignition cartridges or to the contractor assembling the cartridge, and shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the ignition cartridge lot was under the jurisdiction of either contractor.

6.5 **Impact functioning.** The cartridge shall function with sufficient fragmentation of the projectile to adequately disperse the chemical.

6.6 **Supersession data.** The specification supersedes in part MIL-S-11354A (Ord), 27 May 1960, covering Shell, WP, M2, M2 alt, M2A1, M2A1 alt, E84R7 (M328) and E84R7 alt (M328B1); Shell, HE, M3A1, M3A1 alt, M329 and M329E1 w/Fuze for Mortar, 4.2 Inch; Loading, Assembling, Marking and Packing.

6.7 **Submission of test data.** In addition to the normal distribution of records, when the cartridge is procured by the Department of the Army, one copy of all test data shall be forwarded to each of the following:

Commanding Officer
Picatinny Arsenal
ATTN; SMUPA-ND2 and SMUPA-DC8
Dover, N.J.

Custodian:
Army—MU

Preparing activity:
Army—MU

Project Number 1315-A444

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:53Z
Check the source to verify that this is the current version before use.