MILITARY SPECIFICATION

CARTRIDGE, CALIBER .38, SPECIAL, BALL, M41A1

This Amendment forms a part of Military Specification MIL-C-46409C (MU), dated 14 June 1976, and is approved for use within the US Army Armament Munitions and Chemical Command and is available for use by all Deparments and Agencies of the Department of Defense.

PAGE 1

Add the following preamble underneath the title:

"This Specification is approved for use within the US Army Armament Munitions and Chemical Command and is available for use by all Deparments and Agencies of the Department of Defense.".

PAGE 2

3.5, line 3: Delete "25" and substitute "45".

3.6, line 7: Delete "16,000" and substitute "17,000".

PAGE 3

3.10, line 3: Delete "1.262" and substitute "1.565".

PAGE 10

4.4.6: Delete in its entirety and substitute the following:

"4.4.6 Function and casualty. The test shall be conducted in accordance with Appendix F. The cartridges shall be fired single action and double action at the temperatures indicated below:

Temperature F	-40° to -45°	Ambeint	125° to 130°
Single Action	408	408	408
Double Action	408	408	408

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

The test quantities shall be distributed equally among the prescribed test weapons. The Government Contracting Officer shall designate the weapons in which the Function and Casualty test shall be performed dependent upon New Weapons Availability and Weapon Inventory Supplies. The weapons shall be selected from the following:

Colt, Revolver, Caliber .38 Special, 4 Inch Barrel
Smith & Wesson, Revolver, Caliber .38 Special, 4 Inch Barrel
Ruger, Revolver, Caliber .38 Special, Security Six, 4 Inch Barrel.".

PAGE 11

4.4.11: Delete in its entirety and substitute the following:

"4.4.11 The primer sensitivity test shall be conducted on empty primed cases in accordance with TECP 700-700, Vol. III. The primed cases may be obtained by either of the following methods provided one method is consistent throughout the entire sample.

a. Primed cases shall be obtained by disassembly of complete cartridges which have been randomly selected from the loaded cartridge lot. This disassembly shall be accomplished in such a manner as to cause the least possible distortions of the cartridge case.

b. Primed cases selected prior to loading may be employed providing it can be assured that these units are representative samples of the loaded cartridge lot.".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AB78)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.