MIL-D-46406B (PA)
31 March 1975
SUPERSEDING
MIL-D-46406A (MU)
20 February 1964
MIL-D-46911A (MU)
20 February 1964
(See 6.6)

MILITARY SPECIFICATION

DETONATOR, FLASH, M17
PARTS FOR AND LOADING, ASSEMBLING AND PACKING

*This specification is approved for use by all Departments and Agencies of the Department of Defense.

*1. SCOPE

1.1 This specification covers the parts for, loading, assembling and packing for one type of detonator designated as Detonator, Flash, M17.

*2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For
MIL-P-14100 - Primer Stab, M55, Loading, Assembling and Packing

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

s/s
unless

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

PRODUCT AND PACKING DRAWINGS

8797749 - Detonator, M17
9258182 - Box, Set-Up, Packing, Ammunition, Inner for Small Explosive Components
9258183 - Box, Set-Up, Packing, Ammunition, Outer for Small Explosive Components
9258184 - Box, Packing, Ammunition for Small Explosive Components.

INSPECTION EQUIPMENT DRAWINGS

8816367 - Firing Pin Guide
8827934 - Adapter, Ball, Primer Sensitivity Testing Fixture
8855292 - Fixture, Functioning Test
8816368 - Disc
9200602 - Bushing
8867811 - Holder, Primer
9200012 - Pin, Firing

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other publications. - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM Designation E300 - Industrial Chemicals, Recommended Practice for Sampling

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Penn. 19103).

3. REQUIREMENTS

2122

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Detonator. - The detonator shall comply with all requirements specified on Drawing (dwg.) 8797749 and with all requirements specified in applicable specifications.

3.3 Moisture content of lead azide. - The moisture content of the lead azide used in loading the detonator shall not exceed 0.50 percent.

3.4 Functioning. - The detonator shall function on the first attempt and shall cause perforation of the lead disc to a diameter of not less than 3/16 inch.

3.5 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.6 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. - The following types of inspection shall be conducted on this item.

a. First article inspection
b. Quality conformance inspection

*4.3 First article inspection

2133

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

4.3.1 Submission. - The contractor shall submit a first article sample (see 6.1b) as designated by the contracting officer. The first article sample shall consist of fifty (50) complete sets of parts and sub-assemblies (i.e., fifty (50) each of every component and sub-assembly.) The first article sample shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3.

4.3.2 Inspections to be performed. - See MIL-A-48078, paras 4.4.2.1 thru 4.4.2.9 and testing per para. 4.4.3.

4.3.3 Rejection. - See MIL-A-48078.

*4.4 Quality conformance inspection

*4.4.1 Inspection lot formation . - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of detonators shall contain:

a. Parts of one lot interfix from one manufacturer.
b. Lead azide of the same type from not more than two (2) lots produced by the same manufacturer in accordance with the same specification and same specification revision and which have subsequently been subjected to uniformely controlled drying and operating conditions at the loading plant.
c. Tetryl from not more than one lot.

4.4.2 Examination. - (See MIL-A-48078). - Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-D-46406B (PA)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.1	Disc, Detonator				9295137
					NEXT HIGHER ASSEMBLY 8797749
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Diameter		0.40%	3.2	Gage
132.	Thickness		0.40%	3.2	Gage
Minor:					
201.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil - Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

2122

6

CLASSIFICATION OF DEFECTS & TESTS MIL-D-46406B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9295138
*4.4.2.2	Disc, Detonator, Closing				NEXT HIGHER ASSEMBLY 8797749
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Diameter		0.40%	3.2	Gage
132.	Thickness		0.40%	3.2	Gage
Minor:					
201.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil - Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

2122

CLASSIFICATION OF DEFECTS & TESTS MIL-D-46406B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.3	Cup, Detonator		9295136
			NEXT HIGHER ASSEMBLY 8797749

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Cup split or cracked		100%	3.2	Visual
Major B:					
131.	Diameter of flash hole, minimum (min)		0.40%	3.2	Gage
132.	Length		0.40%	3.2	Gage
133.	Thickness bottom, min.		0.40%	3.2	Gage
134.	Concentricity flash hole with outside diameter		0.40%	3.2	Gage
135.	Cup damaged		0.40%	3.2	Visual
Minor:					
201.	Inside diameter, min.		0.65%	3.2	Gage
202.	Outside diameter, maximum		0.65%	3.2	Gage
203.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

7

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

8

2122

CLASSIFICATION OF DEFECTS & TESTS MIL-D-46406B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Assembly, Prior to Loading				8797749
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Coating compound or black lacquer on exposed surface of disc		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil - Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Assembly				8797749
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Cup split or cracked		100%	3.2	Visual
Major B:					
131.	Disc loose, punctured, torn, or wrinkled to such a degree that contents are exposed		0.40%	3.2	Visual
132.	Color of lacquer incorrect on either end		0.40%	3.2	Visual
133.	Cup damaged other than critical above		0.40%	3.2	Visual
134.	Crimp not full 360 degrees		0.40%	3.2	Visual
Minor:					
201.	Length		0.65%	3.2	Gage
202.	Diameter		0.65%	3.2	Gage
203.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

9

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

2122

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.6	Box, Setup, Inner, After Loading and Prior to Closing Slide Cover				9258182
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Filler and cushion assembly missing		100%	3.2	Visual
2.	Filler and cushion assembly improperly assembled		100%	3.2	Visual
3.	Stiffener missing		100%	3.2	Visual
4.	Slide cover assembly reversed		100%	3.2	Visual
Major B:					
131.	Release paper missing		0.40%	3.2	Visual
Minor;					
201.	Marking missing, incomplete or illegible		0.65%	3.2	Visual
202.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.7	Box, Set-up, Outer, with Inner Set-up Boxes Assembled and Prior to Assembling to and Sealing Strip				9258183
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Red surfaces on inner set-up boxes do not alternate on same side of outer set-up box		100%	3.2	Visual
2.	Stiffener not facing one direction		100%	3.2	Visual
Major A&B:	None defined				
Minor:					
201.	Marking missing, incomplete or illegible		0.65%	3.2	Visual
202.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

1:1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

2127

12

CLASSIFICATION OF DEFECTS & TESTS MIL-D-46406B (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.8	Sealed Packed Barrier Bag, Prior to Packing in Box				9258183
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Waterproofness of barrier bag destroyed by rupture, puncture or separation of heat seal		0.40%	3.2	Visual
102	Evidence of crushed box		0.40%	3.2	Visual
NOTE:	Package should be opened if there is evidence of crushing				
Minor					
201	Heat seal of barrier bag located so that one or more subsequent seals cannot be applied		0.65%	3.2	Visual
202	Marking of bag misleading or unidentifiable		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

8122

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-46406B (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.9	Box, Packing, Ammunition, Prior to Assembling Cover and Strapping		9258184
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Bags containing set-up boxes damaged		0.40%	3.2	Visual
132.	Cushioning material incomplete or missing from around outer set-up boxes		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:
13

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

MIL-D-46406B (PA)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.19	Box, Packing, Ammunition				9258184
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Strapping missing, broken, loose, or improperly fastened		0.40%	3.2	Visual/Manual
132.	Box damaged		0.40%	3.2	Visual
133.	Marking missing, incomplete or illegible		0.40%	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

4.4.3 TESTING (See Note)

NOTE: Chemical sampling. - A representative sample shall be randomly selected for the chemical tests specified in 4.5 The procedure described in ASTM E300 should be used to withdraw the samples. The checmical tests in 4.5 shall be performed using prescribed analytical procedure for replicate determinations given in standard analytical textbooks.

4.4.3.1 Binder-lubricant content of tetryl (see dwg. 8797749).- Major A defect - The binder-lubricant content of the tetryl shall be determined for each lot at the time of loading. A sample of 5 grams shall be selected and tested as specified in 4.5.1. If the binder-lubricant content is in excess of the percentage specified, and if loading has not begun, the lot of tetryl shall be rejected until proper corrective action has been accomplished as verified by repeating the binder-lubricant content test specified in 4.5.1. If loading has begun, action on the unloaded tetryl shall be as specified above and all detonators loaded with the questionable tetryl shall be rejected.

4.4.3.2 Moisture content of lead azide (see 3.3). - Major A defect. The moisture content of the lead azide shall be determined at the time of loading. A sample of 2 grams shall be selected and tested as specified in 4.5.2. If the moisture content is in excess of the percentage specified, and if loading has not begun, the lot of lead azide shall be rejected until proper corrective action has been accomplished as verified by repeating the moisture content test specified in 4.5.2. If loading has begun, action on the loaded lead azide shall be as specified above and all detonators loaded with the questionable lead azide shall be rejected.

*4.4.3.3 Functioning (see 3.4). - Major A defect. The sample size, acceptance, or rejection of the lot, shall be in accordance with Table 1. The test shall be performed as specified in 4.5.3, using equipment in accordance with 4.4.4. If more than one loading machine is used in the production of the inspection lot, the sample shall be selected so as to represent proportional quantities of production from each machine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

TABLE I

Lot Size	Sample		Accept	Rejection
To 150,000	First	315	0	3
	Second	315	3	4
150,001 to 300,000	First	500	1	4
	Second	500	4	5
300,001 to 500,000	First	800	2	5
	Second	800	6	7
500,001 and over	First	1250	3	7
	Second	1250	8	9

*4.4.3.4 Heat seal test of sealed bag (see dwg. 9258183). - Major A defect. Sampling, acceptance criteria, and test procedures for this test shall be as specified in MIL-P-116.

4.4.4 Inspection equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and section 6.2 herein.

4.5 Test methods and procedures

4.5.1 Binder-lubricant content of tetry. - An accurately weighed portion of 5 grams shall be transferred to a tared medium porosity sintered glass filtering crucible. The sample shall be extracted with four 10 milliliter (ml) portions of acetone maintaining each portion in contact with the residue for approximately 5 minutes before applying suction. Any lumps which may persist shall be broken up and the sides of the crucible washed down with each 10 ml. portion of acetone to insure complete removal of the tetryl. The residue shall be aspirated until the odor of acetone is no longer detectable. The crucible and contents shall be placed in a drying oven at 95 degrees Centigrade (°C) plus or minus 5 degrees C. for 1/2 hour, cooled in a desiccator and weighed. The above extraction shall be repeated, drying and weighing with individual 10 ml. portions of acetone until the loss in weight on subsequent extractions totals less than 0.005 gram. The weight of the residue in the crucible shall be calculated as the percentage of total binder-lubricant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:22
Check the source to verify that this is the current version before use.

4.5.2 Moisture content of lead azide. - A tared dried aluminum dish 2 inches in diameter shall be covered with a sheet of polytetrafluoroethylene 2 1/2 inches square and sufficiently flat to form a tight cover. An accurately weighed portion of approximately two grams of the sample shall be transferred to the moisture dish and the dish and contents, shall be transferred to an oven and dried at 95 degrees C. plus or minus 2 degrees C. for 2 hours. The cover shall be placed in a sulfuric acid desiccator during the drying period. After drying, the dish shall be quickly transferred to the desiccator and allowed to cool to room temperature. The polytetrafluoroethylene cover shall be placed on the dish and the assembly weighed. The loss in weight shall be calculated to percentage of moisture in the lead azide to determine compliance with 3.3 as follows:

Percentage of moisture = A minus B x 100 Divided by A

where:
A = the weight of the sample before drying.
B = the weight of the sample after drying.

*4.5.3 Functioning. - The detonator shall be assembled to the test fixture so that the output end of the M55 primer (see MIL-D-14100) is facing the sensitive end of the detonator. A steel ball 1 3/16 inches in diameter and weighing 3.95 ounces, maximum, shall be dropped on the firing pin to function the M55 Primer (which has been inserted in primer holder dwg. 8867811) from a height of 8 inches maximum. The height of drop shall be measured as height from the top of the firing pin to the bottom of the ball. A detonator that fails to fire, or fails to create a hole in the lead disc of the required size shall be classed defective. Method of inspection shall be in accordance with dwgs. 8816367, 8827934, 8855292, 8816368, 8855295, 8855298, 8867811 and 9200012.

*4.5.4 Heat seal of sealed bag. - The adequacy of the seal on the bag shall be determined in accordance with MIL-P-116.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

*5.1.1 Level C. - Preservation and packaging shall be as specified on dwgs. 9258182 and 9258183.

*5.1.2 Level C. - The detonator parts shall be packaged in accordance with MIL-STD-1169 requirements.

3122

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

5.2 Packing

*5.2.1 Level C . - Packing shall be as specified on dwg. 9258184.

*5.2.2 Level C. - The detonator parts shall be packaged in accordance with MIL-STD-1169 requirements.

*5.3 Marking. - Detonator containers and bags shall be marked in accordance with instructions contained in dwgs. 9258182, 9258183, and 9258184. Detonator parts containers shall be marked in accordance with MIL-STD-1169 requirements.

6. NOTES

6.1 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Provisions for submission of first article samples.
c. Provisions of MIL-A-48078.

6.2 Submission of inspection equipment designs for approval. - (See MIL-A-48078). Submit equipment designs as required to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T Dover, New Jersey 07801.

6.3 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M Dover, New Jersey 07801.

6.4 Check test for possible deterioration. - The following test is designed to prevent detonators that have deteriorated from being assembled into major ammunition items. The test shall be performed on detonators from each lot which have been stored under normal conditions for more than two years or under adverse conditions for any period of time. If the specification for the ammunition item into which the detonators are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract a provision for the performance of the check test. The Contracting Officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration. Detonator assemblies shall be selected from each lot for this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

6.4.1 Functioning. - A random sample of 315 detonators shall be selected from each lot. If 4 or more detonators fail to comply with the requirement specified, the lot shall be rejected. If more than 1 defective is found, a second sample of 315 shall be selected at random and tested. If, in the combined first and second sample, a total of 5 or more defectives are found the lot shall be rejected. The test shall be performed as specified in 4.5.3 using test equipment as specified in 4.4.4.

6.5 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.6 Supersession Data. - This specification includes the requirements of MIL-D-46911A (MU) dated 20 February 1964.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-121

2122

93f.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

5 5 18

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 72 WHICH MAY BE USED

Source: https://assist.dla.mil - Downloaded: 2026-10-22 05:32
Check the source to verify that this is the current version before use.

2122

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

2122

5.9 oz

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.