MIL–D–46432B(MU)
20 FEBRUARY 1964
SUPERSEDING
MIL–D–46432A (MU)
12 JUNE 1963

MILITARY SPECIFICATION

DETONATOR, STAB, M18

LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of stab detonator designated as Detonator, M18.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL–A–2550 —Ammunition and Special Weapons, General Specification for.

MIL–I–45208 —Inspection Requirements, General Specification for.

MIL–I–45607 —Inspection Equipment, Supply and Maintenance of.

STANDARDS

MILITARY

MIL–STD–105D—Sampling Procedures and Tables for Inspection by Attributes.

MIL–STD–109 —Quality Assurance Terms and Definitions.

MIL–STD–1235 —Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

ORDNANCE CORPS

7548099—Box, Packing, Ammunition for Detonators.

7548103—Box, Set-up, Packing, Ammunition, Outer for Boosters, Detonators, or Primers, Assembly, Details, Packing and Marking.

7548104—Box, Set-up, Packing, Ammunition, Inner, for Boosters, Detonators and Primers, Assembly, Details, Packing and Marking.

9254677—Detonator, M18, Loading Assembly.

PUBLICATIONS

ORDNANCE CORPS

IEL—9254677—Index of Inspection Equipment Lists.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:56Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Detonator. The detonator shall comply with all requirements specified on Drawing (dwg.) 9254677, and with all requirements specified in applicable specifications.

3.3 Moisture content of lead azide. The moisture content of the lead azide used in loading the detonator shall not exceed 0.50 percent when tested as specified in 4.3.2.

3.4 Moisture content of primer mixture. The moisture content of the primer mixture used in loading the detonator shall not exceed 0.30 percent when tested as specified in 4.3.3.

3.5 Functioning.

3.5.1 *Sensitivity.* The detonator shall function on the first attempt and shall cause perforation of the lead disc to a diameter of not less than $\frac{5}{16}$ inch when tested as specified in 4.3.5.1.

3.5.2 *Waterproofness.* The detonator shall comply with the requirements of 3.5.1 after being submerged in water to a minimum depth of 2 inches for not less than 48 hours, at a temperature of 70 degrees F. plus or minus 10 degrees, when tested as specified in 4.3.5.2.

3.6 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. All packing components shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 *Contractor quality assurance system.* The contractor shall provide and maintain an effective quality assurance system in compliance with the requirements of Specification MIL-I-45208. The contractor's quality assurance system shall contain a procedure for the reporting of critical defectives found during the course of his inspection and during inspection by the Government. Any critical defect encountered, unless annotated by an asterisk (*) to the right of the characteristic code number (see 6.2), will be reported within 48 hours. A monthly summary report covering those critical defects annotated by an asterisk will be furnished. The agencies to whom the reports will be furnished are identified in paragraph 6.4. The reports shall contain, as a minimum, the following information:

(a) Contractor and contract number.
(b) Number and revision date of specification.
(c) Characteristic code number.
(d) Lot or serial number.
(e) Number of defectives found.
(f) Assignable cause or analysis of occurrence.
(g) Corrective action taken or recommended.

When the corrective action is beyond the control of the contractor or the scope of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:56Z
Check the source to verify that this is the current version before use.

contract, the report shall contain the contractor's recommendation to the Government.

4.1.2 *Submission of product.* At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

(a) A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.

(b) Number of units of product inspected.

(c) Results obtained for all inspection performed.

(d) Drawing, specification number and date, together with an identification and date of changes.

(e) Certificates of compliance on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.

(f) Number of items in the lot.

(g) Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted will be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 *Government verification.* Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector will verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL–I–45208 and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions.

4.2.1 *Lot formation.* A lot shall consist of detonators produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification, and process changes not affecting safety, performance, or fit, as determined by the Government, shall not necessitate changing the lot interfix number. Lots shall be submitted for inspections in accordance with Standard MIL–STD–105D (or Standard MIL–STD–1235 when applicable). Each lot shall contain:

(a) Parts bearing the same lot interfix number from one manufacturer.

(b) Lead azide from not more than one lot.

(c) Tetryl from not more than one lot.

(d) Primer mixture from one batch or blending of batches which results in homogeniety of all primer mixture used in loading the entire detonator lot.

4.2.2 *Examination.* Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL–STD–105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Standard MIL–STD–1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics list-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:56Z
Check the source to verify that this is the current version before use.

ed using an AQL of 0.25 percent for each major defect and an AQL of 0.40 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 *Assembly, prior to loading* (see dwg. 9254677).

Categories	Defects	Method of inspection	Code No. (see 6.2)
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Coating compound or lacquer on exposed surface of disc	Visual	01001
Minor:	AQL 0.25 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	01002

4.2.2.2 *Assembly* (see dwg. 9254677).

Categories	Defects	Method of inspection	Code No.
Critical:			
1.	Cup cracked or split	Visual	02001*
Major:	AQL 0.40 percent		
101.	Disc loose, punctured, torn or wrinkled to such a degree that the contents are exposed	Visual	02002
102.	Color of lacquer incorrect on either end	Visual	02003
103.	Cup damaged except as described in Critical above	Visual	02004
104.	Crimp not full 360 degrees	Visual	02005
Minor:	AQL 1.50 percent		
201.	Length	Gage	02006
202.	Diameter	Gage	02007
203.	Evidence of poor workmanship (see 3.6)	Visual	02008

4.2.2.3 *Box, set-up, packing, ammunition, inner* (see dwg. 7548104).

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.25 percent		
101.	Box damaged exposing contents	Visual	03001
102.	Label missing or incorrect	Visual	03002
Minor: None defined.			

4.2.2.4 *Box, set-up, packing, ammunition, outer* (see dwg. 7548103).

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.25 percent		
101.	Barrier bag damaged	Visual	04001
102.	Label missing or incorrect	Visual	04002
Minor: None defined.			

4.2.2.5 *Box, packing, ammunition, for detonators* (see dwg. 7548099).

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Box damaged	Visual	05001
102.	Nailing inadequate	Visual	05002
103.	Strapping missing or loose	Visual	05003
104.	Marking incomplete, misleading or unidentifiable	Visual	05004
Minor: None defined.			

4.2.3 *Testing.*

4.2.3.1 *Binder-lubricant content of tetryl (see dwg. 9254677) Major defect—Code No. 06001.* The binder-lubricant content of the tetryl shall be determined for each lot at the time of loading. A sample, in sufficient quantity to perform the test detailed in 4.3.1, shall be selected and tested as specified in 4.3.1. If the binder-lubricant content is in excess of the percentage specified and if loading has not begun, the lot of tetryl shall be rejected. If loading has begun, action on the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:56Z
Check the source to verify that this is the current version before use.

unloading tetryl shall be as specified above and all detonators loaded with questionable tetryl shall be rejected.

4.2.3.2 *Moisture content of lead azide (see 3.3)—Major defect—Code No. 07001.* The moisture content of the lead azide shall be determined for each lot at the time of loading. A sample in sufficient quanity to perform the test detailed in 4.3.2 shall be selected and tested as specified in 4.3.2. If the moisture content is in excess of the percentage specified and loading has not begun, the lot of lead azide shall be rejected. If loading has begun, action on the unloaded lead azide shall be as specified above and all detonators loaded with questionable lead azide shall be rejected.

4.2.3.3 *Primer mixture.*

4.2.3.3.1 *Moisture content (see 3.4)—Major defect—Code No. 08001.* The moisture content of the primer mixture shall be determined for each batch or blend of batches at the time of loading. A sample, in sufficient quantity to perform the test detailed in 4.3.3 shall be selected and tested as specified in 4.3.3. If the moisture content is in excess of the percentage specified and if loading has not begun, the batch or blend of batches of the primer mixture shall be rejected. If loading has begun, action on the unloaded primer mixture shall be as specified above and all detonators loaded with the questionable primer mixture shall be rejected.

4.2.3.3.2 *Composition (see dwg. 9254677) Major defect—Code No. 09001.* The composition of the primer mixture shall be determined for each batch or blend of batches at the time of loading. A sample, in sufficient quantity to perform the test detailed in 4.3.4, shall be selected and tested as specified in 4.3.4. If the composition of the primer mixture fails to conform to the requirements specified on the applicable drawing and if loading has not begun, the batch or blend of batches of primer mixture shall be rejected. If loading has begun, detonators loaded with the questionable primer mixture shall be rejected.

4.2.3.4 *Functioning.*

4.2.3.4.1 *Sensitivity (see 3.5)—Major defect—Code No. 02009.* Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified the sampling plan for this test shall be in accordance with Standard MIL–STD–105D Single Sampling plan, code letter Q, and an AQL of 0.15 percent. The test shall be performed as specified in 4.3.2 using test equipment as specified in 4.2.4.

4.2.3.4.2 After three consecutive lots have met the criteria of 4.2.3.4.1, the sampling plan for this test shall be in accordance with Standard MIL–STD–105D, using the single sampling plan, code letter P and an AQL of 0.15 percent. The test shall be performed as specified in 4.3.2 using test equipment as specified in 4.2.4.

4.2.3.4.3 *Waterproofness (see 3.5)—Major defect—Code No. 02010.* Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified in the sampling plan for this test shall be in accordance with Standard MIL–STD–105D Single Sampling plan, code letter G and an AQL of 0.4 percent. The test shall be performed as specified in 4.3.2 using test equipment as specified in 4.2.4.

4.2.3.4.4 After three consecutive lots have met the criteria of 4.2.3.4.2, the sampling plan for this test shall be in accordance with Standard MIL–STD–105D, using the single sampling plan, code letter F and AQL of 0.65 percent. The test shall be performed as specified in 4.3.2 using test equipment as specified in 4.2.4.

4.2.4 *Inspection equipment.* Index of Inspection Equipment Number IEL–7153513 identifies the inspection equipment required to perform the examinations and tests prescribed in this section The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:56Z
Check the source to verify that this is the current version before use.

4.2.4.1 *Government rights to documentation.* Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 *Supply and maintenance.* Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL–I–45607.

4.2.4.3 *Government use of contractor's inspection and test equipment.* The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of it's accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.2.5 *Check test for deterioration* (not applicable to new production). The following test is intended to prevent the loading of major ammunition items with detonators that have deteriorated. This test shall be performed on detonators from each lot which has been stored under normal conditions for more than two years, or under adverse conditions for any period of time. If the specification for the ammunition item into which the detonators are loaded does not require performance of the check test, the contracting officer should insert a check test requirement in the contract.

4.2.5.1 *Functioning.* The sampling plan for this test shall be in accordance with Standard MIL–STD–105D using the single sampling plan, code letter P, and an AQL of 0.25 percent. The test shall be performed as specified in 4.3.5.

4.3 Test methods and procedures.

4.3.1 *Determination of binder-lubricant content of tetryl.* An accurately weighed portion of 5 grams shall be transferred to a tared medium porosity sintered glass crucible. The sample shall be extracted with four 10 milliliter (ml.) portions of acetone, maintaining each portion in contact with the residue for approximately 5 minutes before applying suction. Any lumps which may persist shall be broken up and the sides of the crucible washed down with each 10 ml. portion of acetone to insure complete removal of the tetryl. The residue shall be aspirated until the odor of acetone is no longer detectable. The crucible and contents shall be placed in a drying oven at 95 degrees Centigrade plus or minus 5 degrees C. for ½ hour, cooled in a desiccator and weighed. The above extraction shall be repeated, drying and weighing with individual 10 ml. portions of acetone until the loss in weight on subsequent extractions totals less than 0.005 gram. The weight of residue in the crucible shall be calculated as the percentage of total binder lubricant.

4.3.2 *Determination of moisture content of lead azide.* A tared dried aluminum dish 2 inches in diameter shall be covered with a sheet of polytetrofluoroethylene 2½ inches square and sufficiently flat to form a tight cover. An accurately weighed portion of approximately two grams of the sample shall be transferred to a moisture dish and the contents and the dish shall be transferred to an oven and dried at 95 degrees C. plus or minus 5 degrees C. for 2 hours. The cover shall be placed in a sulfuric acid desiccator during the drying period. After drying, the dish shall be quickly transferred to the desiccator and allowed to cool to room temperature. The polytetrafluoroethylene cover shall be placed on the dish and the assembly weighed. The loss in weight shall be calculated to percentage of moisture content in the lead azide to determine compliance with 3.3 as follows:

Percentage of moisture = A minus B times 100 divided by A.

where:

A = the weight of the sample before drying.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:56Z
Check the source to verify that this is the current version before use.

B=the weight of the sample after drying.

4.3.3 *Moisture content of primer mixture.* An accurately weighed 0.7 gram portion of the sample shall be dried to constant weight in an oven, maintained at 60 degrees C. plus or minus 5 degrees C., or in a desiccator, containing calcium chloride. The loss in weight shall be calculated as the percentage of moisture.

4.3.4 *Composition of primer mixture.*

4.3.4.1 *Potassium chlorate.* Approximately 1 gram of the primer mixture shall be accurately weighed and transferred to a tared ignited filtering crucible of approximately 15 ml. capacity. Three ml. of lead azide saturated distilled water shall be added at a temperature of 25 degrees C. plus or minus 2 degrees C., agitated for exactly 1 minute, and if necessary, any lumps shall be broken up with a glass rod. Suction shall be applied. This procedure shall be repeated five times making a total of six, 3 ml. extractions. The sample shall be rinsed in the filtering crucible with a few ml. of alcohol and then with a few ml. of ether, dried for approximately 15 minutes at 95 degrees C. plus or minus 5 degrees C; cooled in a desiccator, and weighed. The loss in weight shall be calculated as the percentage of potassium chlorate.

4.3.4.2 *Lead azide.* The residue remaining from the potassium chlorate determination shall be extracted with 5 ml. portions of saturated ammonium acetate solution at about 25 degrees C., (hot saturated ammonium acetate solution shall not be used as it dissolves antimony sulfide to some extent), each 5 ml. portion being agitated for about 30 seconds. Extractions shall be continued with 5 ml. portions until the washings no longer give a yellow precipitate with the addition of a few drops of potassium dichromate solution. The use of more then 60 ml. (12 washings) of ammonium acetate solution should be avoided. The residue shall be washed with distilled water, rinsed with a few ml. of alcohol and then with a few ml. of ether, dried for approximately 15 minutes at 95 degrees C. plus or minus 5 degrees C., cooled in a desiccator and weighed. The loss in weight shall be calculated as the percentage of lead azide.

4.3.4.3 *Antimony sulfide.* The residue remaining from the lead azide determination shall be extracted with concentrated hydrochloric acid until free from antimony sulfide. (This extracting can be made without removing the sample from the filtering crucible. Suction shall be applied and most of the antimony sulfide extracted with cool concentrated acid.) The crucible and residue shall be rinsed thoroughly, ignited to remove separate sulfur and organic matter, cooled in a desiccator and weighed. The loss in weight shall be calculated as the percentage of antimony sulfide.

4.3.4.4 *Carborundum.* The original weight of the ignited filtering crucible shall be subtracted from the weight of the crucible and residue after the antimony sulfide determination and the difference calculated as the percentage of carborundum.

4.3.5 *Functioning.*

4.3.5.1 *Sensitivity.* The detonator shall be assembled to the applicable test fixture specified in 4.2.4, so that the firing pin will strike the sensitive end of the detonator. A steel ball $1\frac{3}{16}$ inch in diameter and weighing 3.95 ounces maximum, shall be dropped on the firing pin, to function the detonator, from a height of 12 inches, maximum. The height of drop shall be measured as the height from the top of the firing pin to the bottom of the ball. A detonator that fails to fire or fails to create a hole in the lead disc of the required size shall be classed defective.

4.3.5.2 *Waterproofness.* The detonator shall be immersed under water as specified for the time specified. Within one hour after removal from the water the detonator shall be subjected to the sensitivity test specified in 4.3.5.1. Any detonator which fails to fire or fails to create a hole in the lead disc of the required size shall be classed defective.

5. PREPARATION FOR DELIVERY

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:56Z
Check the source to verify that this is the current version before use.

5.1 Preservation and packaging.

5.1.1 *Levels B (see 6.1) and C.* The detonators shall be preserved, packaged in accordance with dwgs. 7548103 and 7548104.

5.2 Packing.

5.2.1 *Level C.* The detonator shall be packed in accordance with dwg. 7548099.

5.3 Data cards. Data cards shall be prepared for each lot in accordance with the information specified in Specification MIL–A–2550.

6. NOTES

6.1 Ordering data. Procurement documents shall specify the following:

(a) Title, number and date of this specification.

6.2 Inspection code numbers. The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment. The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of 6.3.1 through 6.3.7.

6.3.1 *Inspection Equipment Lists.* Inspection Equipment Lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (00 Form 1242–3) the numbers of drawings of existing equipment designs or codes as indicated in 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "contractor design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 *Inspection Equipment List codes.* The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5, and 6.3.6 will be designated in the Inspection Equipment List by the following codes:

CDOF —Contractor's design responsibility on Ordnance format; ORDM–608–12.

CDCF —Contractor's design responsibility on contractor format.

OD —Ordnance design.

ODMU—Ordnance design, mandatory for use.

CE —Commercial equipment.

SCD —Specification Control Drawing.

6.3.3 *Ordnance designs.* Ordnance designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Ordnance design is listed for an item of inspection equipment. Ordnance designs fall into two basic classifications; mandatory and non-mandatory. When an Inspection Equipment List references mandatory Ordnance designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 *Specification control drawings.* Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagrammatic, or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared de-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:56Z
Check the source to verify that this is the current version before use.

signs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 *Commercial equipment.* Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and government. Contractors are not required to furnish drawings of commercial inspection equipment but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 *Contractor designs.* Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDOF shall comply with the format and requirements of ORDM 608–12, and, in addition, contain the detail and information specified above.

6.3.7 *Submission of contractor designs.* Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA–ND. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

6.4 **Submission of critical defect reports.** For U. S. Army Munitions Command procurement, one copy of each critical defect report will be furnished the cognizant Government inspection agency; the Army Ammunition Procurement and Supply Agency, ATTN: SMUAP–RO; Picatinny Arsenal, ATTN: SMUPA–ND.

6.4.1 *Reporting to other services.* For other than U. S. Army Munitions Command procurements, critical defect reporting shall be as prescribed by the Contracting Officer.

Custodian:
Army—MU

Preparing activity:
Army—MU

Project No. 1375–A700

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:56Z
Check the source to verify that this is the current version before use.