MILITARY SPECIFICATION

FIRING DEVICE, NON-METALLIC, RELEASE-TYPE T36E1 LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers parts, loading, assembling and packing for one type of firing device designated as Firing Device, Non-Metallic, Release-Type, T36E1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-2550 - General Specification for Ammunition Except Small Arms Ammunition.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109 - Inspection Terms and Definitions.
MIL-STD-350 - Jolt Test for Use in Production of Fuzes.
MIL-STD-351 - Jumble Test for Use in Production of Fuzes.

DRAWINGS

ORDNANCE CORPS

8825196 - Box, Packing, Ammunition, for Firing Device, MM, Pull Type, T35E1 or Release Type, T36E1.
8825197 - Carton, Packing, Ammunition, for Firing Device, MM, Pull Type, T35E1 or Release Type, T36E1.
8845205 - Firing Device, T36E1 and Base Coupling, T2E2, Assembly.

DSC 13575
Source: https://assist.dla.mil -- Downloaded: 2025-10-27T15:37:51
Check the source to verify that this is the current version before use.

PUBLICATIONS

ORDNANCE CORPS

ORD-M608-11 - Procedures and Tables for Continuous Sampling by Attributes.
IEL-(See 6.2) - Index of Inspection Equipment Lists.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Firing devices.-The firing devices shall comply with all requirements specified on Drawing (dwg.) 8845205, and with all requirements specified in applicable specifications.

3.3 Internal air pressure.-The firing device shall withstand, without any drop in pressure, an internal air pressure of two pounds per square inch gage (p.s.i.g.) for ten seconds, minimum (min.), when tested as specified in 4.4.1.

3.4 External air pressure.-The firing device shall withstand, without any drop in pressure, an external air pressure of two p.s.i.g. for 10 seconds, min., when tested as specified in 4.4.2.

3.5 Jolt and jumble.-The firing devices shall not function and shall be safe to handle when subjected to the jolt test specified in Standard MIL-STD-350 and the jumble test specified in Standard MIL-STD-351, when tested as specified in 4.4.3.

3.6 Functioning load.-The firing device shall function satisfactorily as evidenced by the complete functioning of the primer in the base coupling assembly when the cotter pin is removed and a load of 3.25 $\pm$ 0.25 pounds (lbs.) is applied to the pull cord when tested as specified in 4.4.4.

3.7 Workmanship.

3.7.1 Molded parts.-Molded parts shall be free of sinks, porosity, warpage, checks, cracks, chipped edges, blisters, scratches, burrs, excess flash, and other defects affecting serviceability.

3.7.2 Foreign matter.-All parts shall be free of chips, dirt, grease, rust, and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-The supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define the terms used herein. Inspection shall be performed in accordance with this specification and other specifications referenced in any of the contractual documents.

4.1.1 Contractor quality assurance system.-The contractor shall provide and maintain an effective quality assurance system acceptable to the Government covering the supplies procured under this specification and shall perform all inspections required by the system. A current written description of the system shall be submitted to the contracting officer, and meet his approval, prior to initiation of production. It shall include a description covering controls for lot formation and identification, inspections to be performed, inspection stations, sampling procedures, methods of inspection (gages, measuring, and testing equipment), and provisions for control and disposition of non-conforming material. The written description will be considered acceptable when, as a minimum, it provides the quality assurance required by the provisions of 4.3.2 and 4.3.3, and the other documents referenced herein. The contractor shall not be restricted to the inspection station nor the method of inspection listed in this specification provided that an equivalent control is included in the approved quality assurance procedure. In cases of dispute as to whether certain procedures of the contractor's system provide equal assurance, the comparable procedure of this specification shall apply. The contractor shall notify the Government of, and obtain approval for, any change to the written procedure that affects the degree of assurance required by this specification or other documents referenced herein.

4.1.2 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.
b. Number of units of product inspected.
c. Results obtained for all inspection performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of analyses on all material procured directly by the contractor.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

4.1.3 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings, and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification shall consist of: (a) surveillance of contractor operations to determine that the methods and procedures of the written procedure are being properly applied, and (b) Government product inspection. The Government inspector shall also ascertain prior to acceptance that the product complies with all the quality assurance provisions of other specifications referenced in any of the contractual documents.

4.1.3.1 Surveillance.-Surveillance shall include, but is not limited to:

a. Observation of procedures concerning lot formation and identification.

b. Observation of sampling procedures and application of acceptance criteria.

c. Determination that all required examinations and tests are performed in accordance with the prescribed procedures of this specification, or approved equivalents thereto.

d. Review of procedures for control and disposition of non-conforming material.

4.1.3.2 Product inspection.-Physical inspection by the Government of contractor-accepted product will be performed to the extent necessary to assure contractor compliance with the requirements of this specification and to determine the reliability of contractor records. Severity of Government inspection of individual characteristics will be directly related to the seriousness classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records. (See Specification MIL-G-2550).

4.1.3.3 Deviations and deficiencies.-Deviations from the prescribed or agreed-upon procedures, or instances of poor practice which might have an effect on the quality of the product, shall be called to the attention of the contractor immediately. To avoid interference with operations, the contractor shall designate a responsible official, or officials, to whom the Government inspector will report such instances. Failure of the contractor to correct deficiencies promptly shall be cause for suspension of acceptance until correction has been made or until conformance to prescribed criteria has been demonstrated.

4.2 Preproduction inspection.

4.2.1 Process specification.-Prior to the start of the manufacture of the preproduction lot, the contractor shall submit to the procuring activity, for approval, a process specification which shall specify the time, temperature, and pressure ranges which shall be maintained during the production of molded parts. Periodically, during the operation of the approved process, the Government inspector shall observe the process to ascertain that the approved limits are being adhered to. No deviation from these limits without approval from the procuring activity shall be allowed. In the event of an approved deviation, the contractor shall submit a new preproduction lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

4.2.2 Submission.-Prior to the start of regular production, the contractor shall submit a preproduction lot consisting of twenty-five (25) plastic parts from each mold and fifty (50) firing device assemblies (less coupling base assemblies). The lot shall be consecutively produced and shall be produced by the production process which the contractor will use in fulfilling the contract. Submission shall be made to a Government-approved facility designated by the contracting officer. The preproduction quantity shall be submitted prior to initiation of production and whenever a change occurs in manufacturing process, material used, drawing, or specification, such as to significantly affect production uniformity as determined by the Government inspector.

4.2.3 Inspections to be performed.-Each part and firing device assembly shall be inspected for all requirements specified in 4.3.2 and 4.3.3 of this specification.

4.2.4 Rejection.-If any part or firing device assembly fails to comply with the applicable requirements, the preproduction quantity shall be rejected and the contractor shall take the necessary corrective action and submit a new preproduction quantity, or portion thereof, as specified by the contracting officer. The contractor shall continue to submit new or supplemental quantities, as necessary, until such time as a quantity successfully passes the inspection requirements specified, or until otherwise directed by the procuring activity.

4.3 Inspection provisions.

4.3.1 Lot formation.-A lot shall consist of loaded firing device assemblies produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance, or fit, as determined by the Government, shall not necessitate changing the lot number. Each lot shall contain:

a. Parts of one interfix lot number from one manufacturer.

b. Base coupling assemblies of one interfix lot number from one manufacturer

4.3.2 Examination.-Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL-STD-105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Handbook ORD-M608-11 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.25 percent for each major defect and an AQL of 0.40 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

4.3.2.1 Insert, firing pin (see dwg. 8831474 covering a detail of dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 0.40 percent	
101.	Total length	Gage
102.	Profile of point	Gage
103.	Diameter of point	Gage
104.	Finish improper	Visual
Minor:	AQL 0.40 percent	
201.	Major diameter	Gage

4.3.2.2 Body (see dwg. 8831472 covering a detail of dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 1.0 percent	
101.	Diameter of firing pin cavity (gasket groove end)	Gage
102.	Location of firing pin cavity	Gage
103.	Depth to angle behind coupling base thread	Gage
104.	Location of spring support surface	Gage
105.	Radius of spring support surface	Gage
106.	Minor diameter of thread	Gage
107.	Pitch diameter of thread	Gage
108.	Molding defects (see 3.7.1)	Visual
109.	Foreign matter on interior (see 3.7.2)	Visual
110.	Finish improper in firing pin cavity	Visual
Minor:	AQL 0.40 percent	
201.	Diameter of 7 holes	Gage

4.3.2.3 Cover (see dwg. 8831455 covering a detail of dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

Major:		AQL 0.65 percent
101.	Height of spring boss	Gage
102.	Outside diameter of latch cavity boss	Gage
103.	Location of latch cavity boss	Gage
104.	Height of four retaining ribs	Gage
105.	Inside diameter of latch cavity boss	Gage
106.	Molding defects (see 3.7.1)	Visual
107.	Foreign matter on interior (see 3.7.2)	Visual

Minor:		AQL 0.40 percent
201.	Height of seven locking lugs	Gage

4.3.2.4 Cap (see dwg. 8831465 covering a detail of dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 0.40 percent	
101.	Location of pin hole	Gage
102.	Diameter of pin hole	Gage
103.	Total length	Gage
104.	Depth to seal seat	Gage
Minor:	AQL 1.0 percent	
201.	Larger inside diameter, max	Gage
202.	Concentricity between inside diameters	Gage

4.3.2.5 Spring (see dwg. 8831469 covering a detail of dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 0.40 percent	
101.	Load test	Gage
102.	Total length	Gage
103.	Width	Gage
104.	Layers separating	Visual
Minor:	AQL 1.5 percent	
201.	Thickness	Gage
202.	Molding defects (see 3.7.1)	Visual
203.	Foreign matter (see 3.7.2)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

4.3.2.6 Latch (see dwg. 8831467 covering a detail of dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 0.65 percent	
101.	Distance between end and center of body seat pin	Gage
102.	Distance between center of body seat pin and face of firing pin seat	Gage
103.	Length of body seat pin	Gage
104.	Distance between flat side and face of body seat pin	Gage
105.	Trigger-contacting radius at end	Gage
106.	Chamfer missing	Visual
107.	Finish improper	Visual
Minor:	AQL 1.0 percent	
201.	Molding defects (see 3.7.1)	Visual
202.	Foreign matter (see 3.7.2)	Visual

4.3.2.7 Trigger (see dwg. 8831471 covering a detail of dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 1.0 percent	
101.	Location of two pin holes	Gage
102.	Length to larger diameter	Gage
103.	Total length	Gage
104.	Larger diameter	Gage
105.	Smaller diameter	Gage
106.	Location of boss	Gage
107.	Height of boss	Gage
108.	Location of latch slot	Gage
109.	Width of latch slot	Gage
110.	Length of latch slot	Gage
111.	Finish improper	Visual
Minor:	AQL 1.5 percent	
201.	Location of seal groove	Gage
202.	Molding defects (see 3.7.1)	Visual
203.	Foreign matter (see 3.7.2)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

4.3.2.8 Pin, firing (see dwg. 8831470 covering a detail of dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 0.25 percent	
101.	Diameter of insert cavity, max	Gage
102.	Depth of insert cavity	Gage
Minor:	None defined.	

4.3.2.9 Firing pin assembly (see dwg. 8845002 covering a detail of dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 1.5 percent	
101.	Concentricity of insert with pin	Gage
102.	Height of insert above pin face	Gage
103.	Diameter below fluted flange	Gage
104.	Distance between spring seat radius and face of pin	Gage
105.	Distance between spring seat and angle in pull pin cam	Gage
106.	Distance between fluted flange and face of pin	Gage
107.	Distance between latch cutout and face of pin	Gage
108.	Width of latch cutout	Gage
109.	Width of spring seat slot	Gage
110.	Insert loose or missing	Visual-Manual
111.	Chamfer missing	Visual
112.	Molding defects (see 3.7.1)	Visual
113.	Finish improper	Visual
Minor:	AQL 1.5 percent	
201.	Total length	Gage
202.	Radius of spring seat	Gage
203.	Foreign matter (see 3.7.2)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

4.3.2.10 Assembly (less pin and spring)(see dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 0.25 percent	
101.	Movement of firing pin improper (too loose, too tight, rough, etc.	Visual-Manual
102.	Movement of trigger improper (too loose, too tight, rough, etc.	Visual-Manual
Minor:	None defined.	

4.3.2.11 Assembly (less cover) (see dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 0.65 percent	
101.	Component missing.	Visual
102.	Latch, spring, or firing pin incorrectly positioned.	Visual
103.	Molding defects (see 3.7.1).	Visual
104.	Foreign matter on any part or interior surface (see 3.7.2).	Visual
105.	Spring cracked or layers separating.	Visual
106.	Sliding surfaces not coated with friction-reducer.	Visual
Minor:	None defined.	

4.3.2.12 Assembly, less cap over firing pin (see dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 0.40 percent	
101.	Firing pin cord missing or incorrectly assembled (interferes with rubber O-ring).	Visual
102.	Rubber O-ring missing or damaged.	Visual
103.	Safety clip missing or cracked.	Visual
Minor:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

4.3.2.13 Assembly (less coupling base) (see dwg. 8845205).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 0.40 percent	
101.	Firing pin assembly incorrectly positioned	Visual
102.	Firing pin insert missing or damaged	Visual
103.	Foreign matter in coupling base cavity or on firing pin assembly (see 3.7.2)	Visual
Minor:	None defined.	

4.3.2.14 Assembly (see dwg. 8845205).

Categories	Defects	Method of inspection
Critical:		
1.	Cap insecurely cemented	Manual
2.	Cotter pin missing or not spread	Visual
Major:	AQL 0.40 percent	
101.	Coupling base loose or not completely seated	Visual-Manual
102.	Cap over firing pin loose-fit, missing, or damaged (cracked, punctured, etc.)	Visual
103.	Coupling base damaged (cup cut, deep scratches, dented, deformed); thread damaged, etc	Visual
104.	Coupling base gasket missing	Visual
Minor:	AQL 2.5 percent	
201.	Cotter pin cord or pin cord missing or incorrectly tied	Visual
202.	Foreign matter (see 3.7.2)	Visual
203.	Marking misleading or unidentifiable	Visual
204.	Mounting hole missing	Visual
205.	Any part cracked or with deep cut	Visual
206.	Molding defects (see 3.7.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

4.3.2.15 Carton, packing, sealed (see dwg. 8825197).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 0.25 percent	
101.	Assembly damaged so that contents are exposed or liable to become exposed	Visual
102.	Sealing strip incomplete, badly wrinkled or not in contact with surface for at least 1/2 inch around entire carton	Visual
Minor:	AQL 1.0 percent	
201.	Contents move when carton is shaken	Manual
202.	Marking misleading or unidentifiable	Visual

4.3.2.16 Bag, barrier, sealed (prior to insertion into wooden box) (see dwg. 8825197).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 0.25 percent	
101.	Waterproofness destroyed by separation of heat seal, or rip, tear or puncture	Visual
Minor:	AQL 1.0 percent	
201.	Label missing or peeling	Visual
202.	Marking misleading or unidentifiable	Visual

4.3.2.17 Box, packing, sealed wooden (see dwg. 8825196).

Categories	Defects	Method of inspection
Critical:	None defined.	
Major:	AQL 0.65 percent	
101.	Hardware missing, broken or loose	Visual-Manual
102.	Strapping missing, broken or loose	Visual-Manual
103.	Contents exposed	Visual
104.	Board broken or split	Visual
105.	D.O.D. symbol misleading or unidentifiable (when applicable)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

Minor:	AQL 2.5 percent	
201.	Hardware improperly engaged	Visual-Manual
202.	Handle missing or insecure	Visual-Manual
203.	Contents loose (when box is tilted)	Manual
204.	Strapping improperly assembled	Visual
205.	Car seal missing, unsealed or improperly positioned	Visual
206.	Marking misleading or unidentifiable	Visual

4.3.3 Testing.

4.3.3.1 Internal air pressure and external air pressure (see 3.3 and 3.4, resp.) Major defect.-These tests shall be performed 100 percent. Assemblies failing to comply with the specified requirements shall be classed defective and be removed from the lot. The tests shall be performed as specified in 4.4.1 and 4.4.2, resp., using equipment in accordance with 4.3.4.

4.3.3.2 Jolt and jumble (see 3.5) Critical defect for any evidence of functioning, major defect for all others.-Twelve (12) firing devices, less coupling base assemblies, shall be selected from each lot for these tests. If one or more assemblies fail to comply with the specified requirements, the lot shall be rejected. The tests shall be performed as specified in 4.4.3 using equipment in accordance with 4.3.4.

4.3.3.3 Functioning load (see 3.6) Major defect.-The sampling plan for this test shall be in accordance with Standard MIL-STD-105 using code letter I and an AQL of 1.00 percent. Any assembly which fails to comply with the specified requirements shall be classed defective. The test shall be performed as specified in 4.4.4 using equipment in accordance with 4.3.4.

4.3.4 Inspection equipment.-For the performance of the examinations and tests specified in 4.3.2 and 4.3.3, the contractor shall have available, and utilize correctly, all necessary gages, measuring, and testing equipment. (see 6.2). When inspecting the contractor's inspection equipment, the Government inspector will determine that the contractor has available, and utilizes correctly, gages, measuring, and testing equipment of the required accuracy and precision and that the instruments are of the proper type and range to make measurements of the required accuracy. The contractor shall have available a set of master gages, standards, and appropriate instruments for regularly scheduled calibration of his inspection equipment. Records of such regularly scheduled calibration shall be maintained by the contractor and made available for review by the Government. The calibration of gages, standards, and instruments will be periodically checked by authorized Government personnel.

4.4 Test methods and procedures.

4.4.1 Internal air pressure.-The firing devices, less coupling base assemblies, shall be assembled to a specified fixture and subjected to an internal air pressure of 2 p.s.i.g. for not less than 10 seconds to determine compliance with 3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

4.4.2 External air pressure.-The firing devices, less coupling base assemblies, shall be assembled to a specified fixture and subjected to an external air pressure of 2 p.s.i.g. for not less than 10 seconds to determine compliance with 3.4.

4.4.3 Jolt and jumble.-The firing devices, less coupling base assemblies, shall be assembled to a specified adapter and subjected to the jolt test in accordance with Standard MIL-STD-350. The same firing devices, without inspection, shall then be subjected to the jumble test in accordance with Standard MIL-STD-351. The firing devices shall then be examined internally and externally to determine compliance with 3.5.

4.4.4 Functioning load.-The loaded firing device assemblies shall be assembled to a specified test fixture and subjected to this test to determine compliance with 3.6. The test shall be performed behind a suitable barricade to protect personnel during functioning of the primer in the coupling base assembly.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A.-Firing Device, T36E1, shall be packaged in accordance with dwg. 8825197, sheets 1 and 2.

5.1.2 Level C.-See 5.1.1 for requirements.

5.2 Packing.

5.2.1 Level A.-Firing Device, T36E1 shall be packed in accordance with dwg. 8825196.

5.2.2 Level C.-See 5.2.1 for requirements.

5.3 Marking.-Marking shall be in accordance with dwgs. 8825196 and 8825197, sheet 1.

5.4 Data cards.-Data card information shall be as specified in Specification MIL-G-2550.

6. NOTES

6.1 Ordering data.-Procurement documents should specify the title, number, and date of this specification.

6.2 Inspection equipment.-Inspection equipment designs were not available at the time this specification was prepared. Prior to procurement, the procuring agency should contact Picatinny Arsenal, Dover, New Jersey, ATTN: ORDBB-ND4, to determine availability of inspection equipment designs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.

Notice.-When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian:
Army-Ordnance Corps

Preparing activity:
Army-Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:52Z
Check the source to verify that this is the current version before use.