MIL-I-46434C (PA)
18 March 1975
SUPERSEDING
MIL-I-46434B (MU)
30 July 1968 and
MIL-I-46435B (MU)
30 July 1968
(see 6.7)

MILITARY SPECIFICATION

IGNITER, ELECTRIC, M59, PARTS FOR AND LOADING, ASSEMBLING AND PACKING

*This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

*1.1 This specification covers the parts for, loading assembling and packing for one type of igniter, designated as Igniter, Electric, M59.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

*MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables For Inspection by Attributes (ABC-STD-105)

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

MIL-STD-650 - Explosive: Sampling, Inspection and Testing
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1234 - Pyrotechnics: Sampling, Inspection and Testing

*(For meaning of asterisk see paragraph 6.6)

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

8831025 - Igniter, Electric, M59 Loading Assembly
8850245 - Box, Set-up, Packing, Ammunition for Igniter, Electric, M59
8850246 - Box, Packing, Ammunition for Igniter, Electric, M59
9234870 - Metal Parts Arrangement

(Copies of specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material. - Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Parts. - The parts shall comply with all requirements specified in Drawing (dwg.) 9234870 and with all requirements specified in applicable specifications.

3.3 Igniters. - The igniters shall comply with all requirements specified on Drawing (dwg.) 8831025, and with all requirements specified in applicable specifications.

3.4 Moisture content of ignition charge composition. - Prior to assembling the igniters, the moisture content of the ignition charge composition at the loading station at the time of loading the ignition element shall not exceed 0.10 percent when tested.

3.5 Electrical resistance. - The electrical resistance between the ignition element and the body shall be not less than 0.80 ohms nor more than 1.80 ohms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

3.6 Functioning. - The igniters shall function when energized with an electric current of 1.25 amperes maximum (max.)

3.7 Non-functioning. - The igniters shall not function when energized with an electric current of 190 to 200 milliamperes.

*3.8 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. Required packing shall be dry.

3.9 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

*4.2 Classification of inspections. - The following types of inspection shall be conducted on this item.

a. First article inspection
b. Quality conformance inspection

4.3 First article inspection

*4.3.1 Submission. - The contractor shall submit a first article sample (see 6.1b) as designated by the Contracting Officer. The first article sample shall consist of twenty-five (25) complete sets of parts and sub-assemblies (i.e., twenty-five (25) each of every component and subassembly). The first article sample shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3

*4.3.2 Inspections to be performed. - See MIL-A-48078, paragraphs 4.4.2, testing paragraphs 4.4.3 and Table I specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

TABLE I

FIRST ARTICLE INSPECTION

MIL-I-46434C (PA)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*	Metal Parts Arrangement (Igniter, Electric M59)				SEE BELOW
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Metal Parts Dwg. 9234870 Examination for Defects	25(a)		3.2	4.4.2.1 & 4.4.2.2
NOTES:	(a) 25 Each and every component				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

*4.3.3 Rejection. - (See MIL-A-48078)

4.4 Quality conformance inspection

*4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of igniters shall contain:

a. Element, ignition electric M18 metal parts from not more than one lot interfix number from one supplier.

b. Igniter, electric, M59 metal parts from not more than one lot interfix number from one supplier.

c. Ignition composition produced by one supplier under one continuous set of operating conditions and which consists of one or more batches that have been subjected to the same unit chemical or physical mixing process intended to make the final product homogeneous.

4.4.2 Examination. - (See MIL-A-48078). - Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION MIL-I-46434C (PA)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.1	Plug, Closing	1 OF 1	8831028
			NEXT HIGHER ASSEMBLY 9234870

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Pitch diameter of thread		0.40%	3.2	Gage
132.	Hole obstructed or missing		0.40%	3.2	Visual
133.	Length of thread, min		0.40%	3.2	Gage
Minor:					
201.	Major diameter of thread,min		0.65%	3.2	Gage
202.	Diameter of hole, min.		0.65%	3.2	Gage
203.	Diameter of countersink		0.65%	3.2	Gage
204.	Total length, max.		0.65%	3.2	Gage
205.	Slot missing		0.65%	3.2	Visual
206.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-46434C (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.2	Body		8831027
			NEXT HIGHER ASSEMBLY 9234870

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Pitch diameter of external thread		0.40%	3.2	Gage
132.	Pitch diameter of internal thread		0.40%	3.2	Gage
133.	Major diameter of external thread, min.		0.40%	3.2	Gage
134.	Minor diameter of internal thread, max.		0.40%	3.2	Gage
Minor:					
201.	Concentricity of ignition element cavity with ignition element hole		0.65%	3.2	Gage
202.	Length of external thread undercut, max.		0.65%	3.2	Gage
203.	Length of thread pilot, max.		0.65%	3.2	Gage
204.	Length of internal threads, min		0.65%	3.2	Gage
205.	Diameter of ignition element cavity		0.65%	3.2	Gage
206.	Diameter of ignition element hole		0.65%	3.2	Gage
207.	Location of wrench holes		0.65%	3.2	Gage
208.	Diameter of flange		0.65%	3.2	Gage
209.	Total length		0.65%	3.2	Gage
210.	Depth of ignition element hole		0.65%	3.2	Gage
211.	Thickness of flange		0.65%	3.2	Gage
212.	Diameter of wrench holes, min.		0.65%	3.2	Gage
213.	Depth of wrench holes		0.65%	3.2	Gage
214.	Diameter of thread pilot		0.65%	3.2	Gage
215.	Evidence of poor workmanship including absence of chamfer or radius		0.65%	3.8	Visual

NOTES:

1/

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

8

CLASSIFICATION OF DEFECTS & TESTS MIL-I-46434C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.3	Ignition Element Assembly				8831026
					NEXT HIGHER ASSEMBLY 8831025
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:					
1.	Ignition charge above metal surface		100%	3.3	Gage
2.	Ignition charge on exterior surface		100%	3.3	Visual
Major A:					
101.	Ignition charge missing or insufficient		0.40%	3.3	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

MIL-I-46434C (PA)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.4	Assembly, Prior to Inserting Closing Plug				8831025
					NEXT HIGHER ASSEMBLY 8831025
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A: 101.	Closing disc missing or damaged to extent that explosive is exposed		0.40%	3.3	Visual
Major B: 131.	More than one closing disc present		0.40%	3.3	Visual
Minor: 201.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

6

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

10

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-46434C (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.5	Assembly		8831025
			NEXT HIGHER ASSEMBLY 8831025

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Depth to electrode		0.40%	3.3	Gage
132.	Flash hole obstructed		0.40%	3.3	Visual
133.	Closing plug missing		0.40%	3.3	Visual
Minor:					
201.	Closing plug loose to finger pressure		0.65%	3.3	Manual
202.	Total length, max.		0.65%	3.3	Gage
203.	Threads damaged		0.65%	3.3	Visual
204.	Marking misleading or unidentifiable		0.65%	3.3	Visual
205.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-46434C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.6	Box, Set-up, Prior to Sealing				8850245
					NEXT HIGHER ASSEMBLY 8850245
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Incorrect number of igniters		0.40%	3.3	Visual
132.	Igniter inverted		0.40%	3.3	Visual
133.	Packing component missing		0.40%	3.3	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

11

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.7	Box, Set-up, Sealed		8850245
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Contents loose		0.40%	3.3	Manual
132.	Box damaged		0.40%	3.3	Visual
133.	Sealing strip incomplete or badly wrinkled		0.40%	3.3	Visual
Minor;					
201.	Marking missing, misleading or unidentifiable		0.65%	3.3	Visual
202.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.8	Sealed Barrier Bag				8850245
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major A:					
101.	Waterproofness of barrier bag destroyed by rupture, puncture, or separation of heat seal		0.40%	3.3	Visual
102.	Evidence of crushed box		0.40%	3.3	Visual
	NOTE: Package should be opened if there is evidence of crushing				
Minor:					
201.	Heat seal of barrier bag located so that one or more subsequent seals cannot be applied		0.65%	3.3	Visual
202.	Marking of bag misleading or unidentifiable		0.65%	3.3	Visual
203.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

13

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

14

CLASSIFICATION OF DEFECTS & TESTS

MIL-I-46434C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.9	Wood Packing Box Prior to Sealing				8850246
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Incorrect number of cartons		0.40%	3.3	Visual
132.	Any packing component missing		0.40%	3.3	Visual
Minor:					
201.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-I-46434C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8850246
*4.4.2.10	Wood Packing Box, Sealed				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major B:					
131.	Box damaged to the extent that the contents are exposed or likely to become exposed in subsequent handling		0.40%	3.3	Visual
132.	Hardware or strapping, broken or loose		0.40%	3.3	Visual
Minor:					
201.	Hardware or strapping incorrectly assembled		0.65%	3.3	Visual
202.	Contents loose		0.65%	3.3	Manual
203.	Marking misleading or unidentifiable		0.65%	3.3	Visual
204.	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Moisture content of ignition charge composition. - (See 3.4) Major A defect. - The contractor shall provide adequate controls to insure compliance with the requirements, and shall test for verification of at least one sample of composition from each eight (8) hours production of igniter primers. Composite samples shall not be used. If the moisture content of the sample exceeds the requirement, and loading has not begun, that quantity of material represented by the sample shall be rejected. If assemblies have been loaded with material containing excessive moisture, the remaining material that is represented by the sample together with all assemblies loaded with the non-conforming material shall be rejected. The test shall be performed as specified in 4.5.1.

*4.4.3.2 Electrical resistance (See 3.5) - Major A defect - This test shall be conducted 100 percent. Any igniter which fails to comply with the applicable requirement shall be classed defective and removed from the lot. The test shall be performed as specified in 4.5.2.

4.4.3.3 Functioning. (See 3.6) - Major A defect

*4.4.3.3.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, five hundred (500) samples shall be randomly selected from each lot and shall be subjected to the test specified in 4.5.3 with equipment in accordance with 4.4.4. If four (4) or more failures occur, the lot shall be rejected. (Destructive test)

*4.4.3.3.2 After three consecutive lots have met the criteria of 4.4.3.3.1, a double sampling plan in accordance with Code Letter L and an AQL of 0.25 percent shall be used for each lot. The test shall be performed as specified in 4.5.3 using equipment in accordance with 4.4.4.

4.4.3.4 Non-functioning (See 3.7) - Critical defect

*4.4.3.4.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, two hundred (200) samples shall be randomly selected from each lot and shall be subjected to the test specified in 4.5.4 with equipment in accordance with 4.4.4. If any igniter functions, the lot shall be rejected. Igniters subjected to this test shall not be returned to the lot. (Destructive test)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

*4.4.3.4.2 After three consecutive lots have complied with the criteria of 4.4.3.4.1 eighty (80) igniter assemblies shall be selected from each lot for this test. If any igniter functions the lot shall be rejected. Assemblies subjected to this test shall not be returned to the lot. (Destructive test)

*4.4.3.5 Determination of ignition charge composition (See dwg. 8831026) - Major A defect. - Approximately five (5) grams of ignition charge composition shall be selected from that quantity of composition used in loading a complete lot of electric igniters. The analysis shall be performed as specified in 4.5.5. The composition lot shall be rejected if it fails to comply with the requirements.

*4.4.3.6 Heat seal test of sealed bag. (See dwg. 8850245) - Major A defect. - Sampling, acceptance criteria, and test procedures for this test shall be as specified in MIL-P-116.

4.5 Test methods and procedures

4.5.1 Determination of moisture content of ignition charge composition. - The moisture content of the ignition charge shall be determined as specified in Method 101.5 of MIL-STD-1234 except that a five (5) gram sample shall be used.

4.5.2 Electrical resistance. - The igniters shall be tested for electrical resistance by applying an electrical current of 20 milliamperes, max., using the electrode as one contact point and the igniter body as the other. Observation shall be made for compliance with the applicable requirement.

4.5.3 Functioning. - The igniters shall be tested for electrical functioning by applying an electrical current of 1.25 amperes, max., using the electrode for one contact point and the igniter body as the other. The time of the current flow shall be one tenth second maximum. Observation shall be made for functioning.

4.5.4 Non-functioning. - The igniters shall be tested for electrical functioning by applying an electrical current of 190 to 200 milliamperes, using the electrode as one contact point and the igniter body as the other. The time of the current flow shall be one second minimum. Observation shall be made for non-functioning.

4.5.5 Determination of ignition charge composition mixture (see 6.5). - The chemical composition of the ignition charge shall be considered satisfactory if it is in accordance with the following:

Component	Percentage
Potassium Chlorate	44.5 plus or minus 2
Lead Thiocyanate	35.5 plus or minus 2
Charcoal	20.0 plus or minus 1.5
Lacquer Solids (added)	1.6 plus or minus 0.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

4.5.5.1 Lacquer solids. - Approximately 1.5 grams of the sample shall be transferred to a tared medium porosity filtering curcible and allowed to air dry for about an hour. The crucible and contents shall be placed in a vacuum oven for two hours maintained at a temperature of 55 plus or minus 2 degrees Centigrade. The crucible and contents shall be cooled in a desciccator and weighed. The procedure shall be repeated until the change in weight does not exceed 0.5 milligrams. The contents of the crucible shall be extracted with ten 25 milliliter (ml.) portion s of acetone saturated with potassium chlorate and lead thiocyanate. The crucible and contents shall be aspirated until the odor of acetone is no longer perceptible and then dried in a vacuum oven maintained at 55 plus or minus 2 degrees Centigrade for two hours. The crucible and contents shall be cooled in a desiccator and weighed. The percent lacquer solids shall be calculated as follows:

Percent lacquer solids = 100 (A-B) divided by B

where:
A = the weight of the sample dried in the oven.
B = the weight of dried sample after acetone extraction.

4.5.5.2 Charcoal. - Approximately 1.5 grams of the sample shall be transferred to a tared medium porosity filtering crucible. The contents of the crucible shall be extracted with ten 25 ml. portions of acetone saturated with potassium chlorate and lead thiocyanate. The crucible and contents shall be aspirated until the odor of acetone is no longer perceptible and then dired in a vacuum oven maintained at 55 plus or minus 2 degrees Centigrade for two hours. The crucible and contents shall be cooled in a desiccator and weighed. Using a Fisher high form filtrater or equivalent extractor the sample shall be extracted with ten 25 ml. portions of a 5 percent potassium nitrate solution followed with 50 ml. of distilled water. A glass rod shall be used to break up any lumps in the sample during the extraction process, the filtrate shall be reserved for the determination of lead thiocyanate. The crucible and contents shall be aspirated for several minutes then placed in an oven maintained at 100 plus or minus 5 degrees Centigrade for two hours. The crucible and contents shall be cooled in a desiccator and weighed. The percent charcoal shall be calculated as follows:

Percent charcoal = 100 A divided by B

where:
A = The weight of sample after acetone and 5 percent potassium nitrate solution extraction.
B = The weight of sample after acetone extraction.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

4.5.5.3 Lead thiocyanate. - Exactly 35 ml. of stanardized 0.1 normal (N) silver nitrate shall be added to the filtrate reserved from the charcoal determination. The flask and contents shall be swirled and 100 ml. of 3N nitric acid (nitric acid used should be water-white and free of oxides of nitrogen) shall be added. The swirling of the mixture shall be continued for five minutes, 5 ml. of a saturated solution of ferric ammonium sulfate shall be added and the solution titrated with standardized 0.1 N potassium thiocyanate solution to the first permanent pale rose coloration. The percentage of lead thiocyanate in the sample shall be calculated on a dry basis as follows:

Percent lead thiocyanate = 16.17 (AE - CD) divided by B

where:

A = volume of silver nitrate solution used
B = Weight of the sample after acetone extraction (See 4.5.5.2).
C = volume of the potassium thiocyanate solution used.
D = normality of potassium thiocyanate solution.
E = normality of the silver nitrate solution.

4.5.5.4 Potassium chlorate. - The percent of potassium chlorate shall be determined by subtracting the total percentage of charcoal and lead thiocyanate from one hundred percent.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level C. - The igniters shall be preserved and packaged in accordance with dwg. 8850245.

*5.1.2 Level C. - The igniter parts shall be packaged in accordance with MIL-STD-1169 requirements.

5.2 Packing

5.2.1 Level C. - The igniters shall be packed in accordance with dwg. 8850246.

*5.2.2 Level C. - The igniter parts shall be packed in accordance with MIL-STD-1169 requirements.

*5.3 Marking. - Igniter containers and bags shall be marked in accordance with instructions contained in dwgs. 8850245 and 8850246. Igniter parts containers shall be marked in accordance with MIL-STD-1169 requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Provisions for submission of first article samples.
c. Provisions of MIL-A-48078.

6.2 Submission of inspection equipment designs for approval (See MIL-A-48078). Submit equipment designs as required, to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T Dover, New Jersey 07801.

6.3 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M Dover, New Jersey 07801.

6.4 Check test for possible deterioration. - The following test is designed to prevent igniters that have deteriorated from being assembled into major ammunition items. The test shall be performed on igniters from each lot which have been stored under normal conditions for more than two years or under adverse conditions for any period of time. If the specification for the ammunition item into which the igniters are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract a provision for the performance of the check test. The Contracting Officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration. Igniter assemblies shall be selected from each lot for this test.

*6.4.1 Functioning. - One hundred and twenty-five (125) igniters shall be selected from the lot and subjected to the test specified in 4.5.3. If two (2) or more igniters fail to comply with the requirement the lot shall be rejected.

*6.4.2 Non-functioning.- Eighty (80) igniters shall be selected from the lot and subjected to the test specified in 4.5.4. If any igniter functions the lot shall be rejected.

*6.4.3 Electrical resistance. - Each igniter in the lot shall be tested as specified in 4.5.2. Any igniter that fails to comply with the requirement shall be classed defective and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

6.5 Determination of ignition charge composition. - During the manufacture of the ignition charge composition up to two parts of solvent are added to one part of Egyptian lacquer in order to facilitate the blending of the mixture. Because of the volatility of the solvent, the solvent content of the ignition charge composition is found to be a variable. Because of this the determination of the potassium chlorate, lead thiocyanate and charcoal content are determined on a lacquer free basis and the lacquer solids on added basis.

6.6 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.7 Supersession data. - This specification includes the requirements of MIL-I-46435B (MU) dated 30 July 1968.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-129

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

2616

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil - Downloaded: 2026-10-22T05:57
Check the source to verify that this is the current version before use.