NOT MEASUREMENT SENSITIVE

MIL-B-10955/13F
20 December 1994
SUPERSEDING
MIL-B-10955/13E
13 September 1991

MILITARY SPECIFICATION SHEET

# BADGE, QUALIFICATION, AVIATION, FLIGHT SURGEON, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-10955.



DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated (Red Brass only), Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

DIMENSIONS:

HEIGHT (Overall):
-1: 15/16 inch (2.38 cm) (REF)
-2: 5/8 inch (1.59 cm) (REF)

WIDTH (Overall):
-1: 3 inches (7.62 cm) (REF)
-2: 2 inches (5.08 cm) (REF)

THICKNESS (At Thickest Point of Wings):
-1: 0.135 inch ± 0.005 inch (0.342 cm ± 0.012 cm)
-2: 0.095 inch ± 0.005 inch (0.241 cm ± 0.012 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:42Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong and clutch type. The prongs shall be located on the horizontal center line, equidistant from each end and the following distance apart.

   Dash No. 1: 2 inches ± 1/32 inch (5.08 cm ± 0.08 cm)
   Dash No. 2: 1-1/2 inches ± 1/32 inch (3.81 cm ± 0.08 cm)

3. A mock forcer may be used to bring up the design of the shield and ridge line of the wings only.

Custodian:
Army - IH
Air Force - 45

Review activities:
Air Force - 32, 82, 99
DLA - CT

Preparing activities:
Army - IH

(Project No. 8455-0788)



Source: https://assist.dla.mil - Downloaded: 2026-10-17T14:42Z
Check the source to verify that this is the current version before use.