NOT MEASUREMENT SENSITIVE

MIL-B-10955/2G
16 April 1991
SUPERSEDING
MIL-B-10955/2F
21 April 1987

MILITARY SPECIFICATION SHEET

Badge, Qualification, Aviation; Senior Army Aviator

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-10955.



Pierced (-1, -2, -4 only)

MATERIAL:
-1, -2, -3: Red brass or nickel silver
-4: Red brass

DIMENSIONS:
HEIGHT (Overall):
-1,-4: 27/32 inch (2.14 cm) (REF)
-2: 11/16 inch (1.75 cm) (REF)
-3: 13/32 inch (1.03 cm) (REF)

WIDTH (Overall):
-1,-4: 2-1/2 inches (6.35 cm) (REF)
-2: 2 inches (5.08 cm) (REF)
-3: 1-1/4 inch (3.18 cm) (REF)

THICKNESS (At Thickest Point of Wings):
-1,-4: .110 inch ± .010 inch (0279 cm ± 0.025 cm)
-2,-3: .085 inch ± .005 inch (0.215 cm ± 0.012 cm)

FINISH:
-1,-2,-3: Nickel plated (Red brass only), silver plated , oxidized, relieved, satin finish with the highlights of the shield mirror-like polished
-4: Dull, flat black enamel finish

DASH NO:
-1: Regular size
-2: Miniature size
-3: Dress miniature
-4: Regular size, subdued

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:40Z
Check the source to verify that this is the current version before use.

NOTES:

1. Attaching device shall be prong and clutch type. The prongs shall be located on the horizontal centerline, equidistant from each end and the following distance apart:

Dash No. 1 and 4:	1-3/4 inch ± 1/32 inch (4.45 cm ± 0.08 cm)
Dash No. 2:	1-1/2 inch ± 1/32 inch (3.81 cm ± 0.08 cm)
Dash No. 3:	7/8 inch ± 1/32 inch (2.22 cm ± 0.08 cm)

2. A mock forcer may be used to bring up the design of the shield for Dash No. 1, 2 and 4 only.

3. Dash No. 1, 2 and 3 may be nickel or rhodium plated with a mirror-like polished finish for commercial sale except the silver plating requirement shall not apply.

Custodian:
Army - IH

Review Activity:
DLA - CT

Preparing Activity:
Army - IH

(Projected No. 8455-A585)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:40Z
Check the source to verify that this is the current version before use.