METRIC

A-A-55447
14 JUNE 1995

# COMMERCIAL ITEM DESCRIPTION

## FLASHLIGHT, MANUALLY OPERATED MINI-GENERATOR

The General Services Administration has authorized the use of this Commercial Item Description as a replacement for the type A-9 flashlight of MIL-F-8209B for all federal agencies.

1. SCOPE.

1.1. Intended use. The flashlight is intended for use on aircraft emergency life rafts and for other emergency applications to provide a small sturdy beam of light where reliance on conventional battery powered light sources are not desirable. This item is not designed for operation in explosive or potentionally explosive atmospheres.

2. SALIENT CHARACTERISTICS

2.1. Design and construction. The flashlight shall consist of a manually operated electrical generator which provides power for a Single Contact (SC) Mini Flanged size B-3 1/2 incandescent lamp. The lamp shall be positioned within a parabolic reflector so as to produce a narrow beam of light. The lamp and reflector shall be covered by a shatterproof lens. The flashlight body shall fit comfortably in the palm of the hand and complete operation shall be possible using only one hand, leaving the operators other hand free to accomplish other tasks. Lamp replacement shall not require the use of any tools.

2.1.1 Operating force. The force required to operate the generator mechanism shall not exceed 3.6 kilograms at the maximum rated output voltage for the flashlight.

2.1.2. Weight. The weight of the flashlight shall not exceed 370 grams.

2.1.3. Dimensions. The flashlight shall fit into a box (rectangular solid) having dimensions not exceeding 150mm X 60mm X 80mm.

2.1.4. Light beam. The flashlight shall project a concentrated beam of light not less than 120mm nor more than 250mm in diameter when located 1.5m from a screen, the plane of which is perpendicular to the optical axis of the flashlight.

2.1.5. Light intensity. Light emitted shall be not less than 20 candelas, 2 degrees wide or 40 candelas 1 degree wide, in either of two planes perpendicular to each other and passing through the axis of symmetry of the lamp head.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Defense General Supply Center (DGSC), ATTN: DGSC-VCA, 8000 Jefferson Davis Highway, Richmond, VA 23297-5768.

AMSC N/A FSC 6230

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.

2.1.6 Rough handling. The flashlight shall withstand an impact equivalent to a 1m free fall onto a vinyl tiled concrete surface without external damage or any loss of function associated with the electrical power generating mechanism.

2.2. Workmanship. All components and assemblies shall be free of dirt and other extraneous materials. Burrs, slivers, rough die, tool, and grinding marks, dents, and cracks shall be unacceptable. Castings, molded parts and stampings, shall be free of sand, fins, pits, blow holes, and sprues. The surfaces of parts to be welded or brazed shall be clean. All scale and flux shall be removed from the finished weld area. The welds shall be smooth. Threaded fasteners shall not be missing, broken, cracked, or stripped of threads. There shall be no defects affecting serviceability, durability, operation or appearance.

## 3. REGULATORY REQUIREMENTS.

3.1. Recovered materials. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum practical extent. Recycled or reclaimed materials may be used in the construction of the equipment described herein. Recycled and reclaimed materials shall consist of previously used material which has been reprocessed to become a source of new raw materials. Under no conditions or circumstances shall the contractor submit to the Government for acceptance reconditioned or rebuilt components as a part of the equipment described herein.

## 4. QUALITY ASSURANCE PROVISIONS.

4.1 Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same as the product offered for sale in the commercial marketplace. When specific quality assurance provisions are specified for any commercial characteristic the contractor shall maintain records resulting from his inspection(s) conducted in accordance with the specific quality assurance provisions. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided under the provisions of the contract. The government reserves the right to audit the contractor's quality assurance records.

4.2. Successful commercial operation. No item of equipment offered under this CID shall be acceptable unless the manufacturer has marketed equipment of the same size (similar capacity) and type in a commercial environment for a minimum period of one year. Equipment installed for test purposes in a manufacturer's plant or test laboratory shall not be considered as complying with this requirement.

4.3 Warranty. Unless otherwise specified in the contract, the manufacturer's standard commercial warranty terms shall apply.

## 5. PACKAGING.

5.1. Preservation, Packaging, Packing, Labeling and Marking. Preservation, packaging, packing, labeling and marking shall be as specified in the contract or purchase order.

5.1.1. Commercial. In the absence of detailed instructions in the contract or purchase order, preservation and packing shall be in accordance with ASTM D 3951, Standard Practice for Commercial Packaging.



Source: https://assist.dla.mil -- Downloaded: 202610-26T09:47Z
Check the source to verify that this is the current version before use.

## 6. NOTES.

6.1. Commercial item certification. When this CID is used for procurement, the commercial item certification clause must appear in the solicitation.

6.2. Referenced documents. Copies of referenced documents are available from:

Government documents:
Standardization Documents Order Desk
700 Robbins Avenue
Building 4, Section D
Philadelphia, PA 19111-5094

Non-government documents:
ASTM D 3951 may be obtained from:

ASTM
1916 Race Street
Philadelphia, PA 19103

6.3. U.S. Customary product. Products manufactured to inch-pound units of measure will be considered on an equal basis with those manufactured using metric (SI) units of measure, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard 376, and all other requirements of this CID are met.

6.5. Sources of supply. Equipment described herein can be procured from the following sources:
Tek-lite Inc., Union Bridge, MD 21791
Jobar International, Inc., Inglewood, CA 90301-1126
Real Goods Inc., Ukiah, CA 95482-5507
Rush Industries Inc., Albertson, NY 11507

6.6. Subject term (key word) list.
Flashlight, hand generated, no batteries

MILITARY INTERESTS:

Custodians
Air Force - 99
Army - ME
Navy - AS

Review activities

Navy - YD
Air Force - 82

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS/7FXE

PREPARING ACTIVITY:

DLA - GS

(Project 6230-1041)



Source: https://assist.dla.mil -- Downloaded: 202640-26T09:47Z
Check the source to verify that this is the current version before use.