
COMMERCIAL ITEM DESCRIPTION

CONNECTORS, ELECTRICAL, POWER, CRIMP TO WIRE, SOLID PIN

The General Services Administration has authorized the use of this commercial item description (CID)

Abstract This CID covers the general requirements for connector, electrical, power, crimp to wire, solid pin This pin can be used in applications that require crimp to discrete stranded wires, size 14 AWG through 24 AWG Pins covered by this CID are intended for commercial/industrial applications and shall not be used in military systems needing stringent environmental and electrical requirements

Part or Identifying Number (PIN) The PIN for the CID shall be as shown in the following example



Salient characteristics

CID sheet The electrical connectors shall be in accordance with the requirements specified herein

Design, construction, and dimensions Design, construction, and dimensions shall be as specified on figure 1 and table I

Operating temperature The operating temperature range shall be from -55°C to 105°C

Contact material. Contact material shall be of brass or phosphor bronze

Plating Plating shall be pre-tin or 76 micron (30 microinches) minimum localized gold in contact area, over 1.27 microns (50 microinches) minimum of nickel

Mating force Connector mating force shall not exceed 13.34 newtons (3 0 pounds)

Unmating force Connector unmating force shall not exceed 3 11 newtons (0 7 pound) minimum


Contact insertion Contact insertion force shall be 8 90 newtons (2 pounds) maximum per contact

Contact retention Contact retention force shall be 66 72 newtons (15 pounds) minimum

Durability Durability shall consist of 50 cycles of mating and unmating and upon completion the termination resistance, dry circuit, shall not exceed 3.6 milliohms There shall be no indication of physical damage

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited


Source: https://assist.dla.mil -- Downloaded: 202640-26T09:47Z
Check the source to verify that this is the current version before use.



Loose piece configuration A

Figure 1. Dimensions and configurations

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:47Z
Check the source to verify that this is the current version before use.



NOTES:

1. Dimensions are in inches.
2. Millimeters are in parentheses.
3. This item was designed using inch-pound units of measurement. In case of problems involving conflicts between the metric and inch-pound units, the inch-pound units shall rule.
4. Plated with 30 microinches (.76 micron) of gold, over 50 microinches (1.27 microns) of nickel underplate.
5. Plated inside wire barrel with 30 microinches (.76 micron) of gold, over 50 microinches (1.27 microns) minimum of nickel under plate.
6. Unless otherwise specified tolerances are ±.015 inches (±.38 millimeter).

Strip configuration B

Figure 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:47Z
Check the source to verify that this is the current version before use.

Table II Solid pin - loose piece configuration A

CID dash number	Wire gage	Insulation range diameter	Wire barrel height A-A width height	Insulation barrel Height B-B width height
A-A-55468-01	24-18	040- 100	110/ 085 105/ 080	145/ 120 150/ 125
A-A-55468-02	24-18	040- 100	110/ 085 105/ 080	145/ 120 150/ 125
A-A-55468-03	24-18	040- 100	110/ 085 105/ 080	145/ 120 150/ 125
A-A-55468-04	24-18	040- 100	110/ 085 105/ 080	145/ 120 150/ 125
A-A-55468-05	20-14	060- 130	130/ 105 145/ 120	170/ 145 190/ 165
A-A-55468-06	20-14	060- 130	130/ 105 145/ 120	170/ 145 190/ 165
A-A-55468-07	20-14	060- 130	130/ 105 145/ 120	170/ 145 190/ 165
A-A-55468-08	20-14	060- 130	130/ 105 145/ 120	170/ 145 190/ 165
A-A-55468-09	20-14	060- 130	130/ 105 145/ 120	170/ 145 190/ 165
A-A-55468-10	20-14	130- 200	130/ 105 145/ 120	240/ 215 240/ 215
A-A-55468-11	20-14	130- 200	130/ 105 145/ 120	240/ 215 240/ 215
A-A-55468-12	20-14	.130- 200	130/ 105 145/ 120	240/ 215 240/ 215
A-A-55468-13	20-14	130- 200	130/ 105 145/ 120	240/ 215 240/ 215
A-A-55468-14	20-14	130- 200	130/ 105 145/ 120	240/ 215 240/.215

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:47Z
Check the source to verify that this is the current version before use.

Table III Solid pin - strip configuration B

CID dash number	Wire gage	Insulation range diameter	Wire barrel height A-A width height	Insulation barrel Height B-B width height
A-A-55468-15	24-18	040- 100	105/ 090 100/ 085	140/ 125 145/ 130
A-A-55468-16	24-18	040- 100	105/ 090 100/ 085	140/ 125 145/ 130
A-A-55468-17	24-18	040- 100	105/ 090 100/ 085	140/ 125 145/ 130
A-A-55468-18	24-18	040- 100	105/ 090 100/ 085	140/ 125 145/ 130
A-A-55468-17	20-14	060- 130	130/ 105 145/ 120	170/ 125 /190/ 165
A-A-55468-18	20-14	060- 130	130/ 105 .145/ 120	170/ 125 190/ 165
A-A-55468-19	20-14	060- 130	130/ 105 145/ 120	.170/ 125 190/ 165
A-A-55468-20	20-14	060- 130	130/ 105 145/ 120	170/ 125: 190/ 165
A-A-55468-21	20-14	060- 130	130/ 105 145/ 120	170/ 145/ 190/ 165
A-A-55468-22	20-14	130-.200	.125/ 110. 133 ref	235/.220 .230 ref
A-A-55468-23	20-14	130- 200	125/.110:.133 ref	235/.220 230 ref
A-A-55468-24	20-14	130- 200	125/ 110 133 ref	235/ 220· 230 ref
A-A-55468-25	20-14	130- 200	125/ 110 133 ref	235/ 220 230 ref
A-A-55468-26	20-14	130- 200	125/ 110 133 ref	235/ 220 230 ref

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.

Crimp tensile strength The crimp tensile strength of the wire-to-contact termination shall not be less than the value specified in table III when tested at a cross-head parting speed of 25 millimeters (1 inch) per minute, maximum

Table III Crimp tensile strength

Wire size (AWG)	Tensile strength kilograms (pounds)
24	3 63 (8)
22	6 35 (14)
20	6 35 (14)
18	13 61 (30)
16	20 41 (45)
14	22 68 (50)

Dielectric withstanding voltage There shall be no breakdown of the insulating material when subjected to 5000 V ac for one minute between adjacent contacts of the mated connector assemblies

Vibration The connector, or hardware when assembled to the connector, shall exhibit no evidence of breaking, cracking, or loosening of parts when subjected to vibration of 10-55-10 HZ traversed in 1 minute at 1.5 millimeters (06 inch) total excursion for 2 hours in each of three mutually perpendicular planes The contacts shall evidence no discontinuity greater than 10 microseconds and termination resistance, dry circuit, 5 0 milliohms maximum

Physical shock The connector, or hardware when assembled to the connector, shall be subjected to 50 G's at 10 milliseconds, 3 shocks in each direction applied along the three mutually perpendicular planes, total 18 shocks The contacts shall evidence no discontinuity greater than 10 microseconds and the termination resistance, dry circuit, not to exceed 6.0 milliohms

Thermal shock The connector, when mated, shall be subjected to 25 cycles between -55°C and 85°C. dielectric withstanding voltage, 3 75 milliohms maximum termination resistance, dry circuit

Temperature-Humidity cycling The connector, when mated, shall be subjected to temperature-humidity cycling between 25°C and 65°C at 95 percent RH, with cold shock at -10°C during any 5 of the first 9 cycles

Corrosion Corrosion shall be 48 hours at 5 percent salt concentration After exposure of the unmated connectors, the termination resistance dry circuit will not exceed 7 0 milliohms

Regulatory requirements This section is not applicable to this CID

Quality assurance provisions

Responsibility for inspection Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection, examination, and test requirements specified herein Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the inspection requirements specified herein, unless disapproved by the Government The Government reserves the right to perform any of the inspections, examinations, or tests set forth in this description where such inspections, examinations, and tests are deemed necessary to assure supplies and services conform to prescribed requirements

Contractor certification statement The contractor shall certify and maintain objective quality evidence that the product offered meets the requirements of this CID, and that the product conforms to the producer's own drawings, specifications, standards, quality assurances practices, and is the same as the product provided as a bid sample The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.

Certificate of compliance A certificate of compliance shall accompany all parts supplied to this CID

Packaging

Preservation, packaging, packing, labeling, and marking Preservation, packaging, labeling, and marking shall be as specified in the contract or purchase order

Notes This section contains relevant information which is useful to buyers, users and suppliers in the process of procuring the item, but is not mandatory

Ordering data Acquisition documents should specify the following

a CID document number and revision and CID PIN

b Quality assurance provisions

c Packaging requirements

d Color (if applicable)

Comments Comments on this CID should be directed to Defense Electronics Supply Center, 1507 Wilmington Pike, ATTN DESC-ELDI, Dayton, OH 45444-5270, or telephone (513) 296-5391

Sources of supply A suggested source of supply is listed in table IV Additional sources will be added as they become available

Table IV Suggested sources of supply

Solid pin - loose piece ordering data							
CID dash number	Vendor commercial PIN	Figure number 1, configuration	Wire gauge	Base material	Overplate	Under plate	Vendor CAGE Number
A-A-55468-01	350690-1	A	24-18	Brass	Pre-tin	---	00779
A-A-55468-02	350690-2	A	24-18	Brass	Gold 1/	Nickel	00779
A-A-55468-03	350690-3	A	24-18	Ph Br	Pre-tin	---	00779
A-A-55468-04	350690-7	A	24-18	Brass	Gold 2/	Nickel	00779
A-A-55468-05	350547-1	A	20-14	Brass	Pre-tin	---	00779
A-A-55468-06	350547-2	A	20-14	Brass	Gold 1/	Nickel	00779
A-A-55468-07	350547-3	A	20-14	Ph Br	Pre-tin	---	00779
A-A-55468-08	350547-6	A	20-14	Ph Br	Gold 2/	Nickel	00779
A-A-55468-09	350547-7	A	20-14	Brass	Gold 2/	Nickel	00779
A-A-55468-10	350552-1	A	20-14	Brass	Pre-tin	---	00779
A-A-55468-11	350552-2	A	20-14	Brass	Gold 1/	Nickel	00779
A-A-55468-12	350552-3	A	20-14	Ph Br	Pre-tin	---	00779
A-A-55468-13	350552-6	A	20-14	Ph Br	Gold 2/	Nickel	00779
A-A-55468-14	350552-7	A	20-14	Brass	Gold 2/	Nickel	00779

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.

Table IV Suggested sources of supply - continued

Solid pin - strip ordering data							
CID dash number	Vendor commercial PIN	Figure number 1, configuration	Wire gauge	Base material	overplate	Under plate	Vendor CAGE Number
A-A-55468-15	350561-1	B	24-18	Brass	Pre-tin	---	00779
A-A-55468-16	350561-2	B	24-18	Brass	Gold 1/	Nickel	00779
A-A-55468-17	350561-3	B	24-18	Ph Br	Pre-tin	---	00779
A-A-55468-18	350561-7	B	24-18	Brass	Gold 2/	Nickel	00779
A-A-55468-19	350218-1	B	20-14	Brass	Pre-tin	---	00779
A-A-55468-20	350218-2	B	20-14	Brass	Gold 1/	Nickel	00779
A-A-55468-21	350218-3	B	20-14	Ph Br	Pre-tin	---	00779
A-A-55468-22	350218-6	B	20-14	Ph Br	Gold 2/	Nickel	00779
A-A-55468-23	350218-7	B	20-14	Brass	Gold 2/	Nickel	00779
A-A-55468-24	350538-1	B	20-14	Brass	Pre-tin	---	00779
A-A-55468-25	350538-2	B	20-14	Brass	Gold 1/	Nickel	00779
A-A-55468-26	350538-3	B	20-14	Ph Br	Pre-tin	---	00779
A-A-55468-27	350538-6	B	20-14	Ph Br	Gold 2/	Nickel	00779
A-A-55468-28	350538-7	B	20-14	Brass	Gold 2/	Nickel	00779

1/ Plated with 30 microinches (76 micron) of gold in mating area and inside wire barrel over 50 microinches (1 27 microns) minimum nickel underplate on entire contact

2/ Plated with 30 microinches (76 micron) minimum of gold in mating area over 50 microinches (1 27 micron) minimum nickel underplate on entire contact

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:47Z
Check the source to verify that this is the current version before use.

Supersession data Supersession data shall be as specified in table V

Table V Supersession data

Superseded (old) PIN 87101-	Superseding (new) PIN A-A-55468-	Superseded (old) PIN 87101-	Superseding (new) PIN A-A-55468-
021	01	009	15
N/A	02	N/A	16
022	03	010	17
024	04	012	18
N/A	05	N/A	19
N/A	06	N/A	20
N/A	07	N/A	21
N/A	08	N/A	22
N/A	09	N/A	23
017	10	005	24
N/A	11	N/A	25
018	12	006	26
019	13	007	27
020	14	008	28

Vendor CAGE number	Vendor name and address
00779	AMP Incorporated P O Box 3608 Road Harrisburg, PA 17105-3608

CIVIL AGENCY COORDINATING ACTIVITY

GSA - 7FXE

PREPARING ACTIVITY

DLA-ES

(Project 5935-0525)

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:47Z
Check the source to verify that this is the currentversion before use.